

COMPACT UTILITY MODEL 4200 SERIES



Quick set-up with hoses and couplers included



Blade Carrier Assembly



Reinforced Gussets

4200 Performance

- Easily maneuvers through tight spaces.
- Tough and light weight with the power to mow brush and cut saplings up to 3".
- Long-lasting durability with the deck formed from one piece of steel.
- Runs on all compact utility models.
- Reinforced gussets provide safety and stability.
- The 4800 LF Model is a possibility for compact equipment. It will depend upon your equipments weight restrictions and auxiliary hydraulic flow requirements to determine if compatible.
- Always operate with safety glasses and a hard hat.
- Compact/Mini walk-behind options; Toro Dingo, Ditch Witch, Bobcat MT-50, etc.

• Three year warranty on the structural steel.

Toll free: 877-390-9857

SPECIFICATIONS	4200
Cutting Width:	42.000
Overall Width:	43.750
Overall Length:	58.250
Blade Carrier Type:	1.000 High Strength Steel Bar
Blades:	(2) .500 x 4.000 (Updraft)
Blade Rotation:	Counter Clockwise
Drive Protection:	GRD-2 Bolt (Shear Bolt)
Motor / Gearbox Coupler:	Machined Steel
Motor Protection:	Pressure Reliefs
Deck Thickness:	10 Gauge One Piece of Formed Steel
Hydraulic Hose with Protective Wrap*:	66.000
Flat Face Coupling*:	STANDARD
Gearbox Seal Guard:	
Cutting Capacity Maximum:	3"
Required GPM:	8 - 20
PSI MIN/MAX:	3000/3500
Weight:	469 lbs.

*Custom sizes and lengths available upon request.