



# Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0  
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122  
[husky@huskyfarm.ca](mailto:husky@huskyfarm.ca) [www.huskyfarm.ca](http://www.huskyfarm.ca)



## 15000L Galvanized

4000 US Gal., 3300 CDN Gal., 15000 Litres

### 21.5L x 16.1, 14 Ply

1844 sq. in. on ground @ 35 PSI

Rib implement type

111 " (2881 mm)

122" (3740 mm)

125" inches optional 4 ft

7,288 lbs (3,312 kg)

40,608 lbs (18,454 kg)

90" (2286 mm)

70" (1778 mm)

15 ft (4.57 m)

Flanged and reinforced

3/16" (4.5 mm)

1

4"x 8" boxed tubing 1/4" material

Single or double, height adjustable

5000 LB

Adjustable

64000 lbs (29350 kg)

4" C1045

10 bolt, 11.1/4" bolt circle, 8 5/8" pilot hole, hub greaseable

Drop axle 120"

5 year unconditional (non commercial)

Standard

### 28L x 26, 12 Ply

3744 sq. in. on ground @ 24 PSI

Knobby turf type

113.5 " (2881 mm)

149.5" (3797 mm)

127" optional 4 ft

9,260 lbs (4,209 kg)

42,580 lbs (19,354 kg)

Compaction

Tire type

Overall height

Overall width

Discharge height

Empty

Loaded

Tank width

Tank height

Tank length

Tank ends

Tank shell thickness

Number of baffles

Tongue type and thickness

Hitch

Tongue jack

Draw bar weight

Axle capacity

Axle spindle size & material

Hub bolt pattern 10 bolt, 11.1/4" bolt circle, 8 5/8" pilot hole, hub greaseable

Axle width flange to flange

Axle warranty

Light kit ( brake & tail)

### Standard Features

Bearings Tapered roller

Seals Double lip grease purge able

PTO Constant velocity shear protected 1 3/8 6 T,

1 3/8 21T, 1 3/4 20T

Size of discharge 6"

Spreading pattern Up to 60 ft, 18 m

Discharge height 106", 2692 mm optional 4 ft

Unloading speed 6" discharge Up to 2400 gallon

per minute adjustable

Painting preparation Steamed with phosphate

Paint primed Epoxy

Paint finish coat Urethane

Inside coating Aluminized epoxy

Axle warranty 5 year unconditional

Light kit ( brake & tail) Standard

Unloading pump 4 blade fan type

Draw bar weight Adjustable

Walking tandem Axle

Seams welded solid inside

U shape, 1/4" Sill

6 square ft Padding to tank contact

4"x 8" boxed tubing 1/4" material on tongue

73" Tongue



### Options For Your Husky Tank

8" Discharge Unloading Up to 3600 gallon per minute adjustable

Hydraulic drive

Butterfly Lid

Clean Out

Camels Hump

Pipe Down the back

Sight Gage

Swing Away Fan

Slide Lid

Square Man Hole

Cut Outs

High Speed Tires

Steering

In tank Agitation

Valves

1000 RPM Unload

Low Spread

Single Hitch