

6000 US Gal., 5000 CDN Gal., 23000 Litres

30.5L x 32, 12 Ply

Compaction Tire pressure Tire type Overall height Overall width Tank width Tank height Tank length Tank ends Tank shell thickness Number of baffles Distance sills apart Hitch Tongue jack Axle weight (less tires) Axle capacity Axle warranty Axle spindle size & material Hub bolt pattern Empty Loaded





Standard Features Bearings Tapered roller Seals Double lip grease purge able PTO Constant velocity shear protected 1 3/8 6 T, 1 3/8 21T, 1 3/4 20T Size of discharge 6" Spreading pattern Up to 60 ft, 18 m Discharge height 106", 2692 mm optional 4 ft Unloading speed 6" discharge Up to 2400 gallon per minute adjustable Painting preparation Steamed with phosphate Paint primed Epoxy Paint finish coat Urethane Inside coating Aluminized epoxy Axle warranty 5 year unconditional Light kit (brake & tail) Standard Unloading pump 4 blade fan type Draw bar weight Adjustable Walking tandem Axle Seams welded solid inside U shape, 1/4" Sill 10 square ft Padding to tank contact 4"x 8" boxed tubing 1/4" material on tongue 75" Tongue

Options For Your Husky Tank

8" Discharge Unloading speed Up to 3600 gallon per minute adjustable Hydraulic drive Butterfly Lid Clean Out Camels Hump Pipe Down the back Sight Gage Swing Away Fan 1000 RPM Unload Low Spread

4508 sq. in. on ground

Turf type, knobby tread

Flanged and reinforced

1/4" high strength steel

Single or optional double hitch

5 1/2" stress proof HT SR slid in 6 1/2" sleeve

10 bolt, 13.19" bolt circle, hub greaseable

2 full baffles

4432 lbs, 2009 kg

100,000 lbs, 45,351 kg

17,500 lbs (7,936 kg)

67,500 lbs (30,612 kg)

5 year (non commercial)

24/30 lbs

148"

128" 101"

95"

20 ft

54"

8000 lbs

All Figures Are Approximate, Limited Warranty (3Months For Custom Operators), No Warranty On Sand Bedding. For Full Details and Exact Figures, Please Confirm With Husky. 1-800-349-1122