

## Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca



## 23000L Vacuum

6000 US Gal., 5000 CDN Gal., 23000 Litres 28L x 26, 12 Ply 30.5L x 32, 12 Ply





Compaction 3744 sq. in. on ground 4508 sq. in. on ground w/ 3" penetration
Overall height 120" 125"
Overall width 163" Standard

 Discharge height
 136", optional 4 ft
 141" optional 4 ft

 Empty
 16,537 lbs (7,516 kg)
 16,960 lbs (7,693 kg)

 Loaded
 66,517 lbs (30,235 kg)
 66,940 lbs (30,364 kg)

Tire pressure 24 lbs

Tire type Turf type, knobby tread

Tank width 100"
Tank height 78"
Tank length 19.25 ft
Number of baffles 2 full baffles

Hitch Single or optional double hitch

Tongue jack 8000 lbs

Axle weight (less tires) 4432 lbs, 2010 kg
Axle capacity 100,000 lbs, 45,360 kg
Axle warranty 5 year (non commercial)

Axle spindle size & material 5 1/2" stress proof slid in 6 1/2" sleeve Hub bolt pattern 5 1/2" stress proof slid in 6 1/2" sleeve 10 bolt, 13.19" bolt circle hub greaseable

1/4" (6.35 mm) tank shell high strength steel

1/4" Tank ends flanged and dished Full Baffle welded inside and out Sight gauge standard front drivers side 24" rear access hatch, 6" hydraulic discharge 6" manual side valve

15 feet 6" suction hose with Bauer ends

Primary and secondary moisture trap with 6" stainless ball

3" (75 MM) air intake and outlet lines

10 Year rust out warranty

High speed vacuum pumps air cooled High heat vanes / air cooled / 540/ 1000



## Standard Features

PTO Constant velocity shear protected 1 3/8 6

T, 1 3/8 21T, 1 3/4 20T Size of discharge 6"

Painting preparation Steamed with phosphate

Paint primed Epoxy
Paint finish coat Urethane
Inside coating Aluminized epoxy
Axle warranty 5 year unconditional
Light kit ( brake & tail) Standard
Draw bar weight Adjustable
Walking tandem Axle
Seams welded solid inside

U shape, 1/4" Sill

10 square ft Padding to tank contact

4"x 8" boxed tubing 1/4" material on tongue

75" Tongue

Options For Your Husky Tank

Hydraulic drive

Valves

1000 RPM Unload

Single Hitch

Hvdraulic lid

Vacuum pumps 6 sizes to choose from 30 " Domed manhole

