

Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca



27500L Tri Axle



30.5L x 32, 12 Ply, Optional 35.5 x 32

Compaction 4508 sq. in. on ground Tire pressure 26/30 lbs

Tire pressure 26/30 lbs
Tire type Turf type, knobby tread

Tank ends Flanged and reinforced
Tank shell thickness 1/4" high strength steel
Number of baffles 2 full baffles

Inside coating Aluminized epoxy
Light kit (brake & tail) Standard

Light kit (brake & tail) Standa
Seams welded solid inside Yes

Sill style & thickness U shape, 1/2" material, 3/4" over axle

Padding - sills to tank contact 12 square ft

Tongue type and thickness 4" x 8" rectangular tubing 3/8" material

Hitch Single or optional double hitch

Tongue jack 8000 lbs

Unloading pump Fan type with high efficiency blades

RPM 1000, optional 540 RPM

Hydraulic drive Optional

Bearings Timken taper, grease filled chamber

Seals Double seals, purgeable

PTO Constant velocity, shear protected 1 3/8 6T, 1 3/8 21T, 1 3/4 20T

Hydraulic drive Optional Size of discharge 6", 8" optional

Unloading speed 6" discharge Up to 2400 gallon per minute adjustable Unloading speed 8" discharge Up to 3600 gallon per minute adjustable

Spreading pattern Up to 60 ft
Discharge height 135" optional 4 ft
Axle type Walking tandem
Axle weight (less tires) 4432 lbs, 2009 kg

Axle capacity

Axle warranty 5 year (non commercial)

Hub bolt pattern 10 bolt, 13.19" bolt circle, 11 1/16 pilot hole, hub greaseable Painting preparation Steamed with phosphate Paint primerAluminized epoxy acid resistant

Paint finish coat Urethane acid resistant

Empty 24,0004 lbs Loaded 94,000 lbs



Overall Height 3672mm 144.5" Overall Width 3404mm 134"

Overall Length 11412mm 449.25" 37.5ft

(With Inside Agitation) Tank Width2565mm 101" Tank Height 1920mm 75.5" Tank Length 8282mm 326" 27ft

Number Of Baffles 4

Sill Out Side Dimension 1372 mm Tongue Length 1905mm 75"

> Options For Your Husky Tank 8" Discharge Unloading speed Up to 3600 gallon per minute adjustable Hydraulic drive

Butterfly Lid Clean Out Camels Hump Pipe Down the back Sight Gage In tank Agitation

Valves

1000 RPM Unload Low Spread Single Hitch



