



Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca



HUSKY 9000 ELITE

2400 US Gal., 2000 CDN Gal., 9000 Litres

Compaction	1208 sq. in. on ground
Overall height	92 " (2337 mm)
Overall width	97.75" (2482 mm)
Discharge height	106" 2692 mm
Optional Discharge height	4 ft Low Spread
Empty	5,354 lbs (2,433 kg)
Loaded	25,350 lbs (11,522 kg)

Tank Width	74" (1879 mm)
Tank Height	58" (1473 mm)
Tank Length	14 ft (4.32m)
Tank ends	Flanged
Tank shell thickness	3/16" (4.5 mm)
Number of baffles	1
Tire pressure	35 PSI
Tire type	Rib implement type
Hitch	Single or double, height adjustable
Tongue jack	5000 lbs
Draw bar weight	Adjustable
Size of discharge	6", 8" optional
Unloading speed 8" discharge	Up to 3600 gallon per minute adjustable
Axle capacity	32000 lbs
Axle spindle size & material	2 3/4" SPS stress proof material
Hub bolt pattern	8 bolt, 8" bolt circle, 6" pilot hole
Axle width flange to flange	Straight axle 82.25"
Hub greaseable	No
Axle warranty	5 year unconditional (non commercial)

Compaction	1844 sq. in. on ground
Overall height	93.75 " (2381 mm)
Overall width	103.25." (2622 mm)
Discharge height	107.75" 2737 mm
Optional Discharge height	4 ft Low Spread
Empty	5,670 lbs (2,577 kg)
Loaded	25,662 lbs (11,664 kg)



Options For Your Husky Tank

- Hydraulic drive
- Butterfly Lid
- Clean Out
- Camels Hump
- Pipe Down the back
- Sight Gage
- Swing Away Fan
- Slide Lid
- Square Man Hole
- Cut Outs
- High Speed Tires
- In tank Agitation
- Valves
- 1000 RPM Unload
- Low Spread
- Single Hitch
- 8" Discharge

Standard Features

- Bearings Tapered roller
- Seals Double lip grease purge able
- PTO Constant velocity shear protected 1 3/8 6 T, 1 3/8 21T, 1 3/4 20T
- Size of discharge 6"
- Spreading pattern Up to 60 ft, 18 m
- Discharge height 106", 2692 mm optional 4 ft
- Unloading speed 6" discharge Up to 2400 gallon per minute adjustable
- Painting preparation Steamed with phosphate
- Paint primed Epoxy
- Paint finish coat Urethane
- Inside coating Aluminized epoxy
- Axle warranty 5 year unconditional
- Light kit (brake & tail) Standard
- Unloading pump 4 blade fan type RPM 540
- Draw bar weight Adjustable
- Walking tandem Axle
- Seams welded solid inside
- U shape, 1/4" Sill
- 6 square ft Padding to tank contact
- 55 inch Tongue
- 4"x 8" boxed tubing 3/16" material on tongue

All Figures Are Approximate, Limited Warranty (3Months For Custom Operators), No Warranty On Sand Bedding.
For Full Details and Exact Figures, Please Confirm With Husky. 1-800-349-1122