



Husky Farm Equipment Limited

7440 Wellington Rd. 17, R. R. # 2, Alma, On N0B 1A0
Phone 519-846-5329 Fax 519-846-9378 Toll Free 1-800-349-1122
husky@huskyfarm.ca www.huskyfarm.ca




9000L Vacuum

2400 US Gal., 2000 CDN Gal., 9000 Litres

Compaction	1208 sq. in. on ground
Overall height	92 " (2337 mm)
Overall width	97.75" (2482 mm)
Empty	5,354 lbs (2,433 kg)
Loaded	25,350 lbs (11,522 kg)
Tank Width	74" (1879 mm)
Tank Height	58" (1473 mm)
Tank Length	14 ft (4.32m)
Number of baffles	1
Tire pressure	35 PSI
Tire type	Rib implement type
Hitch	Single or double, height adjustable
Tongue jack	5000 lbs
RPM	540-1000 optional
Axle capacity	32000 lbs
Axle spindle size & material	2 3/4" SPS stress proof material
Hub bolt pattern	8 bolt, 8" bolt circle, 6" pilot hole
Axle width flange to flange	Straight axle 82.25"
Hub greaseable	No
Axle warranty	5 year unconditional (non commercial)
1/4" (6.35 mm) tank shell high strength steel	
1/4" Tank ends flanged and dished	
Sight gauge standard front drivers side	
Tongue 73 inches 4" x 8" x 1/4 tubing	
24" rear access hatch , 6" hydraulic discharge	
6" manual side valve	
15 feet 6" suction hose with Bauer ends	
Primary and secondary moisture trap with 6" stainless ball	
3" (75 MM) air intake and outlet lines	
10 Year rust out warranty	
High speed vacuum pumps air cooled	
High heat vanes / air cooled / 540/ 1000	

21.5L x 16.1, 10 Ply

1844 sq. in. on ground
93.75 " (2381 mm)
103.25." (2622 mm)
5,670 lbs (2,577 kg)
25,662 lbs (11,664 kg)



Standard Features

- Bearings Tapered roller
- Seals Double lip grease purge able
- PTO Constant velocity shear protected 1 3/8 6 T, 1 3/8 21T, 1 3/4 20T
- Size of discharge 6"
- Spreading pattern Up to 60 ft, 18 m
- Discharge height 106", 2692 mm optional 4 ft
- Unloading speed 6" discharge Up to 2400 gallon per minute adjustable
- Painting preparation Steamed with phosphate
- Paint primed Epoxy
- Paint finish coat Urethane
- Inside coating Aluminized epoxy
- Axle warranty 5 year unconditional
- Light kit (brake & tail) Standard
- Unloading pump 4 blade fan type
- Draw bar weight Adjustable
- Walking tandem Axle
- Seams welded solid inside
- U shape, 1/4" Sill
- 6 square ft Padding to tank contact
- 4"x 8" boxed tubing 3/16" material on tongue

Options For Your Husky Tank

- Hydraulic drive
- Butterfly Lid
- Clean Out
- Sight Gage
- Slide Lid
- High Speed Tires
- In tank Agitation
- Valves
- Single Hitch
- Hydraulic lid
- Vacuum pumps 6 sizes to choose from
- 30 " Domed manhole
- 8 Inch discharge