2023 MAVERICK X3 X RS TURBO RR WITH SMART-SHOX



Intense Blue, Carbon Black & Chalk Gray / TURBO RR
Triple Black / TURBO RR
Desert Tan, Carbon Black & Magma Red / TURBO RR

PACKAGE HIGHLIGHTS

- · Smart-Lok* front differential
- Smart-Shox** Technology featuring DDA Valve
- FOX† 3.0 PODIUM† shocks with bypass
- · Belt monitoring system
- · 850 W magneto
- 7.6 in. digital display with keypad
- · X-package graphics/seats
- · 4-point harness with shoulder pads
- · Can-Am LED signature
- 14 in. aluminum beadlock wheels
- · 32 in. Maxxis Carnivore† tires
- Full roof
- · HMWPE full skid plate

ENGINE	TURBO RR
Туре	200 hp, Rotax* ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-perfomance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4 modes traction system: 2WD/4WD with front diff. lock/4WD TRAIL ACTIV/4WD TRAIL
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Double A-arm with sway bar/22 in. (55.9 cm) travel/ Trophy truck inspired arms
Front Shocks	FOX 2.5 PODIUM Piggyback with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar/24 in. (61 cm) travel
Rear Shocks	FOX 3.0 PODIUM remote reservoir with bypass and Smart-Shox Technology featuring DDA Valve (Dynamic Damping Adjustment)
TIRES & WHEELS	
Front/Tires	Maxxis Carnivore 32 x 10/10 x 14 in.
Wheels	14 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers

DIMENSIONS & CAPACITIES

DIVIENSIONS & CAPACITIES		
Estimated Dry Weight	1,699 lb (770.7 kg)	
Chassis/Cage	Dual-phase 980 steel	
LxWxH	132 x 72.7 x 68.5 in. (335.3 x 184.7 x 174 cm)	
Wheelbase	102 in. (259.1 cm)	
Ground Clearance	16 in. (40.6 cm)	
Rack Capacity	200 lb (91 kg) with LinQ® Quick-Attach	
Storage Capacity	Total: 2.5 gal (9.4 L)	
Fuel Capacity	10.5 gal (40 L)	

FEATURES

Gauge	7.6 in. wide digital display with keypad
Instrumentation	DC outlet (10-A)
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlight, LED signature, LED tail lights
Winch	N/A
Magneto	850 W
Protection	Integrated front bumper, quarter doors, full roof 4-point harness with shoulder pads HMWPE full skid plate, rear tow hook

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



