

2024 SKANDIC® SE

Spring-only package with premium utility features for ultimate off-trail traction and flotation.



SKANDIC SE
600R E-TEC SHOWN

SKANDIC SE
900 ACE TURBO SHOWN

// WHAT'S NEW

- Rotax 900 ACE™ Turbo available

// PACKAGE HIGHLIGHTS

- Three Rotax® engines available: 600R E-TEC®, 900 ACE™ and 900 ACE Turbo
- Available with five 20 in. or 24 in. track options
- Ultra large LinQ® utility cargo box with 135 L/35.7 US gal of storage
- Heated driver's visor power outlet
- 7.2 in. digital display
- Pilot™ 7.4 skis w/ liners
- KYB® 36 center and rear shocks
- Multi-LinQ plate with 125 lb/56 kg cargo capacity
- LTS telescopic front suspension
- SC¹-5U articulating rear suspension with locking mechanism (no tool required)
- Removable passenger seat with grips
- Ultra-high windshield with side deflectors
- Air radiator with fan
- Standard electric start
- Deep-snow running boards with large openings
- Easy Shift transmission (H-L-N) with RER™ electronic reverse (2-stroke) / electro-mechanical reverse (4 stroke)
- Pivoting mirrors
- pDrive™ clutch
- Low handlebar strap

ROTAX ENGINE	600R E-TEC	900 ACE	900 ACE TURBO
Engine details	Liquid-cooled, two-stroke, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged
Horsepower*	125	95	130
Cylinders - Displacement	2 - 599.4 cc	3 - 899 cc	3 - 899 cc
Bore - Stroke (mm)	72.3 - 73	73 - 69.7	73 - 69.7
Carburation	E-TEC direct injection	EFI	EFI
Fuel type - Octane	Premium unleaded - 91	Regular unleaded - 87	Premium unleaded - 91
Fuel tank (L/US gal)	42/11.1	42/11.1	42/11.1
Oil tank capacity (L/qt)	3.4/3.6	3.3/3.5	3.3/3.5

POWERTRAIN	600R E-TEC	900 ACE	900 ACE TURBO
Drive clutch	pDrive with clickers	pDrive	pDrive
Driven clutch	QRS	QRS	QRS Vent
Drive sprocket pitch (mm/in.)	73/2.86	73/2.86	73/2.86

DRY WEIGHT	600R E-TEC	900 ACE	900 ACE TURBO
Dry weight 20 in track (lb)	639	663	689
Dry weight 24 in track (lb)	671	695	721

DIMENSIONS	600R E-TEC	900 ACE	900 ACE TURBO
Vehicle overall length (mm/in.)		3,222/126.9	
Vehicle overall width (mm/in.)		1,089/42.8	
Vehicle overall height (mm/in.)		1,513/59.6	
Ski stance (mm/in.)		889/35	
Available tracks (in.) (Length x width x profile)		Silent Cobra WT: 154 x 20 x 1.8 Silent Ice Cobra WT: 154 x 20 x 1.5	Silent Cobra SWT: 154 x 24 x 1.5 opt. Silent Ice Cobra SWT: 154 x 24 x 1.5 opt.

COLOR	600R E-TEC	900 ACE	900 ACE TURBO
Terra Green			
Black			

SUSPENSION	600R E-TEC	900 ACE	900 ACE TURBO
Front suspension		LTS	LTS
Front shock		Motion Control	Motion Control
Front suspension travel (mm/in.)		150/5.9	150/5.9
Rear suspension		SC-5U	SC-5U
Center shock		KYB 36	KYB 36
Rear shock		KYB 36	KYB 36
Rear suspension travel (mm/in.)		239/9.4	239/9.4

FEATURES	600R E-TEC	900 ACE	900 ACE TURBO
Platform		REV® Gen4	REV® Gen4
Headlights		Halogen	Halogen
Skis		Pilot 7.4 w/ liners	Pilot 7.4 w/ liners
Seating		WideTrack 2-up	WideTrack 2-up
Handlebar		Standard with J-hooks/Grab handle	Standard with J-hooks/Grab handle
Riser block height (mm/in.)		145/5.7	145/5.7
Starter		Electric	Electric
Reverse		RER (2-stroke)	RER (2-stroke) Electro-mechanic (ACE engines)
Air radiator		High-efficiency w/ fan (4-stroke)	High-efficiency w/ fan (4-stroke) Fan (2-stroke)
Brake system		Brembo ¹	Brembo ¹
Heated throttle lever/grips		Standard (driver only)	Standard (driver only)
Gauge type		7.2 in. digital	7.2 in. digital
Windshield		Ultra-high with mirrors	Ultra-high with mirrors
Runner (in.) - Carbide (in.)		3/8 square - 4	3/8 square - 4
Bumpers (front/rear)		Heavy-duty/Hitch receiver	Heavy-duty/Hitch receiver

// FEATURE HIGHLIGHTS



1 Multi-LinQ plate

Standard LinQ adaptable storage. Fits 16 and 20 in. wide LinQ accessories to maximize accessory options. Up to 125 lb (56.7 kg) of cargo capacity.



2 Ultra large LinQ utility cargo box

135 L/35.7 US gal of lockable, weather-resistant storage capacity. Incorporated hatchet and saw holder, plus attachment points for bungees and two 16 in. LinQ positions on top for expandable accessory use.



3 LTS front suspension

Industry-exclusive telescopic front suspension enables a large, flat belly pan for exceptional deep-snow flotation.



SKANDIC SE
900 ACE TURBO SHOWN



4 Ski liners

Added flotation for extreme capability when your day takes you into the deep stuff.



5 20 in. and 24 in. wide tracks available

A wide range of options built to offer superb flotation and meet any towing needs.



6 SC-5U articulating rear suspension

The articulated rail maximizes deep-snow traction in reverse, and its toolless locking mechanism is ideal for towing.

ski-doo

