

The Perfect Team.

Portable and compact, Brandt Transfer GrainBelts can be used to feed your Swing Away Auger or Harvest GrainBelt. Available in 15", 20", or 24" models for an unbeatable combination of speed, gentleness and versatility while unloading trucks, gravity wagons and belly dump trailers.

Easy Transport

Transfer GrainBelts feature adjustable wheels that allow for easy maneuverability over uneven terrain. Made to be easily towed on its own or paired with a Harvest GrainBelt.

Collapsible Hopper

The collapsible hopper uses tubing rather than flat bar for a stronger frame. Brandt's unique low-profile hopper allows it to fit under even the lowest of center-dump grain trucks.

Flood Feed

Match the capacity of your main swing away auger or grainbelt for optimal performance and minimal unload times.

Discharge Hood

The adjustable discharge hood allows you to direct the grain into any size or shape of bin. Removing the discharge hood allows you to throw the grain back into corners or into long and/or narrow storage facilities.



TRANSFER GRAINBELTS

SPECIFICATIONS

	1515A LP	2021A LP	2421A LP
Performance	787478		
Capacity (bushels per hour)	7,000	12,000	14,000
Recommended Horsepower - Electric	5 - 7.5	10	10
Hydraulic Requirements	11 gpm	11 gpm	11 gpm
Dimensions			
Tube Diameter	10"	14"	14"
Belt Width	15"	20"	24"
Conveyor Length	15'	21'	21'
Raised Height	3'11"	4' 7"	4' 7"
Reach	5' 4"	8' 4"	8' 4"
Transport Height	4' 10"	6' 5"	6' 5"
Transport Length	19'	23' 9"	23' 9"
Wheel Track Width	2' 5" (Std) / 4' 3" (Opt)	5' 6"	5' 6"
Total Weight (lb)	480	1,418	1,574
Features			
Windguards	Standard	Standard	Standard
Belt Type	Rubber	Rubber	Rubber
Drive System	Top-Drive	Top-Drive	Top-Drive
Hopper			
Style	Low Profile	Low Profile	Low Profile
Width x Length	36" x 70"	40" x 72"	40" x 72"
Collapsed Height	7-1/2"	10"	10"
Extended Height	16"	18"	18"

OPTIONS

Gas¹/Electric/Hydraulic Drive

Hopper Cover

Axle Extension Kit¹

¹ Available for 1515 only

