



**AUTOSWEEP.** The patented AutoSweep<sup>®</sup> control system monitors engine speed and automatically adjusts cutter wheel sweep rate to maximize power to the cutter wheel while reducing engine stress.



**OPERATOR PRESENCE SYSTEM.** This user-friendly operator presence system is intended to help protect the operator and enhance operator safety.



**TONGUE LENGTH.** A 60" (152.4 cm) tongue extension helps reduce the amount of repositioning needed on a jobsite.



PATENTED YELLOW JACKET<sup>™</sup> CUTTER SYSTEM. The Vermeer-exclusive Yellow Jacket cutter system is designed to provide faster, easier serviceability, as well as extended pocket and tooth life.



**SWING ARC.** The sweep arc measures 103" (261.6 cm). The below-ground cutting depth of 25" (63.5 cm) allows operators to cut even the largest stumps efficiently. The rear deck design allows for chip containment capacity of approximately 68 cu ft (1.9 cu/m).



**FLOATATION TIRES.** This standard feature allows the weight of the machine to be dispersed over a larger area reducing the ground disturbance.



# SC802 STUMP CUTTER

#### GENERAL

Length: 167.3" (424.9 cm) Width: 79.8" (202.7 cm) Height: 79" (200.7 cm) Weight: 4400 lb (1995.8 kg) Type: Tow-behind

## ENGINE

Make/Model: Deutz TD2.9L Tier 4 Final Gross HP: 74 hp (55.2 kw) Torque (max): 188 ft-lb (254.9 Nm) Number of Cylinders: 4 Fuel type: Diesel Max engine operating angle: 30 deg

## **CUTTING DIMENSIONS**

Cutter wheel straight line dimension: 96" (243.8 cm) Cutter wheel cut above ground: 35" (88.9 cm) Cutter wheel cut below ground: 25" (63.5 cm) Tongue extension: 60" extendable tongue

## **CUTTER WHEEL**

Cutter wheel diameter (without teeth): 28" (71.1 cm) Cutter wheel thickness: .9" (2.4 cm) Tooth style: Yellow Jacket<sup>™</sup> cutter system Number of teeth: 42 Cutter wheel drive type: Gearbox driven direct drive system Chip containment: 68 cu ft (1.9 cu m) Flow control system: AutoSweep control system Cutter wheel guard: Standard

## **CAPACITIES/ELECTRICAL**

Fuel tank: 25 gal (94.6 L) Hydraulic tank: 6 gal (22.7 L) Pump flow at max rpm: 3.2 gpm (12.1 L/min) Electrical system: 12 volt

## **OPTIONS**

Extended warranty Special paint Planned maintenance Vermeer Confidence Plus® Asset Protection Program

NOTES:



Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Yellow Jacket, Vermeer Confidence Plus and AutoSweep are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. Deutz is a trademark of Klockner-Humboldt-Duetz Corporation.

2015 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.