

**SPECIFICATIONS**

MODEL >>	CX2-841	CX2-851	CX2-861	CX2-1041	CX2-1051	CX2-1061	1336
Tube width	8"			10"			13"
Tube length	41'	51'	61'	41'	51'	61'	36'
Wheel track	8' 9"	10' 1"	10' 1"	8' 9"	10' 1"	10' 1"	7' 5"
Belt drives	Double	Double	N/A	Triple	Triple	Triple	Triple
Tube, gauge	14	14	14	12	12	12	12
Flighting, gauge	10	10	10	7	7	7	1/4"
Flighting shaft, dia.	1-1/4"	1-1/4"	1-1/4"	2-3/8"	2-3/8"	2-3/8"	2-3/8"
Flighting shaft, gauge	11 gauge	11 gauge	11 gauge	11 gauge	11 gauge	11 gauge	11 gauge
Drive line	1-3/8"	1-3/8"	1-3/8"	1-3/8"	1-3/8"	1-3/8"	1-1/2"
Gasoline							
- Motor pulley	3-1/2"	3-1/2"	N/A	3-1/2"	3-1/2"	4"	3-1/2"
- Fuel tank capacity	6.5	6.5	N/A	6.5	6.5	6.5	N/A
Motor pulley (tube-mount electric) <sup>4</sup>	3-3/4"	3-3/4"	3-3/4"	3-3/4"	3-3/4"	3-3/4"	3-3/4"
Recommended engine hp	16 hp	20 hp	24 hp	28 hp	32 hp	38 hp	30 hp
Electric motor hp <sup>5</sup>	8 hp	10 hp	15 hp	10 hp	15 hp	20 hp	22 hp

<sup>4</sup>Tube mount kits are recommended to be installed on direct PTO (CX or C) models using pulley diameters shown. Use a 6" motor pulley when installing electric motors on C series engine drive models.

<sup>5</sup>Depends on the type of grain and grain density. Electric hp are estimates only.