

# X4



X4.60 - X4.70 - X4.80

**MCCORMICK**  
Power Technology.



Tractor Model		X4.60	X4.70	X4.80
<b>Performance</b>				
Max. ISO Engine HP @ 1900 RPM	HP (kW)	60 (45)	68 (50)	74 (55)
Max. ISO PTO HP @ 1900 RPM*	HP (kW)	51 (37)	57 (42)	63 (46)
Max. Engine Torque @ 1400 RPM	lb ft (Nm)	206 (279)	221 (299)	221 (299)
<b>Engine</b>				
Engine Type	KOHLER TDI 2504, TIER V COMPLIANT ENGINE, USING DOC+DPF			
Engine Size	2.5L, 4 CYLINDER			
Fuel Capacity	gal (liter)	22 (85)		
<b>Drive Train</b>				
Transmission Type	24X24 synchronized mechanical shuttle w/HI/LO with left hand shuttle lever, 25mph (40kph)			
Rear Axle	Heavy duty flange rear axle; internal planetary final drives; wet disc brakes			
Differential Lock	Fully locking rear differential; mechanical engagement via foot pedal			
4wd Front Axle	Push button 4wd engagement; outboard planetary final drives; automatic 4-wheel braking			
Tire Type	Radial tires standard			
<b>Hydraulics, 3-point Hitch, PTO</b>				
Hydraulic System/Max. Flow	gpm (lpm)	Open center system with separate steering and implement pumps		
Hydraulic Flow Rate	gpm (lpm)	Dedicated steering pump 7.9 (30); Dedicated implement pump 13.7 (52)		
Rear Remote Valves	2 standard with ISO 1/2" quick couplers			
Rear 3-point Hitch Type	Category 2; mechanical operation; position and draft sensing			
3-point Lift Capacity @ Hitch	lb (kg)	6,172 (2,800)		
Rear PTO	540/540E; mechanical engagement			
<b>Operator's Area</b>				
Operator's Area	Cab or 2-post folding ROPS			
Seat and Front Dash	ROPS: Adjustable vinyl seat, mechanical suspension; tilt steering wheel Cab: Cloth seat, air suspension; tilt and telescopic steering wheel			
Wheelbase	in (mm)	83.1(2,110)		
Height Over ROPS in Raised Position	in (mm)	98.4 (2,500)		
Height Over Cab	In (mm)	98.5 (2,433)		
Overall Length without Front Weights	in (mm)	155 (3,930)		
Base Weight without Ballast	lb (kg)	ROPS: 6,724 (3,050) Cab: 7,275 (3,200)		

\* Manufacturer's calculated estimate. +/- 5% tolerance.