

# XT

24 TO 55 ENGINE HP



McCORMICK

# McCORMICK X1: A FULL UTILITY OFFERING



Perfect for homeowners, hobby farmers, and anyone needing a dependable compact tractor to do work around the homestead. All eleven models, from 24 to 55 engine horsepower, are designed from the ground up to dish out power and performance in a wide variety of applications. With rugged steel and cast iron construction, 4-wheel drive, a choice of transmissions, and robust hydraulic system, the X1 lineup delivers everything you have come to expect from a McCormick tractor. Whether used for loader work, grading, tilling, snow removal, or landscaping, there is an X1 model that will go above and beyond to get the job done.

# THE X1.37

The X1.37 is a 37HP cab model with choice of mechanical (X1.37C) or hydrostatic transmission (X1.37HC). Like the current X1 series, the X1.37 model is a heavily built and reliable machine with comfortable and simple operation.



## KEY FEATURES:

### Engine

- 4-cylinder, 2.0L built by Kukje
- 37 rated HP, 33 PTO HP
- Tier 4 final emissions using only DOC and DPF

### Transmission

- Available 12x12 Mechanical or 3 Range Hydrostatic

### Cab

- Designed for increased visibility and operator space
- High level of features come standard
- Factory cab – quiet and well insulated

### PTO

- Independent PTO system
- Choice of 540 and 540E
- "Auto" and "Link" modes of operation

### Frame

- Heavy built, over 4,195 lbs
- Cast iron front axle, rear end, and transmission housing
- 71 inch wheelbase for stability
- Steel single piece hood
- Steel Fenders

### Front Axle

- Cast iron build
- One of the heaviest in the industry
- 56 degree steering angle with 10 degrees of camber for increased maneuverability
- Hydraulic power steering

### Loader

- L160C loader designed by ALO

### Hydraulics

- 11.1 gpm (42 lpm) main pump
- 5 gpm (19 lpm) steering pump

### 3 Point Hitch

- 3,306 lbs (1500kg) lift capacity at ball ends
- Standard category 1 telescoping link ends

# McCORMICK X1: THE ULTIMATE IN UTILITY

<b>Loader Model</b>		<b>C12</b>	<b>C16</b>	<b>C18</b>
Tool Carrier		Pin-On	Skid Steer	Skid Steer
Lift Height at Bucket Pivot Pin	in (mm)	82 (2082)	99 (2514)	109 (2768)
Lift Capacity to Max Height 19.6" Forward of Pivot	lb (kg)	770 (349)	1520 (689)	2050 (929)
Lift Capacity to 59" Lift Height (39" for C12) 19.6" Fwd of Pin	lb (kg)	880 (399)	1910 (866)	2660 (1206)
Breakout Force at Groundline 19.6" Forward of Pivot	lbs (kg)	1120 (508)	2370 (1075)	3240 (1469)
Bucket Rollback Force at Groundline 19.6" Forward of Pivot	lbs (kg)	1420 (644)	3720 (1687)	4440 (2013)
Compatible Tractor Models		X1.25H	X1.35 X1.35H X1.37C X1.37HC	X1.45 X1.45C X1.45HC X1.55H X1.55C X1.55HC

<b>Belly Mower Model</b>	<b>BM60</b>
Cutting Width	in (mm) 60 (1520)
Cutting Height	in (mm) 1.1-3.3 (28-84)
Height Adjustment	3-point lift controls
Number of Blades	3
Drive System	Belt drive from mid PTO
Compatible Tractor Models	X1.25H



# A PLATFORM FOR EVERY OPERATION



McCORMICK

Tractor Model		X1.25H	X1.35	X1.35H	X1.37C	X1.37HC		
Rated Engine Power	HP (kW)	24 (18)	35 (26)	35 (26)	37 (27.1)	37 (27.1)		
Rated Engine Speed		2600 RPM						
Rated PTO Power	HP (kW)	18 (13)	29 (21)	29 (21)	33 (24.2)	32 (23.5)		
Engine Type		3-cylinder diesel						
Displacement		1.2 liter (73 in <sup>3</sup> )	1.7 Liter (104 in <sup>3</sup> )		2.01 Liter (127.1 in <sup>3</sup> )			
Aspiration		Natural						
Emissions System		EPA Tier 4	Tier 4, using combined DOC + DPF					
Fuel Capacity	gal (liters)	6.2 (23.6)	9.3 (35), tank under platform		12 (45), ground level tank			
Transmission Type		Hydrostatic	Mechanical	Hydrostatic	Mechanical	Hydrostatic		
Main Clutch		Dry single disc		None	Dry single disc	None		
Speeds		2-range HST	12F x 12R	3-range HST	12F x 12R	3-Range HST		
Shuttle Type		2 Foot pedals	Synchronized	2 Foot pedals	Synchronized	2 Foot pedals		
Differential Lock		Mechanical, heel pedal						
Rear Brakes		Wet disc brakes with R and L pedals		Wet disc brakes with suspended R and L pedals				
Front Axle Type		4wd with mechanical engagement		4wd with mechanical engagement, 62-degree steering angle				
Rear PTO Type		540 RPM, live transmission driven		Independent, electronically engaged, 540 and 540E standard				
Mid PTO		Standard, 2500 RPM		Not available				
Hydraulic System		Open center system						
Hyd. Flow at Remotes	gpm (lpm)	4.8 (18.2)	8.9 (34)		11.1 (42)	10.4 (39.4)		
Loader Joystick		Mounted to loader sub frame		Standard with 2 mid-mount valves				
Rear Remote Valves		1 optional		2 standard				
3-pt Type		Category I		Category I with telescopic stabilizers and lower links				
3-pt Lift Capacity	lb (kg)	1,500 lbs (680) at ball ends	3,306 (1500) at ball ends; 2,425 (1100) at 24"					
Operator's Area		Folding ROPS, right and left entry, rubber foot deck cover			Cab with HVAC, 2 doors, flat foot deck			
Seat and Steering		Vinyl seat, hydrostatic steering		Adjustable vinyl seat, tilt steering wheel, hydrostatic steering				
Wheelbase	in (mm)	60 (1530)	70.9 (1800)		71.1 (1,806)			
Height over ROPS/Cab	in (mm)	88 (2240)	94 (2390)	94 (2390)	96.8 (2,460)			
Base Weight	lb (kg)	1,810 (821)	4,053 (1840)	4,053 (1840)	4,211 (1,910)	4,195 (1,903)		

**SPECIFICATIONS**

<b>X1.45</b>	<b>X1.45C</b>	<b>X1.45HC</b>	<b>X1.55H</b>	<b>X1.55C</b>	<b>X1.55HC</b>				
47 (35)	47 (35)	47 (35)	55 (41)	55 (41)	55 (41)				
2600 RPM									
42 (31)	42 (31)	42 (31)	47 (35)	47 (35)	47 (35)				
4-cylinder diesel									
2.3 Liter (140 in <sup>3</sup> )									
Natural			Turbocharged						
Tier 4, using combined DOC + DPF									
9.3 (35), tank under platform									
Mechanical	Hydrostatic	Hydrostatic	Mechanical	Hydrostatic					
Dry single disc	None	None	Dry single disc	None					
12F x 12R	3-range HST	3-range HST	12F x 12R	3-range HST					
Synchronized	2 Foot pedals	2 Foot pedals	Synchronized	2 Foot pedals					
Mechanical, heel pedal									
Wet disc brakes with suspended R and L pedals									
4wd with mechanical engagement, 62-degree steering angle									
Independent, electronically engaged, 540 and 540E standard									
Not available									
Open center system									
11.1 (42)				11.1 (42)					
Standard with 2 mid-mount valves									
2 standard									
Category I with telescopic stabilizers and lower links									
3,306 (1500) at ball ends; 2,425 (1100) at 24"									
Open Station ROPS	Cab with HVAC, 2 doors, flat foot deck		Open Station ROPS	Cab with HVAC, 2 doors, flat foot deck					
Adjustable vinyl seat, tilt steering wheel, hydrostatic steering									
70.9 (1800)									
96 (2440)	97 (2460)	97 (2460)	96 (2440)	97 (2460)	97 (2460)				
4,118 (1870)	4,442 (2015)	4,442 (2015)	4,118 (1870)	4,442 (2015)	4,453 (2020)				



McCormick North America  
[www.McCormickNA.com](http://www.McCormickNA.com)

updated: 03.10.20

