



# SNOWBLOWERS HEAVY DUTY CONTRACTOR

## STANDARD FEATURES

- ◆ 1,000 rpm
- ◆ Chain guard
- ◆ 6 bladed fan
- ◆ Bolt-on cutting edge
- ◆ 3-section spout deflector
- ◆ Orbital motor chute rotator
- ◆ Ductile housing on bearings
- ◆ Heavy reinforced end plates
- ◆ Heavy adjustable skid shoes
- ◆ Heavier chain than regular models
- ◆ Heavier auger tube than regular models
- ◆ Heavier fan housing than regular models
- ◆ Heavier auger and bearings than regular models

## OPTIONS

- ◆ Top auger guard
- ◆ Quick hitch set up
- ◆ Telescopic truck loading chute
- ◆ Bank cutter (adjustable or fixed position)
- ◆ Aggressive Augers (1/2" x 3" notched flighting)

Helm Welding (1983) Limited

## Specification Table (Heavy Duty Contractors Models)

MODEL SIZE	D85HD	D9HD	D10HD	
Weight	3800	3850	3950	
Cutting Width	102	108	120	
Cutting Height	44	44	44	
Fan Shaft Diameter	2	2	2	
Fan Blades	6	6	6	
Fan Diameter	34	34	34	
Fan Housing Width	12	12	12	
Fan Housing (thickness)	5/16	5/16	5/16	
Auger Diameter	20	20	20	
Auger Shaft Diameter	1 3/4	1 3/4	1 3/4	
Auger Flighting Thickness	½	½	½	
Auger Chain Size	#80H	#80H	#80H	
Auger Tube Size	4	4	4 1/2	
Chute Diameter	15	15	15	
Chute Length	48	48	48	
Hitch Category	2	2	2	
Recommended H.P.	(min)	100	120	140
	(max)	150	160	180

H.P. recommendations are suggested only (pending snow and ground speed conditions)  
 Unless otherwise indicated, all dimensions are in inches with standard equipment installed.  
 Specifications subject to change without notice.  
 Certain features shown may be optional.