



CFORCE 400 TOURING 2024 **CF400AZ-6L**

Available colours



The most equipped vehicles on the market

More than \$2,800 in add-ons!

Standard features and benefits

Rims \$1,200 value

Trailer hitch \$100 value

5-year CFMOTO warranty

2,500 lbs winch (complete assembly) \$750 value

Safety and convenience package

- Including:
- Side mirrors
- Trailer connector
- Anti-theft device
- (gear lever lock)
- USB port
- Turn signals
- Horn
- \$750 value

4-Wheels Drive

Clutch on demand

Electric-power steering

Fuel injected

Cvtech clutch system

Specifications

Motor

Type: Single-Cylinder, liquid-cooled, 4-valves, 4-strokes Displacement: 400 cc Bore & Stroke: 91 x 61.5 mm (3.58 x 2.42 in) Compression: 10.3:1 Engine management: Fuel injected engine Cooling system: Liquid Starting: Electric Battery: 30 Ah

Size / weight

Length x Width x Height: 2246 x 1125 x 1205mm (88.4 x 44.3 x 47.4 in) Wheelbase: 1460 mm (57.5 in) Ground clearance: 250 mm (9.8 in) Minimum turning radius: 3250 mm (128 in) Fuel tank capacity: 17 L (4.5 gal) Net weight: 346 kg (763 lbs) Towing capacity: 612 kg (1349 lbs) Payload capacity: 170 kg (375 lbs) Rack capacity (Front/Rear):

30 kg (66 lbs) / 60 kg (132 lbs)

Brakes

Three wheel hydraulic disc + rear wheel parking

Wheels

enaine

Front wheels:
Aluminum alloy wheels (12 in)
Rear wheels:
Aluminum alloy wheels (12 in)
Front tires: AT 25 x 8-12
Rear tires: AT 25 x 10-12

Transmission

CV-Tech IBC clutch system: Variable transmission Gear box: L/H/N/R/P (parking lock shift system) Power train: 2WD / 4WD. electric locking differential

Suspension and direction

Front suspension: Double arched A-arm independant Front travel: 190 mm (7.5 in) Rear suspension: Double A-arm independant Rear travel: 225 mm (8.9 in) Steering:

Electronic Power Steering (EPS)

Protection plan

EASY protection plan available





5 Year limited warranty: 1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km

Follow us



