

**RITEWAY** 

**ROCK  
REMOVAL  
SERIES**

**RR250ST  
RR900ST**

**RW1200HD**

**ROCK REMOVAL SERIES**



ROCK REMOVAL SERIES

**RITEWAY** 



## ROCK PICKERS

# RR250ST RR900ST

## REMOVE YOUR ROCKS.

Rite Way rock pickers with hydraulically driven reels can be used as both a fork-type and rotary rock picker for the ultimate in flexibility and efficiency. The reels rapidly pick small to medium sized stones or can be used as a support while picking large rocks.



## ROCKPICKER FEATURES

### 1 - Hydraulic Drive.

Match the reel bat speed to your picking needs, stop the reel to pick a single large rock, or clear a jammed rock by reversing the reel.

### 2 - Wide range of rake heights.

Adjust rake height and use bats for support to pick large rocks and load them into the hopper. Or, keep rake at a minimal angle to separate rocks from dirt quickly and with minimal ground disturbance.

### 3 - Shock protection.

Both reels and forks are shock-protected to allow our rockpickers to remove extra-large rocks. The small but mighty RR250ST picks rocks up to 24" x 45" (61 x 144 cm) and the RR900ST handles rocks up to 28" x 55" (81 x 140 cm).

### 4 - Simple to dump rocks.

An electric solenoid lets you unload with the flick of a switch from your tractor.

### 5 - Ready to Move.

The Hydraulic angled hitch allows you to go from transport to field mode and back again quickly and easily.

## REEL & FORK TEAM UP FOR PICKING LARGE ROCKS.



By positioning the rake and using the reels as a support, the RR250ST can pick rocks up to 24" x 45" (61 x 144 cm) and the RR900ST picks rocks up to 28" x 55" (81 x 140 cm).

### ROCKPICKER STANDARD EQUIPMENT:

- Multi-position Hydraulic Swing Hitch
- Safety chains
- 10" Side Wind Parking Jack

## RAKE YOUR ROCKS.

Clean up your field in record time when you use a Rite Way Windrower in conjunction with your rockpicker.

### WINDROWER FEATURES

#### Affordable and efficient.

An affordable way to speed up your rock picking. Handles rocks from 1 1/2" to 12" (4 to 30 cm) diameter.

#### Three-row spiral design.

For improved speed and efficiency of delivering rocks to windrow.

#### Replaceable Hard-surface teeth.

Ensures long life of the equipment.

#### Hydraulic drive.

Hydraulics control both the depth of the rake and the field to transport positions.

#### Seedbed preparation.

Efficiently breaks up clumps and prepares the soil for seeding.

Working width: 142" (3 1/2 m)

### WINDROWER STANDARD EQUIPMENT:

- Replaceable hard surface teeth



### RR250ST

1.25 CU YD / 1 CU M CAPACITY  
8.7' / 2.7 m Transport Width

### RR900ST

3.2 CU YD / 3.2 CU M CAPACITY  
10.8' / 3.3 m Transport Width



## ROCK WINDROWER

# RW1200HD





# MADE TO WORK. BUILT TO LAST.

Whether your rocks are small or large, the Rite Way Rock Pickers and Windrower are ideal to prepare your land for what's to come. Choose the right size of field-proven equipment to fit your unique needs.

## SPECIFICATIONS:

RR250ST	
DRIVE	Variable Hydraulic Drive
REEL	2 Bat
REEL CHAIN	#80
WEIGHT	2,931 lbs / 1,330 kg
PICKING WIDTH	50" / 127 cm
MINIMUM ROCK DIAMETER	2" / 5 cm
MAXIMUM ROCK DIAMETER	24" x 45" / 61 cm x 114 cm
BUCKET CAPACITY	1.25 cu yd / 0.96 cu meter
REEL & BUCKET CONTROL	Electric over Hydraulic
WEIGHT CAPACITY	3,600 lbs / 1,650 kg
DUMPING HEIGHT	38" / 0.97 m
TIRES	12.5L x 15-6 ply
HITCH	Multi-Position, Hydraulic Swing
HYDRAULIC REQUIREMENTS	12-15 gal/min. @ 1200-1500 PSI 45-57 L/min @ 83-103 bar

RR900ST	
DRIVE	Variable Hydraulic Drive
REEL	3 Bat
REEL CHAIN	#80
WEIGHT	4,784 lbs / 2,170 kg
PICKING WIDTH	60" / 152 cm
MINIMUM ROCK DIAMETER	2" / 5 cm
MAXIMUM ROCK DIAMETER	28" x 55" / 81 cm x 140 cm
BUCKET CAPACITY	3.2 cu yd / 2.4 cu meter
REEL & BUCKET CONTROL	Electric over Hydraulic
WEIGHT CAPACITY	8,000 lbs / 4,500 kg
DUMPING HEIGHT	56" / 1.42 m
TIRES	16.5L x 16.1-6 ply
HITCH	Multi-Position, Hydraulic Swing
HYDRAULIC REQUIREMENTS	12-15 gal/min. @ 1200-1500 PSI 45-57 L/min @ 83-103 bar

RW1200HD	
WORKING WIDTH	11' 10" / 3.6 m
HEIGHT	32" / 81 cm
WEIGHT	1,350 lbs / 612.4 kg
DRIVE	Hydraulic
TRANSPORT HEIGHT	42" / 1.07 m
TRANSPORT LENGTH	8' 11" / 2.7 m
TRANSPORT WIDTH	12' 3" / 3.7 m
HYDRAULIC REQUIREMENTS	12-15 gal/min. @ 1200-1500 PSI 45-57 L/min @ 83-103 bar

We are continuously improving our products. Design, specifications, and material are subject to change without notice.

For more information on the Rock Pickers, Windrower or other land improvement equipment, visit your local Rite Way equipment dealer, or visit [www.RiteWayMfg.com](http://www.RiteWayMfg.com)

Toll free: 1-800-352-8822

