



**DUAL-AUGER GRAIN CART
1100-BUSHEL CAPACITY**



For your biggest fields and biggest yields, the Killbros® 1950 grain cart offers the convenience of the dual-auger design with enormous capacity, and an unloading rate of over 400 bushels per minute to keep your harvest moving at full-speed-ahead.

Killbros

FEATURES AND BENEFITS

- The 8'2" of auger reach and 14'2" of auger height provides easy unloading into the center of trucks. An optional hydraulic spout is available for unloading grain straight down or outward.
- Standard unloading light on discharge auger offers nighttime visibility.
- Auger fold cylinder with integrated pilot-operated lock valve ensures secure operation and prevents grain leakage.



- Low-profile tank design provides narrow transport width, steep side slopes and low center of gravity. The 14" horizontal auger features slide flow gates along with hinged cleanout doors for uniform unloading and complete cleanout.
- Hinged rear ladder for checking cart contents is standard.
- Lighting and reflective striping meet current ASAE requirements.

- Chain oiler along with tighteners for vertical and horizontal auger chains provide easy maintenance. Double #80 roller chain provides maximum life and positive drive control.
- Augers are powered by a 1 3/8" 21-spline or a 1 3/4" 20-spline PTO that is shear bolt-protected with extra shear bolts stored along tongue. An optional PTO with slip-clutch is also available.
- Horizontal gate features a flow indicator to help the operator control grain metering.



MODEL 1950



- Three front-viewing windows for safer and easier monitoring of cart contents.
- Choose red or green high-quality enamel paint with silicone-sealed seams.
- Vertical auger alignment is anchored by a 1 $\frac{3}{4}$ "-thick drive dog with a top mounted spring-loaded bearing for smooth and proper engagement.



1100 BU CAPACITY



AVAILABLE OPTIONS

- Weatherguard rollover tarp to protect grain.
- Hydraulic spout directs grain straight down or outward for precise grain positioning.
- 30 – 55 gpm hydraulic drive with unloading speeds up to 300 bu/min.
- Tracked 36" x 132" undercarriage with steel end-wheels for reduced compaction and enhanced maneuverability.
 - Hydraulic tensioning adjustment for easier track alignment, optimum ground contact and even weight distribution.
- Automatic greasing system for optimum undercarriage lubrication.
- UHarvest™ Data Management System for the most complete detailed grain-cart harvest data possible. Automatically records each bushel loaded into the grain cart by grower, farm, field, truck loaded, grain destination and variety.
 - Optional cart-mounted moisture sensor for dry bushel weight conversions.
- Basic scale package for accurate in-field weighing.
 - Downloader kit or printer for scale package.

SPECIFICATIONS

Model 1950

Capacity (bu)	1,100
Unloading speed (bu/min)	400
Total width	13'4"
Total length	28'5"
Total height	12'3"
Height to tip of spout	14'2"
Height – loading side	11'7"
Auger reach	8'2"
Vertical auger diameter	16"
Horizontal auger diameter	14"
Approximate empty weight (lbs)	12,260
Loaded tongue weight (lbs)	4,500

UNDERCARRIAGE OPTIONS

Model 1950

900/70R x 32 single (29.08 PSI)
1050/50 x 32 singles (21.21 PSI)
36" x 132" tracks with steel idler wheels (12.59 PSI)

Loaded P.S.I. calculated at 3" soil penetration depth
 Due to continuing improvements in the design and manufacture of Killbros products, all specifications contained herein are subject to change without notice.

Stop by your nearest Killbros dealer or killbrosequip.com today for complete details about the Killbros model 1950 dual-auger grain cart.



Rollover tarp



Directional downspout



Hydraulic track tensioning

Unverferth
 Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853
 (419) 532-3121 • unverferth.com

www.killbrosequip.com

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2014 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH
 Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada



KB1950411001M5