

| MODEL: | 9520 Pull Type | 9520 Truck Mount | 9524 Pull Type | 9524 Truck Mount | 9530 Pull Type | 9530 Truck Mount |
|---------------------------------|---------------------------------|----------------------------|---------------------------------|----------------------------|-----------------------------------|----------------------------|
| Box Inside Length | 20' | 20' | 24' | 24' | 30' | 30' |
| Overall Length | 32' 5" w/XTS2400 | 24' 10" w/gearbox | 36' 5" w/XTS3000 | 28' 10" w/gearbox | 42'5" w/XTS4500 | 34'10" w/gearbox |
| Inside Width | 90 3/4" | 90 3/4" | 90 3/4" | 90 3/4" | 90 3/4" | 90 3/4" |
| Overall Width | 104.5"/122.2" | 104.5" | 104.5"/128.1" | 104.5" | 104.5"/124.5" | 104.5" |
| Box/Box w//Tires | w/700/40x22.5 | | w/710/50Rx26.5 | | w/710/45x22.5 | |
| Inside Height | 47 1/2" | 47 1/2" | 47 1/2" | 47 1/2" | 47 1/2" | 47 1/2" |
| Overall Height w/S-200 | 151.4" w/XTSW2400 w/700/40x22.5 | 100.5" + truck height | 155.2" w/HFX3000 w/710/50Rx26.5 | 100.5" + truck height | 1152.5" w/XTSSW4500 w/710/45x22.5 | 100.5" + truck height |
| Loading Height | 112.8" w/Trailer | 63.5" + Truck Height | 116.5" w/Trailer | 63.5" + Ttruck Height | 113.8" w/Trailer | 63.5" + Truck Height |
| Capacity-Struck Heaped | 600/755 Cu. Ft. | 600/755 Cu. Ft. | 720/925 Cu. Ft. | 720/925 Cu. Ft. | 900/1,180 Cu. Ft. | 900/1,180 Cu. Ft. |
| Weight (approximate) w/S-200 | 17,340# w/700/40x22.5 | 12,300# | 19,760# w/710/50Rx22.5 | 13,340# | 26,320# w/710/45x22.5 | 14,617# |
| Horse Power Required-Min. | 200 HP | 300 HP + call factory | 220 HP | 350 HP + call factory | 250 HP | 400 HP + call factory |
| Apron Chains | D667XH/3-Aprons | D667XH/3-Aprons | D667XH/3-Aprons | D667XH/3-Aprons | D667XH/3-Aprons | D667XH/3-Aprons |
| Slats Per Apron | 31/93 Per Box | 31/93 Per Box | 37/111 Per Box | 37/111 Per Box | 46/138 Per Box | 46/138 Per Box |
| Apron Drive | Hydraulic - Variable | Hydraulic - Variable | Hydraulic - Variable | Hydraulic - Variable | Hydraulic - Variable | Hydraulic - Variable |
| Reversing Apron | Standard | Standard | Standard | Standard | Standard | Standard |
| Floor | Super Slide - Solid Poly | Super Slide - Solid Poly | Super Slide - Solid Poly | Super Slide - Solid Poly | Super Slide - Solid Poly | Super Slide - Solid Poly |
| Box Sides | Steel - 10 gauge | Steel - 10 gauge | Steel - 10 gauge | Steel - 10 gauge | Steel - 10 gauge | Steel - 10 gauge |
| Front 36" Folding Guard/Deflect | Standard | Standard | Standard | Standard | Standard | Standard |
| Transport Lights w/Cord | Standard | Standard w/Truck Mount Kit | Standard | Standard w/Truck Mount Kit | Standard | Standard w/Truck Mount Kit |
| OPTIONS | | | | | | |
| Rear Attach S-100/200/400 | Optional | Optional | Optional | Optional | Optional | Optional |
| Silage Extension Package | Optional 36" | Optional 36" | Optional 36" | Optional 36" | Optional 36" | Optional 36" |
| Scale Packages | Optional | Optional | Optional | Optional | Optional | Optional |
| Poly Fenders | N/A | Standard w/Truck Mount Kit | N/A | Standard w/Truck Mount Kit | N/A | Standard w/Truck Mount Kit |
| Poly Apron Return Liner | N/A | Optional | N/A | Optional | N/A | Optional |

| TRAILERS (pull type) | *For 9520* XTSW2400 | *For 9524* HFX3000 | *For 9530* XTSSW4500 |
|---|---|---|---|
| Frame | 4x8 tubing | 4x8 tubing | 4x8 tubing |
| Capacity (trailer/spreader/load) | 48,000# | 60,000# | 90,000# |
| Axle Configuration | Tandem - Non Steer | Tandem - Non Steer | Tridem - Steerable F&R |
| | 25,000# x 2 | 25,000# x 2 | 33,000# x 3 |
| | Fixed Spring Suspension | Sliding Spring Suspension | Fixed Spring Suspension |
| Heavy Duty Hubs | Oil Bath - 10 Bolt | Oil Bath - 10 Bolt | Grease Filled - 10 Bolt |
| Articulating Implement Hitch | Std - Requires 1.5" or 2" pin Hammerstrap Style Hitch | Std - Requires 1.5" or 2" pin Hammerstrap Style Hitch | Std - Requires 1.5" or 2" pin Hammerstrap Style Hitch |
| Poly Fender Liner | Standard | Standard | Standard |
| Steel Fender Flares | Optional | Optional | Optional |
| Tire Options: | 700/40x22.5 High Floatation | 710/50Rx26.5 High Floatation | 710/45x22.5 High Floatation |
| | 425/65x22.5 new truck tires | | |
| | 11Rx22.5 new, Dual Truck Tires | | |
| Brakes (Air, Hyd or Foot Pedal) | Optional | Optional | Standard-No Air Option |
| Safety Chain/SMV | Optional | Optional | Optional |
| Tracks in Lieu of Tires | Call | Call | Call |