XTERRAIN BRUTAL



ROTAX® ENGINE	850 E-TEC
Engine details	Liquid-cooled, two-stroke, 3-D R.A.V.E.™
Cylinders	2
Displacement	849 cc
Bore	82 mm
Stroke	80.4 mm
Maximum engine speed	7,900 RPM
Carburation	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	42 L / 11 gal
Oil tank capacity (2-stroke)	3.4 L / 3.6 qt

Viper Red
3,230 mm / 127 in.
1,200 mm / 47.2 in.
1,230 mm / 48.4 in.
996 mm / 39 in.
500 mm / 20 in.
3,923 mm / 154 in.
2.4 in. PowderMax

Platinum Silver Satin /

## **POWERTRAIN**

Gearbox	
Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

## **SUSPENSION**

Front suspension	LFS
Front shock	KYB 36
Rear suspension	EasyRide
Center shock	KYB 46 Kashima
Rear shock	KYB 46 Kashima

## **FEATURES**

Frame	Radien-X
Skis	Blade DS+
Seating	Brutal, 1-up
Handlebar	U-type aluminum with hooks, low grab handle
Riser block height	120 mm
Starter	Electric and manual
Reverse	RER
Heated throttle lever	Standard
Heated grips	Standard

Gauge	7.2 in. wide digital display
Mirrors	Optional
Windshield	Low
Hitch	Optional
Visor Plug front / rear	Front
USB power outlet	Yes, in front compartment
Air radiator with fan	Yes
LinQ attachment	Multi-LinQ plate



<sup>\*</sup>Overall vehicle length without snow flap.