

2024 COMMANDER MAX X MR



 Wildland Camo

ENGINE	1000R
Type	100 hp, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation. Strategically positioned CVT air intakes and exhaust. Lower gearing ratio and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok® technology True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes
Power Steering	Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar / 14 in. (35.6 cm) suspension travel
Front Shocks	Twin tube gas-charged shocks
Rear Suspension	Arched TTA with sway bar / 14 in. (35.6 cm) suspension travel
Rear Shocks	Twin tube gas-charged shocks
TIRES & WHEELS	
Front / Rear Tires	XPS Swamp Force 30 x 9 / 11 x 14 in.
Wheels	14 in. cast aluminum
BRAKES	
Front / Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

PACKAGE HIGHLIGHTS

- Smart-Lok® front differential
- Strategically positioned engine air intake and CVT inlet / outlet
- Special edition seats
- 7.6 in. digital display with keypad
- LED headlights and Can-Am LED signature
- 64 in. wide with arched A-arm
- 30 in. XPS Swamp Force tires
- 14 in. cast-aluminum wheels
- Heavy-duty front steel bumper
- Relocated 4,500 lb (2,014 kg) winch
- Mudguard extensions

DIMENSIONS & CAPACITIES

Estimated Dry Weight	2,061 lb (937 kg)
Chassis / Cage	Profiled cage, ROPS approved
L x W x H	152 x 64 x 74.3 in. (386.1 x 162.6 x 188.6 cm)
Wheelbase	120.6 in. (306.3 cm)
Ground Clearance	13.5 in. (34.3 cm)
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,280 lb (580.6 kg)
Storage Capacity	Total: 8.5 gal (32.1 L)
Fuel Capacity	10 gal (38 L)

FEATURES

Gauge	7.6 in. wide digital display with keypad
Instrumentation	DC outlet (10 A)
Anti-Theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Magneto	650 W
Lighting	LED headlights LED signature LED tail lights
Winch	Relocated 4,500 lb (2,041 kg) winch with synthetic rope and roller fairlead
Steering Wheel	Adjustable tilt steering
Protection	Premium half doors Full skid plate Mudguards / mudguard extensions Heavy-duty front steel bumper
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service	B.E.S.T. term available up to 30 months
Terms	

can-am®

© 2023 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. †Visco-Lok is a trademark of GKN Viscodrive GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SxS) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly. *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry. Top Speed is limited to a maximum of 100 km/h (62 mph)—except for X mr units with XPS Swamp Force tires.

