

GrainVacs	5200 EX	1300 HP
Performance		
Capacity* (bu/hr)	5,200	8,000 - 8,500
Minimum Tractor Horsepower	70	120
Hydraulic Requirements (1 remote)	2,000 psi @ 2gpm	2,000 psi @ 2gpm
with Pile Driver (+ 3 remotes)	2,000 psi @ 11 gpm	n/a
Auger		
Diameter	10"	13"
Tube Thickness	10 ga	12 ga
Flighting Thickness	1/4"	5/16"
Flighting Material	Chrome	Chrome
Dimensions		
Transport Height	86" (2.18 m)	103" (2.62 m)
Auger Extended	182" (4.62 m)	200" (5.08 m)
Auger Lateral	160" (4.08m)	149" (3.79 m)
Length	126" (3.20 m)	174" (4.42 m)
Width	102" (2.59 m)	102" (2.59 m)
Wheel Track Width	97" (2.46 m)	100" (2.54 m)
Frame Size	4"x4" HSS	4"x4" HSS
Weight	3200 lb (1450 kg)	3400 lb (1542 kg)
Hitch Weight	680 lb (310 kg)	650 lb (300 kg)
Standard Hoses		
Flexible Stainless Steel	One: 7"x3.5' Two: 7"x7'	One: 8"x3.5' Two: 8"x7'
Flex-rigid Combination	-	One 8" x 7'
Rigid Aluminum	Two 7" x 7'	One 8" x 7'
Corrugated Rubber Hose	One 7" x 7'	One 8" x 7'
Cleanup Shovel	7"	8"
MaxFlo Full-bin Nozzle	7"	8"

Product specifications and configuration are subject to change without prior notice. Before ordering, please ask your Brandt dealer for the latest information. The manufacturer reserves the right to make changes at any time, without notice, to prices, specification and models.

© Brandt Industries Ltd. All rights reserved. Brandt and Brandt logo are trademarks of Brandt Industries Ltd, used under license. This product is covered by one or more of the following patents and patent applications: CA2537580, CA 2469239, CA 2243798, US 6979152, and US 670169.

Contact us for more information or to
arrange a demonstration of our products

Brandt Agricultural Products Ltd

P.O. Box 317
13th Ave and Pinkie Rd
Regina, Saskatchewan
Canada S4P 3A1

Toll: 1-866-427-2638
Phone: 1-306-525-1314
Email: agriculture@brandt.ca
Web: brandt.ca

Visit brandt.ca for a list of local Brandt equipment dealers.

