7R TRACTORS 210-350 Engine Horsepower





MOVING FORWARD

Multi-functional. The 7 Series Tractors precision ag offerings take a leap forward with G5^{Plus} display, StarFire[™] integrated receiver, and more. Multi-talented. The 7R Tractors include eight models ranging from 210 to 350 hp that deliver a refined cab, plus integrated intelligence and high power-density. With a base weight of 24,700lbs, the 7R 350 delivers 350 rated engine horsepower and 385 max engine horsepower^{*}. That makes it the best power-to-weight ratio of any John Deere large tractor.

Take advantage of three cab and visibility packages, fight fatigue on those long days with Triple Link Suspension (TLS[™]), AutoTrac[™] and enhanced steering ease with ActiveCommand Steering^{*} (ACS[™]) 2 or Reactive Steering. Plus, enjoy total tractor control at your fingertips with CommandPRO[™].

These are the large-hp, maneuverable tractors that deliver any task you need to accomplish in the field, barnyard or on the road.

*Max engine power PS (hp ISO) at max engine power speed (ECE-R120). The engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer and are to be used for comparison purposes only. Actual operating horsepower and torque may be less. Refer to the engine manufacturer's website for additional information.

2-3 Moving forward

4-5 Overview

6-7 Cab

8-9 Own the day

10-11 Own the night

12-13 Cab view

14-15 Precision ag technology

16-17 Power and efficiency

18-19 Transport

0

20-21 Hitches, axles, hydraulics

22-23 Maintenance and support

24-25 Parts and Service

26-27 Specifications

28 Dealer support

7R TRACTORS OVERVIEW

Large Cab

Select from three packages so your cab works the way you work. Features include an ergonomic seat, G5^{Plus} display and more.

LED Lighting

Make the most of your time, no matter the time, when you choose from three **Visibility Packages.** And with two times the LED light output compared to halogen bulbs, you can focus on the task at hand, not the amount of sunlight left.

Infinitely Variable Transmission (IVT)

Delivering the best in performance and operation, you can smoothly shift up from 0 to 26 or 31 mph (40 or 50 km/h) and any speed in between, including creeper speeds as low as 164 feet (50 m) per hour.

e23 PowerShift Transmission

Meet the demands of whatever conditions are thrown your way – and save on fuel costs - with three operating modes: FullAUTO, Custom, and Manual.

Integrated Intelligence:

■ G5^{Plus} display

The brighter, crisper displays and added processing power of the G5^{Plus} make applications you already use run even better. Like AutoTrac[™] Turn Automation, which lets you execute end rows easily and have a stress-free day in the cab. AutoPath[™] puts your secondary pass guidance lines where you want them, so you don't have to count rows or harvest a row of shame. With the new G5^{Plus} display, you'll get 35% more screen space to add additional maps and widgets, 3x faster processing for quicker boot times and clear 1080p HD resolution. It's all easier with the G5^{Plus}.^{*}

*Compared to previous model.

Integrated StarFire[™] Receiver

Get improved performance and dependability and reduce the time to achieve full signal accuracy with the integrated receiver.

■ JDLink^{™**}

JDLink connection is free and lets you see where your machines are, what they're doing and how they're performing. Simply turn on JDLink service in your Operations Center account.

■ AutoTrac[™]

Enjoy hands-free turns and reduced overlap, all while maximizing inputs and reducing fatigue.

Documentation & Data Sync

You'll get better data to make your decisions with Documentation and Data Sync standard in 7R tractors.

Rear Implement Ethernet

Be prepared to enable high speed data flow between the tractor and implement, once implement ethernet becomes available on planters and other implements. This will allow you to see more of your implement data faster than ever before.

**Activation required. JDLink hardware comes standard with the machine. The customer can turn on the JDLink service in their Operations Center account for free. JDLink requires a cellular connection to transfer information from machine to JDLink website. Consult your John Deere Dealer for coverage availability. 7R TRACTOR CAB

RIDE IN COMFORT

9° 6

Take a seat in the most comfortable chair in the industry. View displays easier when running applications with the bigger, clearer and faster G5^{Plus} display extended monitor. And get ready to log serious hours in comfort, style and peak productivity.

A higher backrest and adjustable side bolsters let you sit comfortably within the seat. Massaging feature helps keep you alert when you're spending long hours in the cab. And since the seat is heated and ventilated, you'll stay warm or cool depending on the season. Get all these features in the Ultimate Comfort & Convenience package.

SIGNATURE EDITION

F

1

-8-



Upgrade to the top of the line with the Signature Edition. The John Deere Signature Edition 7R Tractor includes the Ultimate Comfort and Convenience package, the Ultimate Visibility package, G5 CommandCenter[™], G5 Advanced licenses and Active Seat[™] II or air seat plus cab suspension.

Ultimate Comfort and Convenience package shown.

7R TRACTOR COMFORT AND CONVENIENCE PACKAGES

OWN THE DA

When the hours are long and the terrain is tough, there's no better place to be than our cab. Your home away from home. Easily step through the wide doorway into our most spacious cab. Enjoy more space than our previous cab, complete with extra headroom, extra storage capacity, and extra USB ports. Enjoy a cooler cab and better visibility to operator screens with rear window tint on the CommandView[™] 4 cab glass. Choose from these options; amenities vary by package. Discover more details at JohnDeere.com/7R or JohnDeere.ca/7R.

SELECT

PREMIUM

ULTIMATE

- Cloth seat with manual controls and manual lumbar support; 8° left-hand and 40° right-hand swivel
- AM/FM/WX radio with auxiliary and Bluetooth inputs; 4 speakers
- Business-band ready
- 4 USB ports and 12V outlet
- Dual-tilt steering column
- Foot rests

- Cloth seat with electronic controls and pneumatic lumbar support; 25° lefthand and 40° right-hand swivel
- 6.5-inch (16.5 cm) touchscreen radio, SiriusXM ready; 6 speakers with subwoofer
- Business-band ready
- 4 USB ports, 12V outlet
- Dual-tilt steering column
- Foot rests
- Refrigerator
- Right-hand accessory rail
- 120V outlet

- Leather seat with electronic controls, massage and pneumatic lumbar support; 25° left-hand and 40° righthand swivel; heated and ventilated; adjustable bolsters
- 6.5-inch (16.5 cm) touchscreen radio, SiriusXM ready;
 6 speakers with subwoofer
- Business-band ready
- 4 USB ports, 12V outlet
- Dual-tilt steering column
- Foot rests
- Refrigerator
- Right-hand accessory rail
- Carpeted floor mat
- Leather-wrapped steering wheel
- 120V outlet



7R TRACTOR VISIBILITY PACKAGES

OWN THE NIGHT

Take charge of your night when the daytime hours aren't enough. Our three new Visibility Packages are a bold leap forward, shedding new light on nighttime productivity. With the Ultimate Visibility Package, you'll experience two times more lighting than halogen bulbs thanks to the LED work lights. LEDs provide brighter, 360-degree illumination for those work days that turn into work nights. Amenities vary by package.

SELECT

- 18 Halogen work lights
- Mechanical exterior mirrors
- Front window sunshade
- Front and rear window wipers
- Camera ready

PREMIUM

- 18 LED work lights
- Electronic, heated exterior mirrors
- Front, right-hand, and rear window sunshades
- Front, right-hand, and rear window wipers
- Camera ready

ULTIMATE

- 22 LED work lights, 8 LED convenience lights
- Electric, heated, power telescoping exterior mirrors
- Front, right-hand, and rear window sunshades
- Front, right-hand, and rear window wipers
- Integrated cameras

10



7R TRACTOR CABS

ENJOY THE VIEW

JOHN DEERE

The view is amazing from any angle. Look at implements behind you with ease, thanks to three times more swivel to the left (compared to previous models). Pneumatic lumbar support and electronic controls let you make adjustments with ease.



Precision Ag Solutions

SEE MORE. KNOW MORE. DO MORE.

G5^{Plus} CommandCenter[™] Display

Bigger. Faster. Clearer.

Ready to see more? Know more? DO more? The G5^{Plus} CommandCenter[™] Display gives you a bigger picture of your 7R's performance and work in the field.

• 12.8-inch touchscreen – 35% larger to make on-the-go infield adjustments easier¹

0.0

1

11

A

1

2

3

4

B/

F2

0

18.6

AUTOTRA

(m)

2100

GUIDANCE

6.2

MPH

3.1

. 3.7 Manual

4

日)))

SECTION CTL

1 H

R2

- 3x faster processor ... for quicker boot times¹
- High resolution 1080p screen for brighter, clearer views
- 2 digital and 4 analog video camera inputs
- Essential to be ready for future autonomous and sense-and-act technology

The G5^{Plus} CommandCenter comes with a permanent AutoTrac[™] and Section Control license. And a permanent AutoTrac[™] RowSense[™] license is also available. And for even more automation productivity there's also an optional G5 Advanced Package that bundles our most popular precision tools. More than a display, this is your path to the future of precision ag. Experience the benefits of the larger, faster, and clearer display no matter the job.

John Deere Operations Center[®]:

Unlock the full power of your farm data.




Imagine, managing your farm operations anytime, anywhere. You can with John Deere Operations Center[™]. It's a free², online farm management system that enables 24/7 access to farm information through web, tablet, or mobile phone. Operations Center empowers you to manage your operation more efficiently, do a better job on every pass, reduce costs, and improve profitability.

With Operations Center, you can seamlessly connect data from your fields, your machines, and your operators and advisors. It puts at your fingertips all the information you need to maximize critical farm operations, from tillage, planting and seeding to applying and harvesting.

- Setup and manage your critical farm operations
- Plan work to reduce errors and gain efficiencies
- Monitor job quality and productivity in near real time
- Analyze this season's results to improve next season's crops

Compared with previous Generation 4 displays

² Activation required. JDLink hardware comes standard with the machine. The customer can turn on the JDLink service in their Operations Center account for free. JDLink requires a cellular connection to transfer information from machine to JDLink website. Consult your John Deere Dealer for coverage availability.



06:13

SCV

0

1

ISO

ISOBUS VT

SF-RTK

314

Client

(6)

?

HELP

H

MENU

8)

Farm

Field

Take your in-field productivity and performance to the next level with our optional G5 Advanced Package. It bundles some of Deere's most advanced precision ag tools into one easily renewable 1- or 3-year license. Tailored to your machines, G5 Advanced Package offers lower up-front cost, gets better over time, and you only pay for what your farm needs. Designed to make you more productive, more precise, and less stressed, the G5 Advanced Package includes:

AutoPath[™] – Forget guessing which guidance line to use, even in complex fields. No more counting rows in the field.

AutoTrac[™] Turn Automation – Gives you hands-off and stress-free confidence from one pass to the next. Consistently enter each pass square to reduce gaps and rework.

AutoTrac[™] Implement Guidance – Precise implement placement keeps spacing accurate, even on side hills or around curves.

In-Field Data Sharing – Day or night, between multiple machines and fields, you can share guidance lines, coverage maps, as-applied pass-to-pass data and field totals... without wasting time on radio chatter.

Machine Sync – On-the-go, stress-free unloading in every condition. Work faster, even with inexperienced grain cart operators.

7R TRACTORS POWER AND EFFICIENCY

SHIFT INTO HIGH GEAR

(e

The John Deere PowerTech[™] PVS 6.8L engine found in the 7R 210 features a single variable geometry turbocharger (VGT) that provides the torque rise and engine responsiveness to meet varying load conditions. Overall benefits of the PowerTech PVS 6.8L engine include great fuel economy and peak torque with quick response under load.

Featured in the 7R 230, 7R 250 and 7R 270, the **John Deere PowerTech PSS 6.8L** engine utilizes twin series turbochargers, one fixed and one VGT, that help maintain engine performance and provide a controlled pressure boost for added fuel economy.

The higher horsepower 7R 290, 7R 310, 7R 330 and 7R 350 include the **John Deere PowerTech PVS 9.0L** engine. With a single variable geometry turbocharger- this engine maximizes uptime while setting a new standard for the productivity, efficiency and performance you need.

Power of choice in transmissions. Choose from e23[™] PowerShift with Efficiency Manager[™] with 23 forward gears evenly spaced 15% apart to fit your different operating conditions and implements. Or the Infinitely Variable Transmission (IVT[™]) that lets you move smoothly from 0 to 26 or 31 mph (40 or 50 km/h) and any speed in between, including creeper speeds as low as 164 feet per hour with a single lever. You'll get a more comfortable ride when pulling a Large Square Baler with LSB Ride Control on 7Rs with IVT. This integrated technology learns from the disturbance to improve response and reduces active vibrations.

> CommandPRO[™] (IVT only) delivers seamless control of your tractor and implements all in the palm of your hand. Move from parked to top speeds with a simple push of a button. Eleven customizable buttons let you match functions to the job, with options to configure various set speeds to keep you in command.

7R TRACTORS TRANSPORT

AGILITY AND POWER: THE PERFECT COMBINATION

Hauling implements for transport is another big advantage of the 7R tractor lineup. With high horsepower, light weight and a compact chassis, the nimble 7R tractor delivers the pulling power you need and the drivability to move quickly and easily. Get an additional boost of up to 30 hp in transport or non-stationary PTO applications with Intelligent Power Management (IPM). The 7R 350 can tow implements up to 78 tons.



ActiveCommand Steering 2 (ACS[™] 2)

Optional ACS2 allows you to customize steering performance in the field or on the road, including steering sensitivity and resistance. You can also toggle variable ratio steering from the CommandCenter[™] Display.



I WERTH



Reactive Steering

Have more confidence when transporting an implement on the road thanks to the optional Reactive Steering. Reactive Steering features a steering wheel with force to return to center like an on-road vehicle, when activated.

7R TRACTORS HITCHES, AXLES, HYDRAULICS

that surrout

THE POWER-DRIVEN SUPPORT YOU NEED

With a rear hitch capacity of 17,300 lbs. (7,847 kg), you're set to pull large planters, and the optional front hitch has operations covered with front-mounted implements. A fully independent, 45-mm (1-³/₄-in.), 1000-rpm PTO is standard equipment and specially designed for high-power, heavy PTO loads. Get added load-bearing strength to handle large-capacity and extra-wide implements with an optional Category 4 drawbar.

The heavy-duty hydraulic system boasts plenty of reserve capacity to operate large hydraulic motors, even at reduced engine speeds. Triple Link Suspension (TLS[™]) delivers electro-hydraulic automatic engagement and gives you the drawbar pulling power you need in all operating conditions with reduced power hop.



CONNECTED TO WHAT COUNTS.

We know peace of mind is important to you. That's why we provide comprehensive protection and warranty packages – along with superior customer support – to keep your new 7R tractor operating at its best. From PowerGard[™] and John Deere Protect[™] to John Deere Connected Support, we have just what you need to keep running all year long.

POWERGARD

The PowerGard Protection Plan¹ offers valuable extended warranty coverage to protect your new 7R tractor from the unexpected and to ensure it's ready when you need it. PowerGard is available when purchased during the initial 12-month basic warranty² and provides two options:

- **Comprehensive** (for main components of the full machine)
- Limited (for main components of the engine and powertrain)

Other benefits of a PowerGard Protection Plan include:

- Select from a variety of flexible term lengths, in total months and total hours.
- No pre-approval of claims necessary. Call or visit any authorized John Deere dealership for service.
- Expert dealer technicians will fix it right, with exactly the right John Deere parts to fit your machine.
- Any remaining PowerGard coverage is fully transferable to a new owner, with no transfer fee.

Learn more at JohnDeere.com/PowerGard or JohnDeere.ca/PowerGard.

JOHN DEERE PROTECT

The John Deere Protect Maintenance Plus Plan is designed to help you maintain original performance and uptime of your new John Deere 7R tractor for the first 36 months/1,500 or 3,000 engine hours (with no deductible³ and no additional charges). You can buy the plan when purchased in conjunction with a PowerGard[™] Comprehensive Protection Plan⁴.

The John Deere Protect Maintenance Plus Plan⁵ includes:

- 3 Annual Expert Inspections
- 3 or 6 Scheduled Maintenance Events
- 24-Hour Uptime Assurance⁶

The three end-of-season expert inspections evaluate all critical areas of your 7R tractor and identify potential problems to prevent downtime; while the three or six scheduled preventive maintenance events keep the machine properly maintained for upcoming field work.

24-hour uptime assurance enables you to keep working if your 7R tractor cannot be repaired within 24 hours.

Learn more at JohnDeere.com or JohnDeere.ca.

The PowerGard Protection Plan does not cover attachments, maintenance or wear parts, nor other non-covered components specifically mentioned in the contract terms.

² All new John Deere 7R Series tractors come with a standard basic warranty of 12 months.
³ PowerGard deductible applies to any failures under PowerGard coverage.

extended service plans. Additional details are included in the selling descriptions of each included plan.

⁵ For complete plan details, contact a participating dealer near you.

⁶ Subject to machine availability, a rental machine will be provided while yours is being repaired.

⁷ Activation required. JDLink hardware comes standard with the machine. The customer can turn on the JDLink service in their Operations Center account for free. JDLink requires a cellular connection to transfer information from machine to JDLink website. Consult your John Deere Dealer for coverage availability.

⁴ PowerGard Comprehensive Protection Plan with a minimum term of 36 months/1,500 or 3,000 hours must be purchased separately to be eligible for John Deere Protect

CONNECTED SUPPORT

Your 7R tractor comes standard with JDLink⁷ hardware, and you can activate JDLink service for free from your Operations Center account. Once activated, your John Deere dealer offers the connection needed to keep you running when it's crunch time. With your approval, JDLink provides the bridge to proactive and predictive alerts that identify issues before they arise and from there, the dealer can remotely assess the problem saving you time and money.

Service ADVISOR[™] Remote

Allows your dealer to remotely analyze Diagnostic Trouble Codes in near real time so technicians arrive on-site with the right parts and the right tools to quickly repair your tractor.

Expert Alerts

An industry exclusive, Expert Alerts is a proactive monitoring system that notifies dealers of potential tractor issues. This allows technicians to remotely diagnose issues and fix them before they become a problem.

Remote Display Access

Lets your dealer remotely and quickly assist you with in-cab display setup and adjustments for optimal tractor performance.

Learn more at JohnDeere.com/ConnectedSupport or JohnDeere.ca/ConnectedSupport.

FIND WHAT YOU NEED AT THE ONE PARTS COUNTER

Your John Deere dealer makes sure to put the right people behind the parts counter. People who know the ins and outs of your new 7R tractor and have a clear understanding of your unique needs. Knowledgeable and trained, they can guide you to the right part, attachment or service (if needed) to fit your budget. Stop by the one parts counter today.

- * 12 month/unlimited hour warranty on new OEM agricultural parts installed by an authorized John Deere Dealer. 6 month/unlimited hour warranty for all new John Deere agricultural and turf equipment parts. See John Deere Service Parts Warranty US & Canada and participating dealers for more details.
- ** Financing on approved John Deere Financial credit only. Contact your Multi-Use Account merchant or dealer for complete details.

THE JOHN DEERE DIFFERENCE

- Right Part for Any Budget
- Highly Trained Expert Technicians
- 12 Months Parts & Labor Warranty*
- Short & Long Term Financing Options^{**}



Power Adapter/Power Strip

Install a convenient power source to the interior of your 7R tractor cab. Connect displays, monitors and other electronic devices into a 3-pin octagonal power adapter or a retrofit 6-outlet octagonal power strip.

RE596959: 3-Pin Octagonal Power Adapter

RE596958 & BRE10575: 6-Outlet Octagonal Power Strip & Mounting Rail



Category 4 Air Filtration

As our most advanced filtration system, Category 4 is engineered to reduce exposure and provide greater protection against harmful substances (particulates, aerosols and vapors) while operating your 7R.

BRE10588: Cat 4 Upgrade Field Kit



LSB Ride Control

Equip your 7R with Large Square Baler Ride Control, an integrated software system that slightly varies speed to mitigate tractor vibrations when paired with an LSB.

TR116947: LSB Ride Control Kit



Laforge® EZ Ballast® System

Tucked underneath the belly of the tractor, EZ Ballast provides 3,748 Ibs. (1700 kg) of ballast that is easily loaded and unloaded right from the 7R operator seat. Contact your dealer for details.



Mid-Stack Power Beyond

Add power beyond functionality to the mid-stack hydraulic valve to assist with hooking up large equipment to your 7R tractor – a valuable resource when multiple connections are required.

BXX10967: Mid-Stack Power Beyond



PTG Central Tire Inflation System

Due to our partnership with PTG, you can now have the benefit of monitoring and controlling tire pressure right from the comfort of your cab. Not compatible with 7R tractors equipped with a loader. Contact your dealer for details.

BXX10967: Mid-Stack Power Beyond

SPECIFICATIONS 7R TRACTORS

SPECIFICATIONS 7R TRA	<u>CTORS</u>									
Manufacturers Estimates	7R 210	7R 230	7R 250	7R 270	7R 290	7R 310	7R 330	7R 350		
POWER	and the second							1		
Rated PTO power (hp SAE) at rated engine speed (2100 erpm)*†	170 hp (126 kW)	189 hp (140 kW)	205 hp (152 kW)	224 hp (167 kW)	242 hp (180 kW)	260 hp (193 kW)	260 hp (193 kW)	260 hp (193 kW)		
Rated engine power PS (hp ISO) at rated engine speed (ECE-R12O)*	210 hp (154 kW)	230 hp (169 kW)	250 hp (184 kW)	270 hp (199 kW)	290 hp (213 kW)	310 hp (228 kW)	330 hp (243 kW)	350 hp (257 kW)		
Max engine power PS (hp ISO) at 1900 engine rpm (ECE-R120)*	231 hp (170 kW)	253 hp (186 kW)	275 hp (202 kW)	297 hp (218 kW)	319 hp (235 kW)	341 hp (251 kW)	363 hp (267 kW)	385 hp (283 kW)		
Intelligent Power Management* (Available)		1	1	30	1	1		25		
Additional engine horsepower PS (hp ISO) at 2,100 RPM (rated speed)*		(0%			1		(0%	25		
PTO torque rise PTO power bulge		40%		38%			40%			
ENGINE				10.6						
Manufacturer (EU Stage V)		John Deere Po	werTech™ 6.8L			John Deere F	PowerTech™ 9.0L			
Rated speed				2,100) rpm					
Aspiration (US EPA Final Tier 4)	Single turbocharger,	Dual turboc	hargers, variable geomet æd geometry turbo in ser	ry turbo with			urbocharger,			
Filter, engine air	variable geometry turbo	TD TD	variable gi	variable geometry turbo						
Displacement		415 cu ir	n (6.8L)	Dual		549 c	u in (9.01.)			
Bore and stroke	415 cu in (6.8L) 549 cu in (9.0L) 4.19 in (106 mm) x 5.00 in (127 mm) 4.66 in (118.4 mm) x 5.35 in (136 mm)									
Compression ratio	17.2:1		16.7:1			1	16.0:1			
Lubrication				Full-pressure, full-flov	filtration with bypass					
Filter, oil				Replaceable cartr						
FUEL SYSTEM				high-pressure common ra						
Filter system Filter, primary				o stage with water separa n replaceable cartridge w						
Filter, secondary			TO THICTO	2 micron spir						
TRANSMISSIONS				2 meiori spi	on ciclicit					
e23 PowerShift 40K, 26 mph (40 km/h)	Standard (42 km/h @ 1	1680 rom w/aro 47 tires 4	2 km/h @ 1600 rpm w/a	n 48 tires 42 km/h @ 157	() rom w/aro 49 tires)		600 rpm w/grp 48 tires,	NA		
erst onersine roll, zompritto kni/h)	Standard (42 km/n @ 1680 rpm w/grp 47 tires, 42 km/n @ 1600 rpm w/grp 48 tires, 42 km/n @ 1520 rpm w/grp 49 tires) 4_2						rpm w/grp 49 tires)	114		
e23 PowerShift 50K, 31 mph (50 km/h)	Available (50 km/h @ 2	000 rpm w/grp 47 tires, 5	0 km/h @ 1900 rpm w/gi	rp 48 tires, 50 km/h @ 180	00 rpm w/grp 49 tires)		900 rpm w/grp 48 tires, rpm w/grp 49 tires)	NA		
John Deere Infinitely Variable Transmission, 26	Austhalia (42 June (h. Q.)	1//0 /7 /7	2 June / In @126.0 marries / ma	. (0 time (2 log (b @ 120	0 (0 +i)	-	(42 km/h @ 1360 rpm w/c	grp 48 tires,		
mph (42 km/h)	Available (42 km/h @ 1440 rpm w/grp 47 tires, 42 km/h @1360 rpm w/grp 48 tires, 42 km/h @ 1290 rpm w/grp 49 tires) 42 km/h @ 1290 rpm w/grp 49 tires)									
John Deere Infinitely Variable Transmission, 31 mph (50 km/h)	Available (50 km/h @ 1800 rpm w/grp 47 tires, 50 km/h @ 1700 rpm w/grp 48 tires, 50 km/h @ 1620 rpm w/grp 49 tires) 50 km/h @ 1620 rpm w/grp 49 tires)									
ELECTRICAL SYSTEM				Two b	atteries in parallel	100	ann n @ 10201pin w/gip 4.	Juies		
Alternator/Battery			St	andard: 210 amp / 12 volt,		volt				
Total cold cranking amps					grp 31 batteries)					
REAR AXLE FINAL DRIVES										
Description					ary three pinion					
REAR AXLES 110 x 3010 mm diameter (4.33 x 118.5 in)					and-pinion			NA.		
110 x 2550 mm diameter (4.33 x 118.5 in)	Standard NA Available NA									
110 x 2808 mm diameter (4.33 x 110.5 in)				Available				NA		
10 x 2000 1111 didifecter (1.55 x 10.5 11)	Available									
120 x 2550 mm diameter (4.72 x 100.4 in)				Avai	able			1		
120 x 2550 mm diameter (4.72 x 100.4 in) 120 x 3010 mm diameter (4.72 x 118.5 in)				Avai Available	able			Standard		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT				Available	able			1		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description		Group 47/4	8/49 tires available as sin	Available	able	Group 4	+8/49 tires available as sin	1		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES	NA	Group 47/4-		Available	able			1		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description	NA	Group 47/4:	Standard	Available	able		+8/49 tires available as sin NA	1		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm)	NA		Standard	Available	able			igles/duals		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in. (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM	NA		Standard	Available gles/duals Available Closed-center, pressu	re/flow compensated			gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in. (1524 to 2235 mm) TLS with forth takes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves	NA		Standard	Available gles/duals Available Closed-center, pressu Standard: 4, /	e/flow compensated vailable: 5 - 6			gles/duals NA		
120 x 3010 mm diameter (4, 72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in. (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement)	NA		Standard	Available gles/duals Available Closed-center, pressu Standard: 4, / Standard: 63 cc,	re/flow.compensated wailable: 5 - 6 Available: 85 cc			gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in. (1524 to 2235 mm) TLS with forth takes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves	NA		Standard	Available gles/duals Available Closed-center, pressu Standard: 4, /	e/flow compensated wailable: 5 - 6 Available: 85 cc 0 + or- 300 kPa)			gles/duals NA		
120 x 3010 mm diameter (4,72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated Flow, 63cc pump Rated flow, 85cc pump	NA		Standard	Available gles/duals Closed-center, pressu Standard: 4, A Standard: 63 cc, 2,958 psi (20,40 43 US gpn 59 US gpn	re/flow compensated vailable: 5 - 6 Available: 85 cc 0 + or- 300 kPa } (162.1pm) 1 (223 1pm)			gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in. (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 83cc pump Rated flow, 83cc pump Rated flow, 83cc pump	NA		Standard	Available gles/duals Closed-center, pressu Standard: 4, / Standard: 63 cc, 2,958 psi (20,40 43 US gpn 59 US gpn 35 US gpn 35 US gpn	e/flow compensated vailable: 5 - 6 Available: 85 cc 0 + or- 300 kPa) (162 lpm) 1(32 lpm)			gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 83cc pump Rated flow, 83cc pump Rated flow at a single rear SCV Available flow at a single front SCV	NA		Standard	Available gles/duals Closed-center, pressu Standard: 63 cc, 2,958 psi (20,40 43 US gpn 35 US gpn 35 US gpn 33 US gpn 33 US gpn	e/flow compensated wailable: 5 - 6 Available: 85 cc 0 + or- 300 kPa) (162.lpm) (122.lpm) (122.lpm) (122.lpm)			gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in. (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 83cc pump Rated flow, 83cc pump Rated flow, 83cc pump	NA		Standard	Available gles/duals Closed-center, pressu Standard: 63 cc, 2,958 psi (20,40 43 US gpn 35 US gpn 35 US gpn 33 US gpn 33 US gpn 33 US gpn	e/flow compensated wailable: 5 - 6 Available: 85 cc 0 + or- 300 kPa) (162.lpm) (122.lpm) (122.lpm) (122.lpm)			gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD- tread range 60 to 88 in (1524 to 2235 mm) TLS uth front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63cc pump Rated flow, 63cc pump Rated flow, 63cc pump Rated flow, 85cc pump Available flow at a single rear SCV Available flow at a single front SCV Take out oil capacity 3-POINT HICH - REAR Category 3/3N w/ Quick-Coupler	NA		Standard able	Available gles/duals Closed-center, pressu Standard: 4, A Standard: 63 cc, 2,958 psi (20,40 43 US gpn 35 US gpn 35 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 15, 20	e/flow compensated vailable: 5 - 6 Available: 85 cc 0 + or - 300 kPa) (162 Jpm) 1 (122 Jpm) 1 (123 Ipm) 1 (126 Jpm) Je: 85 L (aux reservoir) addit sensing 00 lb (6894 kg)	Standard		gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 83cc pump Rated flow, 83cc pump Rated flow, 83cc pump Rated flow, 83cc pump Rated flow at a single rear SCV Available flow at a single front SCV Take out oil capacity 3-POINT HITCH - REAR Category 3/3N w/ Quick-Coupler	NA		Standard able	Available gles/duals Closed-center, pressu Standard: 63 cc, 2,958 psi (20,40 43 US gpn 35 US gpn 35 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 15,20 vailable: 17,300 lb (7847 ks	e/flow compensated wailable: 5 - 6 Available: 85 cc 0 + or- 300 kPa } (122 lpm) (122 lpm) (126 lpm) (126 lpm) be: 85 L (aux reservoir) aulic sensing 00 lb (6894 kg) g) (requires 120mm dia a	Standard		gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONTAXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63cc pump Rated flow, 63cc pump Rated flow, 63cc pump Rated flow, 63cc pump Available flow at a single front SCV Take out oil capacity 3-POINT HITCH - REAR Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO)	NA		Standard able	Available gles/duals Closed-center, pressu Standard: 63 c, 2,958 psi (20,40 43 US gpn 59 US gpn 35 US gpn 33 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 15, 20 vailable: 17,300 Ib (1847 K indep	e/flow compensated Available: 5 - 6 Available: 85 cc 0 + or- 300 kPa) 1(62 lpm) 1(22 lpm) 1(23 lpm) 1(126 lpm) ole: 85 L (aux reservoir) aulic sensing 10 lb (6894 kg) J (frequires 120mm dia a endent	Standard		gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63cc pump Rated flow, 63cc pump Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO)	NA		Standard able	Available gles/duals Closed-center, pressu Standard: 63 cc, 2,958 psi (20,40 43 US gpn 59 US gpn 35 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 15,20 vailable: 17,300 lb (7847 ks Indee Stan	e/flow compensated Available: 5 - 6 Available: 85 cc 0 + or- 300 kPa } 1(162 lpm) 1(232 lpm) 1(125 lpm) 1(126 lpm) aulic sensing 101 b (6894 kg) 0 (frequires 120mm dia a endent dard	Standard		gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONTAXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63cc pump Rated flow, 63cc pump Rated flow, 63cc pump Rated flow, 63cc pump Rated flow at a single rear SCV Available flow at a single ront SCV Take out oil capacity 3-POINT HITCH - REAR Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1 ³ /s in 540/1000 rpm	NA		Standard able	Available gles/duals Closed-center, pressu Standard: 63 cr, 2,958 psi (20,40 43 US gpn 55 US gpn 35 US gpn 33 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Closef Standard: 15,20 vailable: 17,300 bb (7847 k Indep Standard: Avai	e/flow compensated wailable: 5 - 6 vailable: 85 cc 0 + or- 300 kPa) 1(162 lpm) 1(223 lpm) 1(123 lpm) 1(126 lpm) ole: 85 L (aux reservoir) aulic sensing 00 lb (6894 kg) 0) frequires 120mm dia a endent dard able	Standard		gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONTAXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63cc pump Rated flow at a single rear SCV Available flow at a single rear SCV Take out oil capacity 3-POINT HITCH - REAR Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1.3/ ₈ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1.3/ ₈ in 540/1000 rpm	NA		Standard able	Available gles/duals Closed-center, pressu Standard: 63 c, 2,958 psi (20,40 43 US gpn 35 US gpn 35 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Closef (1,7,300 lb (7847 k undep) Standard: 15, 20 vailable: 17,300 lb (7847 k Indep) Stan	e/flow compensated Available: 5 - 6 Available: 85 cc 0 + or- 300 kPa) (162 lpm) 1(22 lpm) 1(126 lpm) 1(126 lpm) 1(126 lpm) 1(126 lpm) 1016 lb (6894 kg) 1) (requires 120mm dia a endent dard able able	Standard		gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONTAXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63 cc pump Rated flow, 63 cc pump Rated flow, 63 cc pump Rated flow, 63 cc pump Rated flow, 63 cc pump Cavailable flow at a single front SCV Take out oil capacity 3-POINT HITCH - REAR Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1.3/ ₈ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1.3/ ₈ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1.3/ ₈ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1.3/ ₈ in 540/1000 rpm	NA		Standard able	Available gles/duals Closed-center, pressu Standard: 63 c, 2,958 psi (20,40 43 US gpn 35 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Closed-construction Standard: 15, 20 vailable: 17,300 lb (7847 k Indep Stan Avai Avai	e/flow compensated Available: 5 - 6 Available: 85 cc 0 + or- 300 kPa } (162.lpm) 1 (126.lpm) 1 (126.lpm) 1 (126.lpm) Je: 85 L. (aux reservoir) aulic sensing 10 lb (6894 kg) J [frequires 120mm dia a endent dard able able	Standard xle]		gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONTAXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63 cc pump Rated flow, 63 cc pump Rated flow, 63 cc pump Available flow at a single front SCV Take out oil capacity 3-POINT HITCH - REAR Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-3/ ₄ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-3/ ₄ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-3/ ₄ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-3/ ₄ in 540/1000 rpm PIO Speed @ Engine rpm	NA		Standard able	Available gles/duals Closed-center, pressu Standard: 63 c, 2,958 psi (20,40 43 US gpn 35 US gpn 35 US gpn 35 US gpn 35 US gpn 35 US gpn 13 US gpn 13 US gpn 13 US gpn 13 US gpn 14 US gpn 15 US gpn 15 US gpn 16 US gpn 17 US gpn 18 US gpn	e/flow compensated Available: 5 - 6 Available: 85 cc 0 + or- 300 kPa) 1(62 lpm) 1(22 lpm) 1(126 lpm) 1(126 lpm) 1(126 lpm) 101 b (6894 kg) 201 b (6894 kg) 201 frequires 120mm dia a endent dard dard able able 540E/1000E PTO rpm (Standard xle]		igles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63 cc pump Rated flow, 64 cc pump Rated flow, 63 cc pump Rated flow, 63 cc pump Rated flow, 64 cc pump Rated flow, 65 cc pump Rated flow, 64 cc pump Rated flow, 6	NA		Standard able A (540/1000 PTO r	Available gles/duals Closed-center, pressu Standard: 63 cc, 2,958 psi (20,40 43 US gpn 35 US gpn 35 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Electrohydr Standard: 15, 20 vailable: 17,300 lb (7847 k Indep Stan Avai Avai Avai	e/flow compensated Available: 5 - 6 Available: 85 cc 0 + or- 300 kPa } 1(22 Jpm) 1(22 Jpm) 1(122 lpm) 1(126 lp	Standard xle]		igles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONTAXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63 cc pump Rated flow, 63 cc pump Rated flow, 63 cc pump Available flow at a single front SCV Take out oil capacity 3-POINT HITCH - REAR Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-3/ ₄ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-3/ ₄ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-3/ ₄ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-3/ ₄ in 540/1000 rpm PIO Speed @ Engine rpm	NA		Standard able A (540/1000 PTO r	Available gles/duals Closed-center, pressu Standard: 63 c, 2,958 psi (20,40 43 US gpn 35 US gpn 35 US gpn 35 US gpn 35 US gpn 35 US gpn 13 US gpn 13 US gpn 13 US gpn 13 US gpn 14 US gpn 15 US gpn 15 US gpn 16 US gpn 17 US gpn 18 US gpn	e/flow compensated Available: 5 - 6 Available: 85 cc 0 + or- 300 kPa } 1(22 Jpm) 1(22 Jpm) 1(122 lpm) 1(126 lp	Standard xle]		gles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63 cc pump Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1-¼ in, 20-spline, 1,000-rpm; capable of 1-¼ in 540/1000/n000E rpm 1-¼ in, 20-spline, 1,000-rpm; capable of 1-¼ in 540/1000 rpm PTO Speed @ Engine rpm 3-POINT HITCH - FRONT Lift capacity through full lift range, with hook style ends Imeasured 24 in behind hook point, OECD)	NA		Standard able (540/1000 PTO 6 6,994 lb (315)	Available (gles/duals Closed-center, pressu Standard: 4, 4 Standard: 63 cc, 2,958 psi (20,40 43 US gpn 35 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 15,2 vailable: 17,300 lb (7847 kg Indep Standard: 52 kandard: 15,2 vailable: 17,300 lb (7847 kg Indep Standard: 52 kandard: 15,2 (ndep Standard: 52 kandard: 52 kan	e/flow compensated wailable: 5 - 6 Available: 85 cc 0 + or - 300 kPa) (162 lpm) (122 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (132	Standard xle] p 1750 engine rpm) ium front hitch)		igles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63 cc pump Rated flow, 43 single rear SCV Available flow at a single ront SCV Take out oil capacity 3-POINT HITCH - REAR Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1-1/4 in, 20-splne, 1,000-rpm, capable of 1-1/4 in 540/1000 rpm 1-1/4 in, 20-splne, 1,000-rpm, capable of 1-1/4 in 540/1000 rpm 1-1/4 in, 20-splne, 1,000-rpm, capable of 1-1/4 in 540/1000 rpm 1-1/4 in, 20-splne, 1,000-rpm, capable of 1-1/4 in 540/1000 rpm 1-1/4 in, 20-splne, 1,000-rpm, capable of 1-1/4 in 540/1000 rpm PTO Speed @ Engine rpm 3-POINT HITCH - FRONT Lift capacity through full lift range, with hook style ends (measured 24 in behind hook point, OECD)	NA		Standard able (540/1000 PTO 6 6,994 lb (315)	Available gles/duals Closed-center, pressu Standard: 63 cc, 2,958 psi (20,40 43 US gpn 35 US gpn 35 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Electrohydr Standard: 15, 20 vailable: 17,300 lb (7847 k Indep Stan Avai Avai Avai	e/flow compensated wailable: 5 - 6 Available: 85 cc 0 + or - 300 kPa) (162 lpm) (122 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (132	Standard xle] p 1750 engine rpm) ium front hitch)		igles/duals NA		
120 x 3010 mm diameter (4, 72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 85cc pump Rated flow, 85cc pump Rated flow, 85cc pump Rated flow, 85cc pump Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1 ¹ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1000/1000E rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1540E/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1540E/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1540E/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1540E/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1540E/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1540E/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1540E/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm; capable of 1-3/s in 540/1540E/1000 rpm 1 ³ / ₄ in, 20-spline, 1,	NA		Standard able (540/1000 PTO 6 6,994 lb (315)	Available (gles/duals Available Closed-center, pressu Standard: 4, <i>J</i> Standard: 63 c, 2,958 psi (20,40 43 US gpn 35 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Electrohydr Standard: 52 vailable: 17,300 lb (7847 ks Indep Standard: 52 vailable: 17,300 lb (7847 ks Indep Standard: 52 Availat Avai Avai Avai Avai Avai Categ D kg) lift capacity (ground	e/flow compensated wailable: 5 - 6 Available: 5 - 6 1 - 0 - 300 kPa 1 (162 lpm) (123 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (132 l	Standard xle] p 1750 engine rpm) ium front hitch)		igles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63 cc pump Rated flow, 43 single rear SCV Available flow at a single ront SCV Take out oil capacity 3-POINT HITCH - REAR Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1-1/4 in, 20-splne, 1,000-rpm, capable of 1-1/4 in 540/1000 rpm 1-1/4 in, 20-splne, 1,000-rpm, capable of 1-1/4 in 540/1000 rpm 1-1/4 in, 20-splne, 1,000-rpm, capable of 1-1/4 in 540/1000 rpm 1-1/4 in, 20-splne, 1,000-rpm, capable of 1-1/4 in 540/1000 rpm 1-1/4 in, 20-splne, 1,000-rpm, capable of 1-1/4 in 540/1000 rpm PTO Speed @ Engine rpm 3-POINT HITCH - FRONT Lift capacity through full lift range, with hook style ends (measured 24 in behind hook point, OECD)	NA	Avail	Standard able (540/1000 PT0 1 6,994 lb (3151 7,690 lb (3481	Available (gles/duals Closed-center, pressu Standard: 4, 4 Standard: 63 cc, 2,958 psi (20,40 43 US gpn 35 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Electrohydr Standard: 15, 2 vailable: 17,300 lb (7847 kg Indep Standard: 52 L avai Avai	e/flow compensated wailable: 5 - 6 Available: 85 cc 0 + or- 300 kPa } (122 lpm) (122 lpm) (122 lpm) (126 lpm) ble: 85 L (aux reservoir) aulic sensing 00 lb (6894 kg) g) [requires 120mm dia a endent dard dard dable able able engaging requires prem engaging requires prem engaging requires prem	Standard xle]) 1750 engine rpm) ium front hitch) ium front hitch)	NA	igles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63 cc pump Rated flow, 43 single rear SCV Available flow at a single ront SCV Take out oil capacity 3-POINT HITCH - REAR Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-3/ ₄ in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-3/ ₄ in 540/1000 rpm PTO Speed @ Engine rpm 3-POINT HITCH - FRONT Lift capacity through full lift range, with hook style ends Imeasured 2/4 in behind hook point, OECD) Lift capacity through full lift range, with hook style ends Imeasured 2/4 in behind hook point, OECD) INTEGRATED TECHNOLOGY Integrated AutoTrac [®] Modular Telematics Gateway (MTG) Service Advisor [®] Remote		Avail	Standard able (540/1000 PT0 1 6,994 lb (3151 7,690 lb (3481	Available gles/duals Closed-center, pressu Standard: 63 cc, 2,958 psi (20,40 43 US gpn 39 US gpn 33 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Electrohydr Standard: 15,7 k uailable: 17,300 lb (7847 k Indep Stan Avai Avai Avai Avai Categ D (g) lift capacity (ground B (g) lift capacity (ground	e/flow compensated wailable: 5 - 6 Available: 85 cc 0 + or- 300 kPa) 1(62 lpm) 1(22 lpm) 1(12 lpm) 1(12 lpm) 1(12 fpm) 1(12 fpm) 10 lb (6894 kg) 10 lb (6894 kg) 10 le (6894	Standard Standard xle] 7150 engine rpm) ium front hitch) ium front hitch)	NA	igles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 85cc pump Rated flow, 85cc pump Rated flow, 85cc pump Rated flow, 85cc pump Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ² / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ⁴ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ⁴ / ₄ in, 20-spline, 1,000-rpm,	NA	Avail	Standard able (540/1000 PT0 1 6,994 lb (3151 7,690 lb (3481	Available (losed-center, pressu Standard: 4, 4 Standard: 4, 7 Standard: 63 c, 2,958 psi (20,40 43 US gpn 35 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availab Electrohydr Standard: 15, 2 vailable: 17,300 lb (7847 kg Indep Standard: 52 Available: 17,300 lb (7847 kg Indep Standard: 52 Available: 17,300 lb (7847 kg Indep Standard: 52 Available: 17,300 lb (7847 kg Categ 0 kg) lift capacity (ground Stan are, activations, and ether Available with JDLink" + Availablei with JDLink "	e/flow compensated wailable: 5 - 6 Available: 5 - 6 I - 0 - 300 kPa) (162 lpm) (122 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (127 l	Standard Standard xle] 7150 engine rpm) ium front hitch) ium front hitch)	NA	igles/duals NA		
120 x 3010 mm diameter (4, 72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 85cc pump Rated flow, 85cc pump Rated flow, 85cc pump Available flow at a single rear SCV Available flow at a single rear SCV It (apacity through full fitr range, with hook style ends Imeasured 24 in behind hook point, OECD) Ifte capacity through full fitr range, with hook style ends Imeasured AutoTrac [®] Modular Telematics Gateway (MTG) Service Advisor [®] Remote Command Center [®] A in [23 mm] w/ 4600 processor Command Center [®] A in [23 mm] w/ 4600 processor	NA	Avail	Standard able (540/1000 PT0 1 6,994 lb (3151 7,690 lb (3481	Available gles/duals Closed-center, pressu Standard: 63 cr, 2,958 psi (20,40 43 US gpn 35 US gpn 35 US gpn 33 US gpn 33 US gpn 33 US gpn 33 US gpn 13 US gpn 14 US gpn 33 US gpn 33 US gpn 33 US gpn 33 US gpn 34 US gpn 34 US gpn 35 US gpn 35 US gpn 35 US gpn 35 US gpn 35 US gpn 36 US gpn 37 US gpn 38 US gpn 39 US gpn 39 US gpn 30 US	e/flow compensated wailable: 5 - 6 Available: 5 - 6 I - 0 - 300 kPa) (162 lpm) (122 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (127 l	Standard Standard xle] 7150 engine rpm) ium front hitch) ium front hitch)	NA	igles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULIC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 85cc pump Rated flow, 85cc pump Rated flow, 85cc pump Rated flow, 85cc pump Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ¹ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ² / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ³ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ⁴ / ₄ in, 20-spline, 1,000-rpm, capable of 1-1/s in 540/1000 rpm 1 ⁴ / ₄ in, 20-spline, 1,000-rpm,		Avail	Standard able (540/1000 PT0 1 6,994 lb (3151 7,690 lb (3481	Available gles/duals Closed-center, pressu Standard: 4, <i>I</i> Standard: 63 c, 2,958 psi (20,40 43 US gpn 35 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Electrohydr Standard: 15, 20 vailable: 17,300 lb (7847 k Indep Stan Avai Avai Avai Avai (pm @ 1950 engine rpm) (Categ 0 kg) lift capacity (ground 8 kg) lift capacity (ground are, activations, and ether Available with JDLink" 1 Available with JDLink" 1 Available with JDLink" 1	e/flow compensated wailable: 5 - 6 Available: 5 - 6 I - 0 - 300 kPa) (162 lpm) (122 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (126 lpm) (127 l	Standard Standard xle] 7150 engine rpm) ium front hitch) ium front hitch)	NA	igles/duals NA		
120 x 3010 mm diameter (4.72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63 cc pump Rated flow, 63 cc pump Rated flow, 63 cc pump Rated flow, 63 cc pump Rated flow, 63 cc pump Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1-½/, in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/, in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/, in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/, in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/, in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/, in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/, in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/, in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm, capable of 1-½/ in 540/1000 rpm 1-½/ in, 20-spline, 1,000-rpm 1-½/ in, 20-spline, 1,000		Avail	Standard able (540/1000 PT0 1 6,994 lb (3151 7,690 lb (3481	Available gles/duals Closed-center, pressu Standard: 4, <i>J</i> Standard: 63 c, 2,958 psi (20,40 43 US gpn 35 US gpn 33 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availab Electrohydr Standard: 15, 20 vailable: 17,300 lb (7847 k Indep Stan Avai Avai Avai Avai Avai Avai Avai Avai Avai Avai Avai Stan Avai Avai Avai Stan Avai Avai Avai Stan Avai	e/flow compensated Available: 5 - 6 Available: 85 cc 0 + or- 300 kPa) (162 lpm) 1 (223 lpm) 1 (126 lp	Standard Standard xle] 7150 engine rpm) ium front hitch) ium front hitch)	NA	Igles/duals NA Standard		
120 x 3010 mm diameter (4, 72 x 118.5 in) REAR WHEEL EQUIPMENT Description FRONT AXLES 1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS - tread range 60 to 88 in (1524 to 2235 mm) TLS with front brakes, available with 40km/h, standard with 50km/h HYDRAULC SYSTEM Selective control valves Main pump, axial piston (displacement) Maximum pressure Rated flow, 63cc pump Rated flow, 63cc pump Rated flow, 63cc pump Rated flow, 63cc pump Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler Category 3/3N w/ Quick-Coupler REAR POWER TAKE OFF (PTO) 1-½/in, 20-spline, 1,000-rpm, capable of 1-½/in 540/1000 rpm 1-½/in, 20-spline, 1,000-rpm 1-½/in, 2		Avail	Standard able (540/1000 PT0 1 6,994 lb (3151 7,690 lb (3481	Available gles/duals Closed-center, pressu Standard: 4, <i>I</i> Standard: 63 c, 2,958 psi (20,40 43 US gpn 35 US gpn 33 US gpn 33 US gpn Standard: 65 L, Availat Electrohydr Standard: 65 L, Availat Electrohydr Standard: 15, 20 vailable: 17,300 lb (7847 k Indep Stan Avai Avai Avai Avai (pm @ 1950 engine rpm) (Categ 0 kg) lift capacity (ground 8 kg) lift capacity (ground are, activations, and ether Available with JDLink" 1 Available with JDLink" 1 Available with JDLink" 1	e/flow compensated wailable: 5 - 6 Available: 85 cc 0 + or- 300 kPa } (162.1pm) 1 (223 1pm) 1 (226 1pm)	Standard Standard xle] 7150 engine rpm) ium front hitch) ium front hitch)	NA	Igles/duals NA Standard		

Specifications and design subject to change without notice. Pre-production models shown. *John Deere Standard RES10080, SAE Standards J1995. The engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer and are to be used for comparison purposes only. Actual operating horsepower and torque may be less. Refer to the engine manufacturer's website for additional information. † PTO power for IVT models. Does not include available equipment losses. Nominal data is metric. Standard data is converted from metric data. Use metric for all calculations.

Manufacturers Estimates	7R 210	7R 230	7R 250	7R 270	7R 290	7R 310	7R 330	7R 350		
WHEELBASE										
MFWD / TLS	115.2 in (2925 mm)									
MFWD / TLS axle clearance - 1300 axle, G43 420/85R34 tires	19.5 in (495 mm)									
Turning radius - 380/85R34 group 42 tires @ 60" spacing, 1300			23 ft (7 m)				NA			
Turning radius - 600/70R30 group 43 tires @ 74.1" spacing TLS	22 ft (6.7 m)									
Turning radius - 620/75R30 group 44 tires @ 82" spacing, TLS	28.5 ft (8.7 m)									
See OM for additional configurations										
AVERAGE BASE WEIGHT										
IVT, 85cc pump, 4 SCVs, PTO, CAT4 drawbar, 600/70R30 front tires, 710/70R42 rear tires, TLS, front hitch	25,700 lb (11700 kg)									
IVT, 85cc pump, 6 SCVs, PTO, CAT4 drawbar, 480/70R34 front tires, 480/80R50 rear tires, TLS	24,300 lb (11000 kg)									
e23, 63cc pump, 4 SCVs, PTO, CAT3 drawbar, 18.4R46 rear tires, 420/90R30 rear tires, TLS	22,200 lb (10000 kg)						NA			
Max ballast level	145 lbs/SAE PTO HP - see OM for specific ballast instructions				135 lbs/SAE PTO HP - see OM for specific ballast instructions					
Max payload capacity	See OM for details on tractor loading									
CAB										
Cab glass area	70.61 sq ft (6.56 sq m)									
Cab volume	114.42 cu ft (3.24 cu m)									



Supported by one of the most responsive dealer networks in the business

Nobody cares more about keeping your equipment in solid working order than your John Deere dealer. With a complete inventory of genuine John Deere parts, highly trained service technicians, and a thorough understanding of your business, your John Deere dealer knows how to keep you and your equipment up and running.

A strong name in equipment, and a strong dealership network: get it all with John Deere.

This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification and design of all products described in this literature without notice. John Deere, the leaping deer symbol, and green and yellow trade dress are trademarks of Deere & Company Copyright 2023 Deere & Company.

