

Email: sales@harcoag.ca

www.harcoag.ca

# Are you standing around splitting wood? Why not do your wood splitting sitting down?







Halverson

Wood Products. Inc.



File Section: 5, Page 14 Effective Date: June 1, 2024

#### **Features**

- Simple to operate controls
- Sets up in minutes
- Auto chain oiler
- Multiple splitting head options available
- The most portable processor on the market
- 102" width it can be legally transported attached to your skid steer
- Processes logs up to 10 feet in length and 16 inches in diameter

#### **Advantages**

- One-man operation
- Few moving parts
- Ready to go in minutes
- Stay-in-the-machine operation for safety and comfort
- Small, easy to store
- Can process right into a truck or trailer without a conveyor
- Totally portable; no set up or tear down to move or store

Easy to adjust and change cutting length 22" maximum cut length

#### **Specifications**

- Required minimum hydraulic flow 15.5 Gallons
   Per Minute
- Required Minimum Pressure 2850 PSI
- Length 102 Inches
- Weight 1310 lbs
- Universal Quick Attach Skid Steer Plate
- Universal wiring harness plugs into the power port of your machine

#### Uses

- Tree Services
- Firewood Operations
- Farmers
- Outdoor Boiler Owners
- Logging/Firewood
- Homeowner

#### Warranty

- 6 Months to 1 year Warranty
- Fast Factory Support

#### **Productions**

■ 1 ½ - 2 Cords Per Hour


# www.halversonwoodproducts.com

PRICED IN CANADIAN DOLLARS



Email: sales@harcoaq.ca

www.harcoag.ca





#### Compare us to the competition and you'll see why wood cutting & splitting is experiencing a REVOLUTION!


	HWP-100	HWP-120	HWP-125GS	HWP-1408	HWP-150	HWP-150 EXTENDED
LENGTH	Travel= 80" (203 cm)	Travel= 99" (203251 cm)	33" (84 cm)	Travel= 102" (259 cm)	Travel= 107* (272 cm)	Travel= 121" (307 cm)
	Working= 100 (254 cm)	Working= 121" (307cm)		Working= 126" (320 cm)	Working= 129* (328 cm)	Working= 143" (363 cm)
WIDTH	41" (104 cm)	SS" (140 cm)	46" (142 cm)	55" (140 cm)	58" (147 cm)	58" (147 cm)
HEIGHT	41" (104 cm)	51" (130 cm)	41" (104 cm)	51" (130 cm)	57" (145 cm)	57" (145 cm)
WEIGHT	706 lbs (320 kg)	1280 lbs. (581 kg)	770 lbs. (349 kg)	1450 lbs. (658 kg)	1638 lbs. (743 kg)	1905 lbs. (864 kg)
MATERIAL	3/16" Steel	1/4" Steel	3/8" & S/8" Steel	3/8" Steel	3/8" Steel	3/8" Steel
-MINIMUM PRESSURE	2800 (193 bar)	2850 (196 bar)	2850 (196 bar)	2850 (196 bar)	2850 (196 bar)	2850 (196 bar)
-fLOW	10-15 gpm (39 - 57 l/min)	14-20 gpm (53 - 76 l/min)	15-20 gpm (57 - 76 l/min)	15-20 gpm (57 - 76 l/min)	15-20 gpm (57 - 76 l/min)	15-20 gpm (57 - 76 l/min)
-CONNECTIONS	1-Pressure, 1-Return	1-Pressure, 1-Return	1-Pressure, 1-Return	1-Pressure, 1-Return	1-Pressure, 1-Return	1-Pressure, 1-Return
		1-Case Drain	1-Case Drain	1-Case Drain	1-Case Orain	1-Case Drain
MAX LOG DIAMETER	14" (37 cm)	15" (38 cm)	27" (69 cm)	18" (46 cm)	22" (56 cm)	22" (56 cm)
MAX LOG LENGTH	10' (3.05 m)	12' (3.66 m)	NA	12' (3.56 m)	12' (3.66 m)	12' (3.65 m)
MIN LOG LENGTH	4' {1.22 m}	6' (1.82 m)	NA	6' (1.82 m)	6' (1.82 m)	6' (1.82 m)
FIREWOOD CUT LENGTH	Up to 16" (33cm - 38 cm)	Up to 22" (56 cm)	NA	Up to 22" (56 cm)	Up to 22" (56 cm)	Up to 33" (84 cm)
SAW BAR	18" (64 cm) Versacut	25"(64cm) Harvester	31" (80cm) Harvester	25"(64cm) Harvester	31" (80cm) Harvester	31" (80cm) Harvester
SAW CHAIN	68 Dt. 3/8 pitch 0.58	78 DL .404 pitch/18HX	93 DL .404 pitch/18HX	78 Dt. 404 pitch/18HX	93 DL .404 pitch/18HX	93 Dt. 404 pitch/18HX
SAW MOTOR	Gear	Bent Axis Piston	Bent Axis Piston(Industrial)	Bent Axis Piston(Industrial)	Bent Axis Piston(Industrial)	Bent Axis Piston(Industrial)
SAW OILER	Automatic 2 Qt (1.89 I)	Automatic 2 Qt (1.89 I)	Automatic 2 Qt (1.89 l)	Automatic 2 Qt (1.89 I)	Automatic 2 Qt (1.89 l)	Automatic 2 Qt (1.89 I)
MAX SAW CUT	14" (37 cm)	15" (38 cm)	27" (69cm)	18" (46 cm)	22" (56 cm)	22" (56 cm)
SPLITTER CYLINDER	Custom 3" x 18" Strake	Standard 3.5" x 24" Stroke	NA.	Custom 3.5" x 24" Stroke	Custom 4" x 24" Stroke	Custom 4" x 36" Stroke
SPLITTER FORCE	21,195 @ 3000 psl	28,850 @ 3000 psl	NA	28,850 @ 3000 psi	36,138 @ 3000 psi	36,138 @ 3000 psi
SPLITTING WEDGE	2-way or 4-way	4-way or 6-way Manually	NA	4-way or 6-way Manually	4-way or 6-way Hydraulically	4-way or 6-way Hydraulical
		Adjustable		Adjustable	Adjustable	Adjustable
IN-FEED	Sliding Trough Carries	Sliding Trough Carries	Grapple	Sliding Trough Carries	Sliding Trough Carries	Sliding Trough Carries
	Log to Wedge	Log to Wedge		Log to Wedge	Log to Wedge	Log to Wedge
MOUNTING	Universal Quick Attach	Universal Quick Attach	Universal Quick Attach	Universal Quick Attach	Universal Quick Attach	Universal Quick Attach
	SAE Spec J2513	SAE Spec J2513	SAE Spec J2513	SAE Spec J2513	SAE Spec J2S13	SAE Spec J2513
MEASURING	NA	NA	NA	Manual Moveable Device	Manual Moveable Device	Manual Moveable Device
	1		1			

	HWP-100TR-D	HWP-100TR-H	HWP-100-3P	Hydraulic Pump	Kit For 3 Point
LENGTH	Travel= 126" (320 cm) Working= 96" (244 cm)	Travel= 126" (320cm) Working= 96" (244 cm)	81" (205 cm) W/ Hyd, Wedge- 86" (218 cm)	Fluid Capacity	15 US Gallon
WIDTH	68" (172 cm)	68" (172 cm)	64" (162.5 cm)	Pump Flow Rate	21.2 GPM
HEIGHT	64" (162.5 cm)	64" (162.5 cm)	62 " (157.5 cm)	Pump Max	2,500 PSI
WEIGHT	1260 lbs (572 kg)	1405 lbs (637 kg)	1027 lbs ( 466 kg)	Pump PTO Speed	S40 RPM
CONNECTIONS	NA	NA	1-Pressure, 1-Return	Hydraulic Cooler	50 GPM
MATERIAL	3/16" Steel	3/16" Steel	3/16" Steel	Pressure Relief Valve	2,400 PSI
MAX LOG DIAMETER	14" (37 cm)	14" (37 cm)	14" (37 cm)	Hydraulic Fan & Wiring	12 Volt
MAX LOG LENGTH	8' (2.44 m)	8' (2.44 m)	8' (2.44 m)	Thermostat	Max 185°F (85°C)
MIN LOG LENGTH	4' (1.22 m)	4' (1.22 m)	4' (1.22 m)	Filter Assembly & Filter	25 Micron
FIREWOOD CUT LENGTH	Up to 16" (33cm - 38 cm)	Up to 16" (33cm - 38 cm)	Up to 16" (33cm - 38 cm)	Adjustable Legs	
SAW BAR	18" (64 cm) Versacut	18" (64 cm) Versacut	18" (64 cm) Versacut		
SAW CHAIN	68 DL 3/8 pitch 0.58	68 Dt 3/8 pitch 0.58	68 DL 3/8 pitch 0.58		
SAW MOTOR	Gear	Gear	Gear		
SAW OILER	Automatic 2 Qt (1.89 I)	Automatic 2 Qt (1.89 I)	Automatic 2 Qt (1.89 I)		
MAX SAW CUT	14" (37 cm)	14" (37 cm)	14" (37 cm)	1	
SPLITTER CYLINDER	Custom 3.5" x 18" Stroke	Custom 3.5" x 18" Stroke	Custom 3" x 18" Stroke		
SPLITTER FORCE	21,195 @ 2600 psl	21,195 @ 2600 psl	21,195 @ 2400 psl		
SPLITTING WEDGE	2-way or 4-way	2-way or 4-way	2-way or 4-way		
IN-FEED	Sliding Trough Carries	Stiding Trough Carries	Sliding Trough Carries		
	Log to Wedge	Log to Wedge	Log to Wedge		
TIRE SIZE	4.8-12	4.8-12			
MOUNTING	2" Ball	2" Ball	)		
MOTOR	DuroMax 420CC	GX630 Honda	]		
	1	20.8 hp 1" Keyed Shaft			
FUEL CAPACITY (GAS)	1.75 Gal	1.5 Gal			
OIL CAPACITY	37.2 FL OZ	15 Gal			
RPM	3600	3600			
PUMP	High Low	Honor Gear Pump			
	L	5/8 Keyed Shaft			
GPM	16	16	}		
HYDRAULIC FILTER		Spin On	1		



Email: sales@harcoag.ca

www.harcoag.ca





SHIPPING SPECIFICATIONS				
ITEM	1	WEIGHT	DIMENSIONS (LXWXH)	NMFC/ Class
HWP 100 Processor w/ 2 Way Wedge		770 lbs	82x36x48	133300-09/ 100
HWP 100 Processor w/ 4 Way Wedge		779 lbs	82x36x48	133300-09/ 100
HWP 100 Processor w/ both Wedges		800 lbs	82x36x48	133300-09/ 100
HWP 120 Processor- FIXED		1380 lbs	96x36x48	133300-09/ 100
HWP 120 Processor w/ 4 Way Wedge		1380 lbs	96x36x48	133300-09/ 100
HWP 120 Processor w/ 6 Way Wedge		1393 lbs	96x36x48	133300-09/ 100
HWP 120 Processor w/ both Wedges		1447 lbs	96x36x48	133300-09/ 100
HWP 140B Processor w/ 4 Way Wedge		1550 lbs	102x36x56	133300-08/ 175
HWP 140B Processor w/ 6 Way Wedge		1563 lbs	102x36x56	133300-08/ 175
HWP 140B Processor w/ both Wedges		1617 lbs	102x36x56	133300-08/ 175
HWP 150 Processor w/ 4 Way Wedge		1738 lbs	107x44x64	133300-08/175
HWP 150 Processor w/ 6 Way Wedge		1749 lbs	107x44x64	133300-08/175
HWP 150 Processor w/ both Wedges		1816 lbs	107x44x64	133300-08/175
HWP 150 Extended w/ 4 Way Wedge		2005 lbs	121x44x64	133300-08/175
HWP 150 Extended w/ 6 Way Wedge		2016 lbs	121x44x64	133300-08/175
HWP 150 Extended w/ Both Wedges		2083 lbs	121x44x64	133300-08/175
125GS HD Grapple Saw		845 lbs	48x48x42	114225-01/ 100
Grapple		735 lbs	48x48x42	114225-01/ 100

Function

Requirements Hot pin, ground pin, 6 function


Hot pin, ground pin, 5 function

Hot pin, ground pin, 5 function



Email: sales@harcoaq.ca

www.harcoag.ca





# **PRICELIST**

Model	Description	Price [CDN]
HWP-100	Processor w/2 way wedge	\$14,052.00
HWP-100	Processor w/4 way wedge	\$14,432.00
HWP-100	Processor w/2 way & 4 way wedge	\$14,706.00
HWP-120	Processor/Adjusts 4 way	\$17,888.00
HWP-120	Processor/Adjusts 6 way	\$18,220.00
HWP-140B	Processor/Adjusts 4 way	\$26,595.00
HWP-140B	Processor/Adjusts 6 way	\$26,927.00
HWP-150	Processor/Adjusts hydraulically 4 way	\$34,475.00
HWP-150	Processor/Adjusts hydraulically 6 way	\$34,818.00
HWP-125GS	Grapple Saw	\$15,070.00
HWP-200GS	Grapple Saw	\$15,488.00
HWP-WHS10	100/120 Main Cab Harness Kit	\$976.00
HWP-WHS8	140B//150 Main Cab Harness Kit	\$976.00
HWP-WHGHK	Grapple Saw Cab Harness Kit	\$599.00
No # available	120 Joystick Harness Kit	\$1,604.00
No # available	140B Joystick Harness Kit	\$1,604.00
No # available	150 Joystick Harness Kit	\$1,604.00
HWP-2111	120/140 6-way Wedge	\$1,038.00
HWP-2112	150 6-way Wedge	\$1,143.00

# **LEFT HAND PROCESSORS**

Model	Description	Price [CDN]
HWP-140B	LH Processor w/4 way wedge	\$27,580.00
HWP-140B	LH Processor w/6 way wedge	\$27,912.00
HWP-140B	LH Processor w/4 way & 6 way wedge	\$28,618.00
HWP-150	LH Processor w/4 way wedge	\$35,460.00
HWP-150	LH Processor w/6 way wedge	\$35,803.00
HWP-150	LH Processor w/4 way or 6 way wedge	\$36,603.00



Email: sales@harcoag.ca

www.harcoag.ca



File Section: 5, Page 18

Wood Products, Inc.

# **EXTENDED PROCESSORS**

Model	Description	Price [CDN]
HWP-150	Extended Processor w/4 way wedge	\$36,445.00
HWP-150	Extended Processor w/6 way wedge	\$36,788.00
HWP-150	Extended Processor w/4 way or 6 way wedge	\$37,588.00

# **TRAILER MODELS**

Model	Description	Price [CDN]
100-3PT	Trailered Processor w/2 way	\$13,020.00
100-3PT	Trailered Processor w/4 way	\$13,398.00
PUMP	Pump for 100TR-3PT	\$4,084.00
ADJ.WEDGE	Hydraulic 4-WAY wedge for 100-3PT	\$788.00
100TR-D	Trailered Processor w/2 way *no adj. wedge*	\$16,166.00
100TR-D	Trailered Processor w/4 way *no adj. wedge*	\$16,534.00
ELECTRIC START	Electric Start for 100TR-D	\$788.00
100TR-H	Trailered Processor w/2 way	\$23,640.00
100TR-H	Trailered Processor w/4 way	\$24,018.00
ADJ.WEDGE	Adjustable hydraulic 4 way wedge for 100TR-H	\$788.00

# **PARTS & ACCESSORIES**

Model	Description	Price [CDN]
18HX078E	Harvester Chain Micro Chisel, 120/140	\$85.00
18H-KRF78DL	Carbide Steel Chain, 120/140	\$633.00
642RHFN104	Harvester 18HX Bar, 120/140	\$280.00
No # available	Oregon Sharpener	\$481.00
No # available	Oregon File	\$8.00
802HSFN104	Harvestor Bar, 150	\$321.00
18HX093-E	Harvestor Chain, 150	\$121.00
18HKRF93DL	Carbide Chain, 150	\$633.00



Email: sales@harcoag.ca

www.harcoag.ca

File Section: 5, Page 19 Effective Date: June 1, 2024



The Halverson Wood Products Hydraulic Power Unit (HWP-HPU) was specifically designed to power Halverson Firewood Processors on tractors that do not have the proper hydraulic flow.

This new product was born from the launch of the HWP-100 processor, and allows tractor owners to utilize our HWP-100 or HWP-120 processor (by adding a case drain fitting) in conjunction with the HWP-HPU.

There are two versions of the HWP-HPU, one with a cooler (radiator) and fan, and one without.

# HWP – HPU PTO Driven Hydraulic Power Unit



PTO Pump Speed: 540 RPM

Warranty:

Hydraulic Specifications: 21.2 gpm @ 2500 psi (maximum)
Hydraulic connections: 2 (Includes a port for adding case drain)

Hydraulic Cooler: 50 GPM Cooler Fan: 12 Volts Assembled Weight: 168 lbs. (Dry) 31.25" x 30.25" x 20" Assembled Dimensions: Shipping Dimensions: 35" x 34" x 25" Connection Method: 3-point hitch 25 US Gallons Oil Tank Capacity: Adjustable Leg Style:

PLEASE NOTE: This unit comes dry, oil is extra (requires 25 U.S. gallons) not included in below prices.

6 Months

Description	Price [CDN]
Without Cooler Assembly	\$4,783.00
With Cooler Assembly	\$5,965.00

#### PRICED IN CANADIAN DOLLARS