

Email: sales@harcoag.ca

www.harcoag.ca

Are you standing around splitting wood? Why not do your wood splitting sitting down?







File Section: 5, Page 14 Effective Date: June 2023

Revised-12/23-HWP-HPU OIL UPDATE

Wood Products. Inc.

Advantages

- Simple to operate controls
- Sets up in minutes
- Auto chain oiler
- Multiple splitting head options available
- The most portable processor on the market
- 102" width it can be legally transported attached to your skid steer

Features

Processes logs up to 10 feet in length and 16 inches in diameter

- One-man operation
- Few moving parts
- Ready to go in minutes
- Stay-in-the-machine operation for safety and comfort
- Small, easy to store
- Can process right into a truck or trailer without a conveyor
- Totally portable; no set up or tear down to move or store

Easy to adjust and change cutting length 22" maximum cut length

Specifications

- Required minimum hydraulic flow 15.5 Gallons Per Minute
- Required Minimum Pressure 2850 PSI
- Length 102 Inches
- Weight 1310 lbs
- Universal Quick Attach Skid Steer Plate
- Universal wiring harness plugs into the power port of your machine

Uses

- Tree Services
- **Firewood Operations**
- **Farmers**
- **Outdoor Boiler Owners**
- Logging/Firewood
- Homeowner

Warrantv

- 6 Months to 1 year Warranty
- Fast Factory Support

Productions

1 ½ - 2 Cords Per Hour

www.halversonwoodproducts.com

PRICED IN CANADIAN DOLLARS

PRICES ARE FOB HARRISTON, ONTARIO - DESIGN & PRICE ARE SUBJECT TO CHANGE WITHOUT NOTICE




HWP-125GS

HWP-100

Email: sales@harcoaq.ca

www.harcoag.ca



HWP-150 EXTENDED



HWP-150

Compare us to the competition and you'll see why wood cutting & splitting is experiencing a *REVOLUTION*!

HALVERSON WOOD PRODUCTS SPECIFICATIONS

HWP-140B

HWP-120

			I			
LENGTH	33" (84 cm)	Travel= 80" (203 cm)	Travel= 99" (251 cm)	Travel= 102" (259 cm)	Travel= 107" (272 cm)	Travel= 121" (307 cm)
		Working= 100 (254 cm)	Working= 121" (307 cm)	Working= 126" (320 cm)	Working= 129" (328 cm)	Working= 143" (363 cm
WIDTH	46" (142 cm)	41" (104 cm)	55" (140 cm)	55" (140 cm)	58" (147 cm)	58" (147 cm)
HEIGHT	41" (104 cm)	41" (104 cm)	51" (130 cm)	51" (130 cm)	57" (145 cm)	57" (145 cm)
WEIGHT	770 lbs. (349 kg)	706 lbs (320 kg)	1280 lbs. (581 kg)	1450 lbs. (658 kg)	1638 lbs. (743 kg)	1905 lbs. (864 kg)
MATERIAL	3/8" & 5/8" Steel	3/16" Steel	1/4" Steel	3/8" Steel	3/8" Steel	3/8" Steel
HYDRAULICS						
-MINIMUM PRESSURE	2850 (196 bar)	2800 (193 bar)	2850 (196 bar)	2850 (196 bar)	2850 (196 bar)	2850 (196 bar)
-FLOW	15-20 gpm (57 - 76 l/min)	10-15 gpm (39 - 57 l/min)	14-20 gpm (53 - 76 l/min)	15-20 gpm (57 - 76 l/min)	15-20 gpm (57 - 76 l/min)	15-20 gpm (57 - 76 l/min
-CONNECTIONS	1-Pressure, 1-Return 1-Case Drain	1-Pressure, 1-Return	1-Pressure, 1-Return 1-Case Drain	1-Pressure, 1-Return 1-Case Drain	1-Pressure, 1-Return 1-Case Drain	1-Pressure, 1-Return 1-Case Drain
MAX LOG DIAMETER	27" (69 cm)	14" (37 cm)	15" (38 cm)	18" (46 cm)	22" (56 cm)	22" (56 cm)
MIN LOG DIAMETER	NA NA	NA NA	NA NA	NA NA	NA NA	NA NA
MAX LOG LENGTH	NA NA	10' (3.05 m)	12' (3.66 m)	12' (3.66 m)	12' (3.66 m)	12' (3.66 m)
MIN LOG LENGTH	NA NA	4' (1.22 m)	6' (1.82 m)	6' (1.82 m)	6' (1.82 m)	6' (1.82 m)
FIREWOOD CUT LENGTH	NA NA	Up to 16" (33cm - 38 cm)	Up to 22" (56 cm)	Up to 22" (56 cm)	Up to 22" (56 cm)	Up to 33" (84 cm)
SAW BAR	-					
SAW BAK	31" (80cm) Harvester	18" (64 cm) Versacut	25"(64cm) Harvester	25"(64cm) Harvester	31" (80cm) Harvester	31" (80cm) Harvester
SAW CHAIN	93 DL .404 pitch/18HX	68 DL 3/8 pitch 0.58	78 DL .404 pitch/18HX	78 DL .404 pitch/18HX	93 DL .404 pitch/18HX	93 DL .404 pitch/18H)
	Series		Series	Series	Series	Series
SAW MOTOR	Bent Axis Piston(Industrial)	Gear	Bent Axis Piston	Bent Axis Piston(Industrial)	Bent Axis Piston(Industrial)	Bent Axis Piston(Industri
	Automatic 2 Qt (1.89 l)	Automatic 2 Qt (1.89 l)	Automatic 2 Qt (1.89 l)	Automatic 2 Qt (1.89 l)	Automatic 2 Qt (1.89 l)	Automatic 2 Qt (1.89 l
SAW OILER	Tank	Tank	Tank	Tank	Tank	Tank
MAX SAW CUT	27" (69cm)	14" (37 cm)	15" (38 cm)	18" (46 cm)	22" (56 cm)	22" (56 cm)
SPLITTER CYLINDER	NA	Custom 3" x 18" Stroke	Standard 3.5" x 24" Stroke	Custom 3.5" x 24" Stroke	Custom 4" x 24" Stroke	Custom 4" x 36" Stroke
SPLITTER FORCE	NA.	21,195 @ 3000 psi	28,850 @ 3000 psi	28,850 @ 3000 psi	36,138 @ 3000 psi	36,138 @ 3000 psi
			4-way or 6-way Manually	4-way or 6-way Manually	4-way or 6-way	4-way or 6-way
SPLITTING WEDGE	NA	2-way or 4-way	Adjustable	Adjustable	Hydraulically Adjustable	Hydraulically Adjustabl
	Grapple	Sliding Trough Carries	Sliding Trough Carries	Sliding Trough Carries	Sliding Trough Carries	Sliding Trough Carries
IN-FEED		Log to Wedge	Log to Wedge	Log to Wedge	Log to Wedge	Log to Wedge
	Universal Quick Attach	Universal Quick Attach	Universal Quick Attach	Universal Quick Attach	Universal Quick Attach	Universal Quick Attack
MOUNTING	SAE Spec J2513	SAE Spec J2513	SAE Spec J2513	SAE Spec J2513	SAE Spec J2513	SAE Spec J2513
		-				
MEASURING	NA	NA	NA	Manual Moveable Device	Manual Moveable Device	Manual Moveable Devi
MEASURING	NA	NA	NA SHIPPING SPECIFICATIONS		Manual Moveable Device	Manual Moveable Device
	NA	NA			Manual Moveable Device DIMENSIONS (LXWXH)	NMFC/ Class
ІТЕМ		NA		WEIGHT	DIMENSIONS (LXWXH)	NMFC/ Class
ITEM HWP 100 Processor w/ 2 V	Vay Wedge	NA .				NMFC/ Class 133300-09/ 100
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V	Vay Wedge Vay Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs	DIMENSIONS (LXWXH) 82x36x48 82x36x48	NMFC/ Class 133300-09/ 100 133300-09/ 100
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot	Vay Wedge Vay Wedge th Wedges	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 82x36x48	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor-FIXED	Vay Wedge Vay Wedge th Wedges	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 82x36x48 96x36x48	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ both HWP 120 Processor-FIXED HWP 120 Processor w/ 4 V	Vay Wedge Vay Wedge th Wedges) Vay Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 82x36x48 96x36x48	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor FIXED HWP 120 Processor w/ 4 V HWP 120 Processor w/ 6 V	Way Wedge Way Wedge th Wedges) Way Wedge Way Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 82x36x48 96x36x48 96x36x48	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor - FIXED HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 V	Way Wedge Way Wedge th Wedges Vay Wedge Way Wedge Way Wedge th Wedges	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor w/ bot HWP 120 Processor w/ 4 V HWP 120 Processor w/ 4 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ 4 W	Vay Wedge Vay Wedge th Wedges Vay Wedge Vay Wedge Vay Wedge th Wedges Way Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs 1550 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48 96x36x48 102x36x56	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor FIXED HWP 120 Processor w/ 4 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 W HWP 140B Processor w/ 4 W HWP 140B Processor w/ 4 HWP 140B Processor w/ 6	Vay Wedge Vay Wedge th Wedges Vay Wedge Vay Wedge th Wedge Way Wedge Way Wedge Way Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs 1550 lbs 1563 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48 102x36x56 102x36x56	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 175 133300-08/ 175
HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ 4 V HWP 100 Processor - FIXED HWP 120 Processor w/ 4 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ bot HWP 140B Processor w/ 6 H HWP 140B Processor w/ 6 H HWP 140B Processor w/ 6	Vay Wedge Vay Wedge th Wedges Vay Wedge Vay Wedge th Wedges Way Wedge Way Wedge Way Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs 1550 lbs 1563 lbs 1617 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48 96x36x48 102x36x56 102x36x56	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-08/ 175 133300-08/ 175 133300-08/ 175
HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 V HWP 140B Processor w/ 4 W HWP 140B Processor w/ 6 W HWP 140B Processor w/ 6 W HWP 140B Processor w/ 6 W HWP 150 Processor w/ 6 W HWP 150 Processor w/ 4 V	Vay Wedge Vay Wedge th Wedges Vay Wedge Vay Wedge Vay Wedge Way Wedges Way Wedge Way Wedge Oth Wedges Vay Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs 1550 lbs 1563 lbs 1617 lbs 1738 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48 96x36x48 102x36x56 102x36x56 107x44x64	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-08/ 175 133300-08/ 175 133300-08/ 175
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor w/ 4 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 W HWP 140B Processor w/ 6 HWP 140B Processor w/ 6 HWP 140B Processor w/ 6 HWP 150 Processor w/ 4 V HWP 150 Processor w/ 4 V	Vay Wedge Vay Wedge th Wedges Vay Wedge Vay Wedge Way Wedge Way Wedge Way Wedge Oth Wedges Vay Wedge Vay Wedge Vay Wedge Vay Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs 1550 lbs 1563 lbs 1617 lbs 1738 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48 102x36x56 102x36x56 102x36x56 107x44x64 107x44x64	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 105 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor w/ 4 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 W HWP 140B Processor w/ 6 W HWP 140B Processor w/ 6 W HWP 150 Processor w/ 6 W	Vay Wedge Vay Wedge th Wedges) Vay Wedge Vay Wedge th Wedges Way Wedge Way Wedge outh Wedge Vay Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs 1550 lbs 1561 lbs 1617 lbs 1738 lbs 1749 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48 102x36x56 102x36x56 102x36x56 107x44x64 107x44x64	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ both HWP 120 Processor w/ 6 V HWP 140B Processor w/ 4 H HWP 140B Processor w/ 6 W HWP 150 Extended w/ 4 W	Vay Wedge Vay Wedge th Wedges Vay Wedge Vay Wedge Way Wedge Way Wedge Way Wedge Way Wedge Vay Wedge Vay Wedge Vay Wedge Vay Wedge th Wedge Vay Wedge Vay Wedge Vay Wedge Vay Wedge Vay Wedge Vay Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs 1550 lbs 1563 lbs 1617 lbs 1738 lbs 1749 lbs 1816 lbs 2005 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48 102x36x56 102x36x56 102x36x56 107x44x64 107x44x64 121x44x64	NMFC/ Class 13330-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor w/ 4 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ bot HWP 140B Processor w/ 6 HWP 140B Processor w/ 6 HWP 140B Processor w/ 4 HWP 150 Processor w/ 4 HWP 150 Processor w/ 6 HWP 150 Extended w/ 6 HWP 150 Extended w/ 6 HWP 150 Extended w/ 6	Vay Wedge Vay Wedge th Wedges Vay Wedge Vay Wedge th Wedges Way Wedge Way Wedge Oth Wedges Vay Wedge Vay Wedge th Wedges Vay Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs 1550 lbs 1563 lbs 1617 lbs 1738 lbs 1749 lbs 1816 lbs 2005 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48 96x36x48 102x36x56 102x36x56 102x36x56 107x44x64 107x44x64 121x44x64 121x44x64	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ 6 V HWP 120 Processor w/ bot HWP 140B Processor w/ bot HWP 140B Processor w/ 6 W HWP 150 Processor w/ 6 V HWP 150 Processor w/ 6 V HWP 150 Processor w/ bot HWP 150 Processor w/ bot HWP 150 Extended w/ 4 W HWP 150 Extended w/ 4 W HWP 150 Extended w/ 6 W HWP 150 Extended w/ 6 W	Vay Wedge Vay Wedge th Wedges Vay Wedge Vay Wedge th Wedges Way Wedge Way Wedge Oth Wedges Vay Wedge Vay Wedge th Wedges Vay Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs 1550 lbs 1563 lbs 1617 lbs 1738 lbs 1749 lbs 1816 lbs 2005 lbs 2016 lbs 2083 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48 96x36x48 102x36x56 102x36x56 102x36x56 107x44x64 107x44x64 121x44x64 121x44x64	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175
ITEM HWP 100 Processor w/ 2 V HWP 100 Processor w/ 4 V HWP 100 Processor w/ bot HWP 120 Processor w/ 6 V HWP 140B Processor w/ 4 HWP 140B Processor w/ 6 HWP 150 Processor w/ 4 HWP 150 Processor w/ 4 HWP 150 Processor w/ 4 HWP 150 Processor w/ 6 V	Vay Wedge Vay Wedge th Wedges Vay Wedge Vay Wedge th Wedges Way Wedge Way Wedge Oth Wedges Vay Wedge Vay Wedge th Wedges Vay Wedge	NA .	SHIPPING SPECIFICATIONS	WEIGHT 770 lbs 779 lbs 800 lbs 1380 lbs 1380 lbs 1393 lbs 1447 lbs 1550 lbs 1563 lbs 1617 lbs 1738 lbs 1749 lbs 1816 lbs 2005 lbs	DIMENSIONS (LxWxH) 82x36x48 82x36x48 96x36x48 96x36x48 96x36x48 96x36x48 102x36x56 102x36x56 102x36x56 107x44x64 107x44x64 121x44x64 121x44x64	NMFC/ Class 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-09/ 100 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175 133300-08/ 175


Function

Requirements Hot pin, ground pin, 6 function Hot pin, ground pin, 5 function Hot pin, ground pin, 5 function



Email: sales@harcoag.ca

www.harcoag.ca





HWP-100 Specifications



The HWP-100 is designed for the homeowner that cuts 1-10 cord per year.



Operate the machine from the safety and comfort of the cab on your skid steer, mini excavator and/or tractor!

SPECS	VALUE
Weight	706 Lbs.
Dimensions	82" x 36" x 48"
Materials	3/16" Steel
Splitting Head	2-Way, Optional 4-way for Purchase
Minimum Pressure	2,800 PSI
Flow Rate	10-15 GPM
3/4" Hydraulic Connection	1- Pressure, 1- Return
Max Log Diameter	14"
Log Length	Min. 4' to Max.10'
Firewood Cut Length	16" Maximum
Max Saw Cut	16"
Saw Chain	69 DL 3/8 pitch 0.58
Saw Motor	Gear
Saw Oiler	Automatic 2 Qt Tank
Saw Bar	18" Versacut
Splitter Cylinder	Custom 3" x 18" Stroke
Splitter Force	21,195 @ 3,000 PSI
In-Feed	Sliding Trough Carrier
Mounting	Universal Quick Attach J2513

Optional Wire Harness Available


Perfect for residential and farm use, the HWP-100 Firewood Processors truly makes the job hassle-free. The lighter weight processor allows you to operate on tractors, excavators, mini skid steers and some mini skid loaders.





Email: sales@harcoaq.ca

www.harcoag.ca





PRICELIST

Model	Description	Price [CDN]
HWP-100	Processor w/2 way wedge	\$12,513.00
HWP-100	Processor w/4 way wedge	\$12,885.00
HWP-100	Processor w/2 way & 4 way wedge	\$13,157.00
HWP-120	Processor/Adjusts 4 way	\$16,296.00
HWP-120	Processor/Adjusts 6 way	\$16,623.00
HWP-140B	Processor/Adjusts 4 way	\$26,190.00
HWP-140B	Processor/Adjusts 6 way	\$26,517.00
HWP-150	Processor/Adjusts hydraulically 4 way	\$33,950.00
HWP-150	Processor/Adjusts hydraulically 6 way	\$34,300.00
HWP-125GS	Grapple Saw	\$14,841.00
HWP-WHS10	100/120 Main Cab Harness Kit	\$805.00
HWP-WHS8	140B//150 Main Cab Harness Kit	\$805.00
JCB Extension Kit 120	3' Extension Kit w/wires, hose & couplers	\$250.00
JCB Extension Kit 140B/150	3' Extension Kit w/wires, hose & couplers	\$264.00
No # available	120 Joystick Harness Kit	\$1,579.00
No # available	140B Joystick Harness Kit	\$1,579.00
No # available	150 Joystick Harness Kit	\$1,579.00
HWP-2111	120/140 6-way Wedge	\$1,053.00
HWP-2112	150 6-way Wedge	\$1,125.00


LEFT HAND PROCESSORS

Model	Description	Price [CDN]
HWP-140B	LH Processor w/4 way wedge	\$27,160.00
HWP-140B	LH Processor w/6 way wedge	\$27,487.00
HWP-140B	LH Processor w/4 way & 6 way wedge	\$28,213.00
HWP-150	LH Processor w/4 way wedge	\$34,920.00
HWP-150	LH Processor w/6 way wedge	\$35,259.00
HWP-150	LH Processor w/4 way or 6 way wedge	\$36,045.00



Email: sales@harcoag.ca

www.harcoag.ca





EXTENDED PROCESSORS

Model	Description	Price [CDN]
HWP-150	Extended Processor w/4 way wedge	\$35,890.00
HWP-150	Extended Processor w/6 way wedge	\$36,229.00
HWP-150	Extended Processor w/4 way or 6 way wedge	\$37,015.00

PARTS & ACCESSORIES

Model	Description	Price [CDN]
18HX078E	Harvester Chain Micro Chisel, 120/140	\$85.00
18H-KRF78DL	Carbide Steel Chain, 120/140	\$633.00
642RHFN104	Harvester 18HX Bar, 120/140	\$280.00
No # available	Oregon Sharpener	\$230.00
No # available	Oregon File	\$8.00
802HSFN104	Harvestor Bar, 150	\$321.00
18HX093-E	Harvestor Chain, 150	\$121.00
18HKRF93DL	Carbide Chain, 150	\$633.00



File Section: 5, Page 19 Effective Date: June 2023 Revised 12/23-HWP-HPU OIL UPDATE

5808 Hwy #9, Harriston, Ontario, N0G Phone: 519-338-2923, Fax: 519-338-27

Email: sales@harcoag.ca

www.harcoag.ca





The Halverson Wood Products Hydraulic Power Unit (HWP-HPU) was specifically designed to power Halverson Firewood Processors on tractors that do not have the proper hydraulic flow.

This new product was born from the launch of the HWP-100 processor, and allows tractor owners to utilize our HWP-100 or HWP-120 processor (by adding a case drain fitting) in conjunction with the HWP-HPU.

There are two versions of the HWP-HPU, one with a cooler (radiator) and fan, and one without.

HWP – HPU PTO Driven Hydraulic Power Unit



PTO Pump Speed: 540 RPM

 Hydraulic Specifications:
 21.2 gpm @ 2500 psi (maximum)

 Hydraulic connections:
 2 (Includes a port for adding case drain)

Hydraulic Cooler: 50 GPM Cooler Fan: 12 Volts Assembled Weight: 168 lbs. (Dry) Assembled Dimensions: 31.25" x 30.25" x 20" **Shipping Dimensions:** 35" x 34" x 25" Connection Method: 3-point hitch Oil Tank Capacity: 25 US Gallons Leg Style: Adjustable Warranty: 6 Months

PLEASE NOTE: This unit comes dry, oil is extra (requires 25 U.S. gallons) not included in below prices.

Description	Price [CDN]
Without Cooler Assembly	\$3,934.00
With Cooler Assembly	\$5,098.00