

RP 800

SPECIFICATIONS

| | |
|------------------------------------|--|
| Weight - Empty (Calculated) | 9750 lb (4423 kg) |
| Tongue Weight | 1600 lb (725 kg) |
| Length - Transport | 230 ½" (5.85 m) |
| Length - Working | 228 ¼" (5.79 m) |
| Width - Picking | 80" (2.03 m) |
| Width - Transport | |
| 550/45 tires | 145" (3.68 m) |
| Width - Working | |
| 550/45 tires | 189 ¼" (4.80 m) |
| Height | 87" (2.21 m) |
| Trailer Dumping Height | 102" (2.59 m) |
| Dumping Height | 88" (2.23 m); 101" (2.56m); 114" (2.9 m) |
| Bucket Capacity (max.) | 5.4 yd3 (4.1 m3)) |

| | |
|-----------------------------------|--|
| HP Required | 90 hp (67 kW) |
| Hydraulic Outlets Required | 3 |
| Hydraulic Pressure | 2500 psi (172 bar) |
| Hydraulic Flow Required | 18 gpm (68 l/min) |
| Hitch Requirement | Cat 3 |
| Min Rock Diameter Pickup | 2" (.05 m) |
| Max Rock Diameter Pickup | 25" (.63 m) |
| Tines | Replaceable tines, tine tips & tine top plates |
| Bucket | Grated on front, bottom & sides |
| Reel Bats | Weld hard-faced & reversible |
| Recommended Reel Speed | 23 rpm @ 2 mph (23 rpm @ 3.2 kmh) 47 rpm @ 4 mph (47 rpm @ 6.4 kmh) |

Note: Right/left hand is determined by sitting in the tractor seat looking forward

While every effort has been made to ensure that the information is accurate/current at the time of production, all specifications are subject to change.

For the latest product information, please visit: www.highlinemfg.com.