

File Section: 1, Page 25 Effective Date: January 2024

5808 Hwy #9, Harriston, Ontario, N0G 1Z0 Phone: 519-338-2923, Fax: 519-338-2756 Email: <u>sales@harcoag.ca</u> <u>www.harcoag.ca</u>



New vertical tillage concept by HCC Inc. features patented self sharpening tines in a three tine configuration followed by adjustable rolling harrows.

Unit can be purchased less the rolling harrows. Machines with harrows can be operated with harrows lifted or with varying rates of penetration and different angles allowing for varying finish results.

Extremely heavy frame and tongue provide excellent downward pressure. At the same time the rolling aerator tines are protected from impact by 'C' shanks.

SMART-TILL					
Model	Width	Weight (Ibs)	Set Up	MSRP [USD]	
SMT 101	10 Feet Less Rolling Harrows	3,350	\$200.00	\$30,920.00	
SMT 101	10 Feet With Rolling Harrows	5,250	\$350.00	\$38,930.00	
SMT 151	15 Feet Less Rolling Harrows	5,000	\$350.00	\$43,540.00	
SMT 151	15 Feet With Rolling Harrows	7,850	\$400.00	\$56,210.00	
SMT 203	20 Feet Less Rolling Harrows	7,550		\$60,690.00	
SMT 203	20 Feet With Rolling Harrows	11,500		\$83,790.00	
SMT 303	30 Feet Less Rolling Harrows	10,500		\$95,515.00	
SMT 303	30 Feet With Rolling Harrows	16,500		\$117,985.00	

Dual wheels are standard on all machines.

## PRICED IN UNITED STATES DOLLARS FOB FACTORY – PRICES SUBJECT TO CHANGE WITHOUT NOTICE



File Section: 1, Page 26 Effective Date: January 2024

5808 Hwy #9, Harriston, Ontario, N0G 1Z0 Phone: 519-338-2923, Fax: 519-338-2756 Email: <u>sales@harcoag.ca</u> <u>www.harcoag.ca</u>



Rotary Harrows Modules					
Part #	Description	MSRP [USD]			
853044	Harrow Module – 3'	\$2,385.00			
853066	Harrow Module – 5' 7"	\$2,925.00			
853033	Harrow Module – 6'	\$3,055.00			
853109	Harrow Module – 9'	\$4,000.00			

Farm Equipment







Harrow Hangers					
Part #	Description	MSRP [USD]			
853129*	3' Harrow Hanger	\$545.00			
853103*	5' 7", 6', 9' Harrow Hanger	\$645.00			

Harrows smooth, level & loosen soil – Ideal for seed bed preparation. Harrows can be varied up to 30° at either standard or aggressive angles. Tine material is wear resistant 4140 steel. \*Includes hanger, bushing & decal.