



**HALVERSON WOOD PRODUCTS SPECIFICATIONS**

	HWP-125GS GRAPPLE	HWP-120 PROCESSOR	HWP-140B PROCESSOR	HWP-150 PROCESSOR	Inverted Splitter
<b>LENGTH</b>	33"	Travel= 99" Working= 121"	Travel= 102" Working= 126"	Travel= 107" Working= 129"	
<b>WIDTH</b>	56"	55"	55"	58"	
<b>HEIGHT</b>	41"	51"	51"	57"	
<b>WEIGHT</b>	645 lbs.	975 lbs.	1450 lbs.	1638 lbs.	
<b>MATERIAL</b>	3/8" & 5/8" Steel	1/4" High Tensile Steel	3/8" Steel	3/8" Steel	
<b>HYDRAULICS</b>					
<b>-MINIMUM PRESSURE</b>	2850	2850	2850	2850	NA
<b>-FLOW</b>	15-20 gpm	14-18 gpm	15-20 gpm	15-20 gpm	NA
<b>-CONNECTIONS</b>	1-Pressure, 1-Return 1-Case Drain	1-Pressure, 1-Return 1-Case Drain	1-Pressure, 1-Return 1-Case Drain	1-Pressure, 1-Return 1-Case Drain	1-Pressure, 1-Return
<b>MAX LOG DIAMETER</b>	27"	15"	18"	22"	NA
<b>MIN LOG DIAMETER</b>	3"	NA	NA	NA	NA
<b>MAX LOG LENGTH</b>	NA	12'	12'	12'	29"
<b>MIN LOG LENGTH</b>	NA	6'	6'	5'	NA
<b>FIREWOOD CUT LENGTHS</b>	NA	Up to 22"	Up to 22"	Up to 22"	Up to 29"
<b>SAW BAR</b>	31" (80cm) Harvester	25"(64cm)Harvester	25"(64cm)Harvester	31" (80cm) Harvester	NA
<b>SAW CHAIN</b>	93 DL .404 pitch/18HX Series	78 DL .404 pitch/18HX Series	78 DL .404 pitch/18HX Series	93 DL .404 pitch/18HX Series	NA
<b>SAW MOTOR</b>	Bent Axis Piston(Industrial)	Bent Axis Piston	Bent Axis Piston(Industrial)	Bent Axis Piston(Industrial)	NA
<b>SAW OILER</b>	Automatic 2 Qt Tank	Automatic 2 Qt Tank	Automatic 2 Qt Tank	Automatic 2 Qt Tank	NA
<b>MAX SAW CUT</b>	27"	15"	18"	22"	NA
<b>SPLITTER CYLINDER</b>	NA	Standard 3.5" x 24" Stroke	Custom 3.5" x 24" Stroke	Custom 4.0" x 24" Stroke	Custom 4.0" x 29" Stroke
<b>SPLITTER FORCE</b>	NA	28,850 @ 3000 psi	28,850 @ 3000 psi	36,138 @ 3000 psi	35,794 @ 3000 psi
<b>SPLITTING WEDGE</b>	NA	4-way Fixed or 4-way or 6-way Manually Adjustable	4-way or 6-way Manually Adjustable	4-way or 6-way Hydraulically Adjustable	4-way Fixed Splitter
<b>IN-FEED</b>	Grapple	Sliding Trough Carries Log to Wedge	Sliding Trough Carries Log to Wedge	Sliding Trough Carries Log to Wedge	NA
<b>MOUNTING</b>	Universal Quick Attach SAE Spec J2513	Universal Quick Attach SAE Spec J2513	Universal Quick Attach SAE Spec J2513	Universal Quick Attach SAE Spec J2513	Universal Quick Attach SAE Spec J2513
<b>MEASURING</b>	NA	NA	Manual Moveable Device	Manual Moveable Device	NA

**SHIPPING SPECIFICATIONS**

ITEM	WEIGHT	DIMENSIONS	NMFC/ Class
120 Processor w/ 4 Way Attachment	1200 lbs	96x36x48	133300-09/ 100
120 Processor w/ 6 Way Attachment	1215 lbs	96x36x48	133300-09/ 100
120 Processor w/ both Attachments	1265 lbs	96x36x48	133300-09/ 100
120 Processor- FIXED	1160 lbs	96x36x48	133300-09/ 100
140B Processor w/ 4 Way Attachment	1560 lbs	102x36x56	133300-08/ 175
140B Processor w/ 6 Way Attachment	1575 lbs	102x36x56	133300-08/ 175
140B Processor w/ both Attachments	1625 lbs	102x36x56	133300-08/ 175
HWP 150 Processor w/ 4 Way Attachment	1726 lbs	107x44x64	133300-08/175
HWP 150 Processor w/ 6 Way Attachment	1740 lbs	107x44x64	133300-08/175
HWP 150 Processor w/ both Attachments	1796 lbs	107x44x64	133300-08/175
125GS HD Grapple Saw	770 lbs	48x48x42	114225-01/ 100
Inverted Splitter	825 lbs	93x48x31	130325-05/ 110
Grapple	570 lbs	48x48x42	114225-01/ 100