



## PREMIUM VALUE

Whether your passion for motorcycles leads you to the track or to the open road, you want to spend your hard-earned money wisely. Haulmark understands. We proudly manufacture motorcycle trailers with smart, rugged designs that will faithfully perform day-after-day, year-after-year.



*Trailers shown may feature optional equipment available at an additional charge.*





# SPECIFICATIONS



	VNLH7X12WT2	VNLH7X14WT2	VNLH7X16WT2	VNLH7X18WT2
<b>Body:</b>				
Length (Including "V")	14' 7"	16' 7"	18' 7"	20' 7"
Width	7' 0"	7' 0"	7' 0"	7' 0"
<b>Overall:</b>				
Length	16' 7"	18' 7"	20' 7"	22' 7"
Width	8' 6"	8' 6"	8' 6"	8' 6"
Height	6' 8"	6' 8"	6' 8"	6' 8"
<b>Interior:</b>				
Length (Including "V")	14' 2"	16' 2"	18' 2"	20' 2"
Width	6' 9"	6' 9"	6' 9"	6' 9"
Height	5' 3"	5' 3"	5' 3"	5' 3"
<b>Platform Height at Beavertail</b>	12"	12"	12"	12"
<b>Spring Suspension E-Z Lube Axles: Qty Total Capacity Axle Type</b>	Tandem 7,000 lbs. 22.5° Up Angle	Tandem 7,000 lbs. 22.5° Up Angle	Tandem 7,000 lbs. 22.5° Up Angle	Tandem 7,000 lbs. 22.5° Up Angle
<b>Electric Brakes with Breakaway Kit</b>	Electric Drum	Electric Drum	Electric Drum	Electric Drum
<b>Radial Tire Size Tire Load Range</b>	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST225/75R15 D
<b>Hitch Ball Size</b>	2-5/16"	2-5/16"	2-5/16"	2-5/16"
<b>Hitch Height to Top of Ball</b>	17"	17"	17"	17"
<b>Hitch Weight (% of Curb Weight)</b>	10% to 15%	10% to 15%	10% to 15%	10% to 15%
<b>Curb Weight (Approximate)</b>	2,575 lbs.	2,720 lbs.	2,870 lbs.	3,020 lbs.
<b>GVWR</b>	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
<b>Payload Capacity (Approximate)</b>	4,425 lbs.	4,280 lbs.	4,130 lbs.	3,980 lbs.
<b>Rear Ramp Door Opening - Width x Height</b>	75" X 63"	75" X 63"	75" X 63"	75" X 63"
<b>12V Male Connection</b>	7-way	7-way	7-way	7-way
<b>Beavertail</b>	32"	32"	32"	32"

## STANDARD FEATURES

- V-Nose/Flat Roof Profile
- 16" OC Vertical Posts
- 16" OC Crossmembers
- 16" OC Roof Bows
- Rear Ramp Door with Spring Assist
- .080 Ramp Door Hinge Cover
- Drop-Down Stabilizer Jacks
- 32" x 54" Side Entry Door
- E-Z Lube® Hubs
- 15" Radial Tires with Steel Silver Wheels & Chrome Center Caps
- Chrome Rear Corners & Header
- Polished Aluminum Lower Exterior Side Panels
- Chrome Nose
- .030 Aluminum Exterior Bonded (no screws)
- 24" ATP Stoneguard
- Flow-Thru Sidewall Vents
- 12v LED Exterior Lighting
- Low Hauler® Graphics
- Removable Chrome Wheel Chock(s)
- 5,000 lbs. D-Rings
- 500 lbs. Rope Rings
- Rubber Tread Plate Flooring, Ramp Deck & Ramp Extension
- White Vinyl Sidewall & Ceiling Liner
- 12v LED Dome Light with Wall Switch
- 3-year Limited Warranty



Trailers shown feature optional equipment available at additional cost.



GET MORE | GO FURTHER

www.haulmark.com

Specifications, features, options, packages & pricing subject to change **without** notice. See your authorized Haulmark dealer for more information.