# 2022 NEW MACH Z<sup>™</sup>

The return of a legend. For one year only.

#### // WHAT'S NEW

- Rotax® 900 ACE™ Turbo R with cable throttle housing and launch control
- Smart-Shox semi-active suspension with high-performance KYB PRO shock package
- Lowered RAS™ X front suspension
- Lowered rMotion™ X rear suspension
- Rack steering system
- Exclusive coloration, dark smoke windshield and handguards and reflective decals.
- Standard with two sets of LinQ attachment points
- Two-ply Ripsaw II Track



- 7.8 in. wide LCD display with BRP Connect standard
- Electric starter
- RS running boards

ROTAX® FNGINE

- · Low windshield with deflectors
- Forward adjustable riser
- Transparent handguards

900 ACF™ TURBO R

- - Pilot X skis

Carbon Black / Liquid Titanium

Rear suspension travel

Runner - Carbide

Bumpers (front/rear)

• Backlit multifunction handlebar controls

KUIAA" ENUINE	JUU ACE TURBU K
Engine details	Liquid-cooled, four-stroke D.O.H.C.,
	dry sump, turbocharged
Horsepower	180
Cylinders - Displacement	3 - 899 cc
Bore - Stroke	73 mm – 69.7 mm
Carburation	EFI
Fuel type – Octane	Premium unleaded – 91
Fuel tank	36 L/9.5 US gal
Oil tank capacity	3.3 L/3.5 qt
POWERTRAIN	
Drive clutch	pDrive™
Driven clutch	QRS Vent
Drive sprocket pitch	73 mm/2.86 in.
DRY WEIGHT	
Dry weight	249 kg/548 lb
DIMENSIONS	
Overall vehicle length	3,038 mm/119.6 in.
Overall vehicle width	1,209 - 1,232 - 1,255 mm/47.6 - 48.5 - 49.4 in.
Overall vehicle height	1,267 mm/49.9 in.
Ski stance	1,069 - 1,092 - 1,115 mm/42.1 - 43 - 43.9 in.
Track	2-Ply Ripsaw II:
(Length x Width x Profile)	137 x 15 x 1.25 in.

# SUSPENSION Front suspension RAS™ X Front shock KYB¹ PRO Smart-Shox Front suspension travel 235 mm/9.3 in. Rear suspension rMotion™ X Center shock KYB¹ PRO 40 Rear shock KYB¹ PRO Smart-Shox

292 mm/11.5 in.

Round 7/16 - 4 in.

Std/Std

#### **FEATURES** Frame REV® Gen4 Bodywork Wide design Pilot™ X Skis Trail with storage Seating U-shaped aluminum with J-hooks/ Handlebar Dark smoke handguards Riser block height Adjustable-120 mm/4.7 in. Starter Electric Reverse Electro-mechanic Brake system Brembo racing brake with stainless-steel braided brake line Heated throttle lever/grips Standard Gauge type 7.8 in. wide LCD color display Windshield 360 mm/14 in.

#### // FEATURE HIGHLIGHTS



## 1 Rotax® 900 ACE™ Turbo R with cable throttle housing and Launch Control

Now the most powerful engine ever offered in a Ski-Doo. Ferocious instant acceleration and top speed through bigger fuel injectors, increased boost and optimized intake and exhaust systems. The new cable-activated iTC throttle better matches a performance rider's profile while offering four driving modes including exclusive Launch Control.



#### 2 Smart-Shox

An industry-first, Smart-Shox semi-active suspension instantly reads terrain and rider input to automatically dial in your suspension to give you the optimal ride in any conditions.



#### 3 Lowered suspension

1.5 in. lower ride height for improved aerodynamics, lower center of gravity, more traction due to a better attack angle of the track and an aggressive look.



MACH ZTM 900 ACETM TURBO R SHOWN



### 4 Large panoramic 7.8 in. wide LCD color display

Wide-screen full-color display lets riders truly customize their ride from behind the bars. Choose your preferred sled info, and see app integrated-information in a split-screen format with GPS, Bluetooth music, helmet-to-helmet communication and more.

#### 5 Two-ply Ripsaw II racing track

Two-ply for extra durability. Excellent traction in all conditions. Pre-marked for studding.

#### 6 Rack steering system

Derived from the MXZx race sled, further increases steering precision and straight tracking for a nimble and predictable ride in extreme bumps.



