



HYDRAULIC SPECIFICATIONS -TRUCK WET KIT PROVIDED BY CUSTOMER

40 GPM @ 1,500 TRUCK ENGINE RPM
 3500 PSI PEAK PRESSURE W/RELIEF VALVE INSTALLED & SET AT 3500 PSI
 45-50 GALLON RESERVOIR FILLED W/40 GALLONS OF HYDRAULIC OIL
 TRAILER FEATURES 1-5/16 - 12 JIC MALE CONNECTIONS ON TRAILER FRONT
 (CUSTOMER MUST PROVIDE 1" HYDRAULIC HOSES WITH FEMALE CONNECTIONS)

5 4 3 2 1

NAME		DATE		MEYER MFG CORP.	
DRAWN BY		JAA			
CHECKED				MATERIAL:	
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32" ANGULAR: BEND ± 0.5° TWO PLACE DECIMAL ± 0.02" THREE PLACE DECIMAL ± 0.005"				TITLE: 9100T-RT HYDRAULIC SPECIFICATIONS	
PROPRIETARY AND CONFIDENTIAL. THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MEYER MFG CORP. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MEYER MFG CORP. IS PROHIBITED.				SIZE	DWG. NO.
				A	9100T-RT HYDRAULIC SPECIFICATIONS
				SCALE: 1:1	WT: XX.XX
				SHEET 1 OF 1	REV. -