

SALFORD

See our full line of products and find your local dealer at **salfordgroup.com** Osceola, lowa • Cornelia, Georgia • Salford, Ontario • Elie, Manitoba • 1-866-442-1293



## SIMPLE & ACCURATE APPLICATION

Salford's latest AB320 model features Valmar's Venturi metering design with proven reliability and simple maintenance. Reduce application overlap and save on input costs with variable rate application and left/right section control. Engineered specifically for the John Deere floater chassis, this AB320 model will integrate seamlessly with your chassis.

Valmar AB320DF Mounted Air Boom Applicator for John Deere	
Chassis Compatibility	John Deere® F4365 & 800R
Hopper Option 1	409 Stainless Steel (Painted to match chassis) 3 Compartments 2x Main Products + 1 Micronutrient/Cover Crop/Granular Herbicide
Hopper Option 2	409 Stainless Steel (Painted to match chassis) 2 compartment 1x Main Product + 1 Micronutrient/Cover Crop/Granular Herbicide
	Factory ready for 4600 Command Center display & function control switches
	Left / Right section control
Metering	Independent Variable Rate by Product
	Stainless Steel 304 Conveyors (Compartments 1 & 2)
	Meter Rollers to apply micro-nutrients cover crops or granular herbicides
	90-foot spread, 304 stainless steel
Boom	Hydraulic bi-fold booms with spring protected break-away tips
	Hydraulic boom suspension with optional NORAC Auto- Boom Height Control

## Products and specifications subject to change without notice and without liability therefore. Images may include optional equipment. All trademarks, service marks, trade names, product names and logos appearing within are the property of their respective owners. Any rights not expressly granted herein are reserved. John Deere is a registered trademark of Deere & Company. Salford® is a registered trademark of Salford Group Inc. Copyright® 2023 Salford Group Inc. 2023.01

## **REVOLUTIONARY NEW HOPPER DESIGN**

This NEW AB320 model is capable of applying one, two or three products at once with various hopper configurations. Empty hoppers can be adjusted in seconds, no tools or bin inserts required.











