GN / FW MODEL

Configure your trailer to your specific needs:

- Platforms available in four lengths: 25, 30, 35 and 40 feet.
- Several axle capacities: 20,000 lbs., 24,000 lbs. and 30,000 lbs. tandems.
- Choice between hydraulic or electric brakes.
- Hutch suspension.

GN25-5LHT30HR40-01-22 shown subject to change









GOOSENECK

GALVANIZED

TANDEM

TRIDEM (on request)

									(0.1.104.001)
	20+5				25+5		30+5	35+5	
	20,000 lbs single wheel	20,000 lbs.	24,000 lbs.	30,000 lbs.	20,000 lbs.	24,000 lbs.	30,000 lbs.	30,000 lbs.	30,000 lbs.
Deck lenght	25'			30'			35'	40'	
Deck width	97 ¼ po								
Axles	2 x 10,000 lbs single wheel		2 x 12,000 lbs.	2 x 15,000 lbs.	2 x 10,000 lbs.	2 x 12,000 lbs.		2 x 15,000 lbs.	
Suspension	38" Axles spread 49"								
Brakes	Electric or Electro-hydraulic								
Load capacity	16,625 lbs.	16,625 lbs.	21,625 lbs.	29,625 lbs.	15,375 lbs.	20,375 lbs.	27,875 lbs.	26,650 lbs.	25,250 lbs.
Trailer weight	6,700 lbs.	6,700 lbs.	6,700 lbs.	6,700 lbs.	7,700 lbs.	7,700 lbs.	7,700 lbs.	9,000 lbs.	9,000 lbs.
Jacks	2 x 2 speed 25,000 lbs.								
Tires / Rims	17.5" 16 ply	16" 10 ply		17.5" 16 ply	16" 10 ply		17.5" 16 ply		
Deck	Hemlock								
Frame	W12 I-Beam								
Crosstmembers	C3 every 16" C/C								





K-TRAIL.CA

INFO@K-TRAIL.CA | 877 248-7018


DECK SERIES

GN / FW MODEL

FEATURES

- Hemlock decking
- Winch track
- Aluminum toolbox
- Footboard
- Side pockets linked by a flat bar
- 40" wide ramps
- Standard stabilizer legs
- Hutch suspension
- LED lights
- 2 x 2 speeds 50,000 lbs. drop leg jacks
- Cold-resistant harness

- W12 frame optimized for each load capacity
- C3 crossmember every 16" C/C
- Anti-torsion tubing on 35' and 40' models








SIDE TOOLBOX



8' x 8' FRONT DECK



WORKING LIGHTS



STANDARD CHAIN TRAY

ACCESSORIES & OPTIONS

front deck, chain holder, side toolbox, plank support, working lights, hydraulic jack, spare tire, etc.

IK-TRAIL

K-TRAIL CA