




**Artificial
Lift
XWerx Ltd.**

228-246-86



GENERAL DIMENSIONS

A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	BACK WIDTH	FRONT WIDTH	OVERALL WIDTH
98.50	111.00	191.50	98.50	110.50	76.00	37.00	78.00	74.25	86.00	17.50	84.25	198.00	240.75	43.00	247.50	325.00	27.50	72.00	83.00

EFFECTIVE COUNTERBALANCE DATA

Weight Combination		Counter Balance Effect
Crank Only		3555
2	#13	5841
2	#15	7723
4	#13	8127
2	#16	9191
2	#13 + #15	10009
2	#13 + #16	11476
4	#15	11891
2	#17	12129
2	#15 + #16	13359
2	#13 + #17	14415
4	#16	14826
2	#15 + #17	16297
2	#16 + #17	17764
4	#17	20702


GENERAL ENGINEERING DATA

Peak Torque Rating, API	228,000 in-lbs
Polish Rod Capacity	24,600 lbs
Stroke Lengths	86", 74", 62"
Walking Beam Size	24" @ 117 lbs
Reducer Model	T228
Reducer Ratio	28.873
Input Shaft Size	3.000
Sheave Diameter	36.4 4C
Belts for Std High Mount	C195
Oil Capacity	205L
Structural Unbalance	-296 lbs
Gear Box Weight	6820 lbs
Total Weight	* 23158 lbs

* NOT INCLUDING COUNTER WEIGHT

Counter Weights	Weight	Crank Arm	Weight
#13	738 lbs	R37	2040 lbs
#15	1494 lbs		
#16	2100 lbs		
#17	3500 lbs		

GET PUMPED UP AT "WWW.ALXJACKS.COM"



228-246-86

STANDARD EQUIPMENT

- * High Mount Assembly
- * Bendix Style Brake
- * Mesh Crank Arm Guards
- * Bridle Assembly
- * Single Rail Tie Down Bars
- * Adjustable Motor Rails
- * 2 Ladders With Safety Cages
- * Cable Fall Restraint
- * Wrist Pin Wrench
- * Gear Oil Fill
- * T Bolts
- * Painted Black & Safety Yellow

OPTIONAL EQUIPMENT

- * Counter Balance Weights
- * Electric Motors
- * Triple Rated Electric Motors
- * Low Oil Level Switch
- * Full Guard With Mesh
- * Fiberglass Full Guard
- * Concrete Bases
- * Colour Options
- * Low Mount Brake Cables
- * Low Mount Engine Rails
- * Drive Sheave & Bolts
- * Vibration Switches
- * Central Lubrication
- * Full Guard Enclosed
- * Partial Belt Guard
- * Pressure Treated Stripping
- * Low Mount Brake Mount
- * Speciality Lube Oils

CONSTRUCTION FEATURES

- * Manufactured To API 11E Specifications
- * CWB Welded To W48
- * Mono Gear Box Mounting Plate
- * Three Leg Sampson Post - Removable Third Leg
- * Saddle Bearing - Double 6" x 11" Railroad Style
- * Split Case Gear Boxes
- * Replaceable Wrist Pin Sleeves
- * Hangar Style Rear Equalizer
- * Pitman Arm Utilize Brass Bearings For Quiet Operation
- * Common Off The Shelf Bearings and Seals

ALX PUMPING UNITS

Please Call For Quote:

ALX Sales: 1-866-ALX-JACK (259-5225)

Address:

ALX Plant
521 6th Street
Estevan, SK
S4A-1A4

Corporate Office
P. O. Box 695
Estevan, SK
S4A-2A6

Date: January 15, 2022

GET PUMPED UP AT "WWW.ALXJACKS.COM"