

QUEST[®] S-SERIES

PREMIUM RESIDENTIAL RIDER. SUPERIOR COMFORT AND VALUE.

FEATURES

Series 2 Deck

Side Discharge: 54

Engine

Kohler® or Exmark

Superior Comfort

Ergonomic seat system

Foot-Lift Assist

Standard to help ease lifting and lowering the cutting deck

Single-Point Height Adjust

Easily to vary the Quest's cutting deck















COMMERCIAL-GRADE FEATURES

Exmark's Quest is a premium entry-level zero-turn mower. The proven commercial features have been adapted for consumer use including the tires and fabricated deck.

LESS TIME MOWING

Quest mowers offer the value you need as a homeowner. Primarily used for your own property, you need the power, performance, comfort and fuel efficiency of a commercial mower.

TOP ACCESSORIES

2-Bag Collection System Assist Bar Engine Maintenance Kit Equipment Cover LED Light Kit Micro-Mulch System ROPS Kit Turf Striping Kit

Accessories may not fit each mower model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.



QUEST S-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
QZ\$708GEM54200	Exmark 708 V-Twin	54"	Series 2 Fabricated	616 lbs.	65.2" x 46.6" x 76.0"
QZ\$735GKC54200	Kohler 7000 KT735	54"	Series 2 Fabricated	616 lbs.	65.2" x 46.6" x 76.0"





POWER COMPONENTS

Engine – Exmark 708cc V-Twin engine; Kohler 7000 Series KT735; governed to 3,300 rpm.

Air Filter – Standard engine manufacturer's air filter

Drive System – Two Hydro-Gear ZT-2200 hydro static transmissions with no hoses and integrated cooling fans and integrated reservoir.

Hydro Fluid – Exmark Premium Hydro Oil.

Speed – Infinitely variable speed selection from 0–7.0 mph (11.3 kmph) forward, 0–5.0 mph (8.0 kmph) reverse.

PTO Engagement – Electromagnetic 105-ft-lb clutch.

Fuel Capacity – 3.0-gallon (11.0-L) single fuel tank with single fill location.

Drive-Wheel Release – Allows unit movement without engine running.

Safety Package – Operator Presence Controls (OPC) and drive system interlock. Deck Lift - Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in

DECK

transport position.

Style – Exmark Series 2 fabricated and welded steel deck. Side discharge standard with the option to bag or mulch.

Deck Construction – 10-gauge top that is formed and welded, 12-gauge side skirt and 7-gauge welded bumper. 4 point suspension.

Widths Available – 54" (137 cm).

Cutting Height – 1.5" (3.8 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments, adjustable from operator seat with standard hand lever or foot-operated assist.

Blade Spindles – No maintenance, sealed and non-greasable spindles. 5.50"-diameter cutter housing with 17mm- (.67") diameter spindle shaft.

Blade-Tip Speed – Approximately 18,500 fnm

EQUIPMENT

Tractor Frame – Unibody, riveted 10-gauge steel.

Steering and Motion Control – Hydraulically dampened twin levers, adjustable both fore and aft. Levers are also adjustable to 2-height positions.

Casters – .25" thick caster yoke arms. Front Caster Tires – 13 x 6.5–6, smooth-tread, pneumatic.

Drive Tires – $20 \times 10-10$ Turf Tech TL.

Turning Radius – True zero-turn.

Parking Brake – Automatic-actuated pawl brake

Seat Comfort – Commercial grade, high back contoured foam padded with arm rests. Hinged mounting and spring suspension. Adjustment is fore and aft for operator position.

Electrical – 12-volt battery with 15-amp alternator.

Standard Features – Engine hour meter, cup holder and hitch.

ACCESSORIES & OPTIONS

2-Bag Collection System, Anti-Blowout Kit, Assist Bar Kit, Engine Maintenance Kit, Equipment Cover, Jack, Jack Mount Receiver, LED Light Kit, Micro-Mulch System, ROPS Kit, Sunshade, Turf Striping Kit and Weight Kit. Accessories may not fit each model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

WARRANTY

Limited Warranty:30-Day Commercial or 3-Year Consumer, 3-Year Engine

