



RADIUS® X-SERIES

LOW MAINTENANCE. COMMERCIAL DURABILITY. SIMPLE OPERATION.

FEATURES

UltraCut™ Deck

Side Discharge: 60

Commercial-Grade Engines

Kawasaki®

Easy to Service


Toolless removable floor pan and belt shields

Full-Suspension Seating System

Standard on X-Series

Standard Integrated Tow Hitch

Allows for quick attachment of light implements and carts with an 80-pound capacity



EASY TO SERVICE

Operators can easily access the top side of the cutting deck, belts and spindles with the toolless, removable floor pan and belt shields. The welded jack receiver also allows quick access to the underside of the deck when combined with the optional jack.



COMMERCIAL-GRADE ENGINES

All Radius models come with commercial-grade engines. The X-Series models feature heavy-duty, canister-style air filtration systems for extended filter and engine life.

TOP ACCESSORIES

- Engine Maintenance Kit
- LED Light Kit
- Micro-Mulch System
- Operator Controlled Discharge
- Sun Shade
- Trash Container
- Turf Striping Kit
- UltraVac Collection Systems

Accessories may not fit each mower model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

The commercial mowers more landscape pros trust.

exmark.com

RADIUS X-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
RAX921GKA604A3	FX921V Kawasaki	60"	UltraCut Series 4	1240 lbs.	72.7" x 70.4" x 82.2"



Side Discharge



Side Discharge

POWER COMPONENTS

Engine – FX921V Kawasaki engines; governed to 3,700 rpm.

Air Filter – Heavy-duty canister air filtration system.

Drive System – Dual Hydro-Gear ZT-3400, hydrostatic transmission with charge pumps, relief valves and spin-on filter.

Hydro Fluid – Exmark Premium Hydro Oil.

Speed – Infinitely variable speed selection from 0–10.0 mph (16.1 kmph) forward, 0–6.0 mph (9.7 kmph) reverse.

PTO Engagement – MagStop electromagnetic 125-ft-lb clutch.

Fuel Capacity – 7-gallon (26.5-L) single fuel tank with single fill location.

Drive-Wheel Release – Allows unit movement without engine running.

Safety Package – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

Rollover Protection System (ROPS) – 2-post foldable ROPS standard with seat belt and latch.

Deck Lift – Standard; foot-controlled deck lift changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

DECK

Style – Full-floating 5.5"-deep UltraCut Series 4. All models have side discharge standard with molded discharge chute and option to bag or mulch.

Deck Construction – 10-gauge top that is formed and continuously seam welded and 7-gauge side skirt on all units. 7-gauge spindle mounting. Adjustable, anti-scalp rollers.

Widths Available – 60" (152 cm).

Cutting Height – 1.5" (3.8 cm) to 5.0" (12.7 cm) in 0.25" (.6 cm) increments, adjustable from operator seat.

Blade Spindles – No maintenance, sealed and non-greasable spindles. 7.75"-diameter cutter housing with 25mm- (.98") diameter spindle shaft and splined blade driver.

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Tractor Frame – Unibody, welded, heavy-duty 2" X 3" rectangular tubular steel.

Steering and Motion Control – Hydraulically dampened twin levers, adjustable both fore and aft. Levers are also adjustable to 2-height positions.

Casters – 0.375"-thick caster yoke arms.

Front Caster Tires – 13 x 6.5–6, smooth tread, pneumatic.

Drive Tires – 24 x 10.5–12.

Turning Radius – True zero-turn.

Parking Brake – Lever-actuated pawl brake.

Seat Comfort – Deluxe suspension (adjustable spring suspension) seat with high back, molded foam flip-up armrests, and integral safety switch.

Electrical – 12-volt battery with 15-amp alternator.

Standard Features – Engine hour meter, cup holder, tow hitch and jack receiver.

ACCESSORIES & OPTIONS

12-Volt Power Adapter, 2-Bag Collection System - Powered, 3-Bushel Bagger, 5-Gallon Bucket, Bucket Mount Kit, Bucket Mount & 5-Gallon Bucket, Engine Maintenance Kit, Equipment Cover, Extended Drive Lever Kit, Hydro Maintenance Kit, Jack, Light Kit - LED, Micro-Mulch System, Operator Controlled Discharge (Hand), Seat Cover, Semi-Pneumatic Tire Assembly, Sun Shade, Trash Container, Turf Striping Kit, UltraVac Collection Systems.

Accessories may not fit each model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

WARRANTY

Limited Warranty: 4-Year or 1,000 Hours, includes engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut = 99 = acres per hour | 80% efficiency: MPH x width of cut = 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Radius® are registered trademarks of Exmark Mfg. Co., Inc. ©2022 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2022. Rev 1.