

Boat Manufactured By V// 2550 Highway 52 • Moncks Corner, SC

(843) 761-6090

www.seafoxboats.com

SEA FOX[®] 226 COMMANDER

Length	22' 4"
Beam	8' 6"
Dry Weight (Boat Mfr. Pub)	2,700 lbs
Maximum HP	250 hp
Fuel Capacity	105 gal
Weight as Tested	3,979 lbs

F200XB

Horsepower	200 hp
Induction	EFI
Displacement	2.8 L
Weight (Estimated)	489 lbs
Gear Ratio	1.86

ENGINE MOUNTING HEIGHT

Mounting Hole Position	#2
Ventilation Plate Height	1/2" Above Boat Bottom

PROPELLER(S)

Series	Reliance®
Diameter x Pitch	14 1/2 x 15
Yamaha Part #	68F-45970-20-00
Propeller Material	Polished Stainless Steel

TEST CONDITIONS

Number of People	2
Air / Water Temperature (Fahrenheit)	88° F / 81° F
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

COMMENTS

Test weight includes 1/2 tank of fuel, 1 battery, safety and test gear.

YPB#: PB_SFX_226Commander_F200XB_2017-08-13_OCC

PERFORMANCE BULLETIN



Engine: Yamaha F200XB Boat: Sea Fox[®] 226 Commander **Configuration:** Single Test Date: 13-Aug-2017



PERFORMANCE DATA

4000			6.00
1000	5.1	0.8	6.38
1500	6.6	1.3	5.08
2000	7.8	2.1	3.71
2500	9.2	3	3.07
3000	16.3	4.1	3.98
3500	23.9	5.2	4.6
4000	28.4	6.5	4.37
4500	33.1	8.3	3.99
5000	36.6	11.6	3.16
5500	41	15.6	2.63
5900	44.2	18.6	2.38

NOTICE TO CONSUMER The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/dv boat weight, and operator ability. Please confirm the specifications and performance data on your specific hoad/regine combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha PowerMatched components. Yamaha reserves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.