

Marlin 300

30' Walkaround Cabin



Marlin 300 Main Specifications

Beam Amidships	10'7" (3.23 m)
Center Line Length w/o Engines	30'6" (9.30 m)
Bridge Clearance	9'9" (2.97 m)
Cockpit Depth	29" (0.74 m)
Hull Draft	23" (0.58 m)
Transom Deadrise	19.5 degrees (SeaVee® progression)
Maximum HP	700 (522 kW)
Fuel Capacity - Standard	282 gal. (1067 l)
Weight w/o Engines	8221 lb. (3729 kg)

Marlin 300 Features & Options

STANDARD FEATURES

Safety

2 automatic bilge pumps (total 2600 GPH) (9842 LPH)

Basic flotation

Bow rail - 316 grade stainless steel

Captain Grady® - digital boat systems & operations guide for iPad & iPhone

Cockpit toe rails

Cabin

Accessory outlet - 5V duplex USB port

Berth - aft double berth

Berth - forward vee berth

Carbon monoxide detector

Door - lockable w/screen & companionway hatch

Forward hatch - low profile acrylic hatch w/screen & shade

Galley - port galley w/sink, light & Corian® cutting board

Composite stringer system & transom - water impervious

Nonskid fiberglass liner

Nonskid recessed walkaround

Self-bailing cockpit w/cockpit drains (4)

Stainless steel through-hull fittings

Rod storage - aft berth horizontal (4)

Rod storage - forward horizontal (6)

Stereo system w/AM/FM tuner, MP3 auxiliary audio connections/amplifier, Bluetooth®, remote unit & fold down storage; speakers w/LED lights - cabin (2), cockpit (2), helm (2)

Storage - galley cabinets & counter

Storage - under berth compartments

Storage nets

Head - enclosed head area w/sink, shower, lamp & VacuFlush® marine head w/freshwater supply, 10-gallon (38 l) holding tank, overboard discharge & deck pump out

Lighting - dome (2)

Lighting - reading (3)

Microwave oven

Mirror

Refrigerator - stainless steel

Cockpit & Deck

100% hand laid SeaV² hull & deck

Accessory outlet - 12V

Accessory outlet - 5V duplex USB port

Anchor windlass w/remote switches at helm & windlass

Batteries (4) w/battery select switches (one per engine) & charger system (1)

Bow pulpit w/roller

Cleats

Cockpit bolsters

Cockpit freshwater shower (recessed)

Cockpit lights - blue LED

Companion grab rail

Deck hardware - 316 grade stainless steel through-bolted

Dockside power w/galvanic isolator

Drink holders - stainless steel (9)

Engine flush system w/hose attachment aft (one per engine)

Factory engine pre-rigging

Fighting chair reinforcement

Fish box - 290-qt. (274.4 l) aft insulated fish box w/light & ob drain

Flush mount electronics area

Footrests - helm & companion (fold down)

Freshwater level indicator

Fuel capacity - 282 gallons (141-gallon tank, 141-gallon tank) (1067 l)

Stove - electric glass top

Table - cherry

Teak & holly sole

Water heater - 6-gallon (22.7 l), 120V

Water tank - 32-gallon (121.1 l) freshwater

Windows - tinted frameless acrylic w/shade

International lighting

Livewell - 32-gallon (121.1 l) port insulated raw water livewell w/light, full column distribution inlet & ob drain (1100 GPH pump) (4164 LPH)

Rigging station - freshwater sink, insulated bait box w/ob drain & lockable drawers

Rod holders (4)

Rod storage racks - horizontal (6)

Rubrail - high density PVC w/stainless steel insert

Seating - Deluxe II vertically & horizontally adjustable helm & companion chairs

Seating - foldaway aft bench seat w/cushion

Seating - foredeck cushions

Seating - port livewell cushion

Seating - starboard rigging station cushion

Steering - Helm Master EX® Digital Electric Steering

Steering wheel - 316 grade stainless steel w/knob

Stern eyes - 316 grade stainless steel

Storage - aft deck lift out box

Storage - forward anchor locker w/rode storage

Storage - lockable storage under helm & companion seats

Storage - under step compartment

Transducer mounting flats

Transom door - fiberglass

Hardtop w/painted aluminum frame, radio box, storage nets, spreader lights, side mounted rod holders (4), outrigger plates & drop, front & side curtains (black or ivory)

Hydraulic trim tabs w/indicator & retractor

Integrated outboard mounting system w/swim platform & ladder

Washdown - freshwater

Washdown - pressurized raw water w/hose

Water tank - 32-gallon (121.1 l)

Windshield - ventilated tempered glass

Windshield wipers w/starboard washer

OPTIONAL FEATURES

Options

Air conditioning - 8000 BTU in cabin

Bow thruster

CE certification package (European Conformity)

Cockpit freshwater shower w/hot & cold mixer

Engine paint - Yamaha factory-painted engine(s), pearlescent white

Generator - 5kW diesel, 12-gallon (45.4 l) fuel capacity

Hardtop color - underside of fiberglass hardtop (requires matching gelcoat hull color option)

Hull color - Celestial Blue, Coastal Fog Blue, Ocean Mist Blue, or Sea Glass gelcoat

International AC electrical conversion - 220V (50Hz)

Lighting - underwater blue LED (3)

Outrigger kit - 18-ft. (5.5 m) crank hardtop mounted stainless steel outriggers w/carbon fiber poles

Painted hardtop top mounted rod holders (6)

Rod storage - folding cabin rack (4)

Seating - companion bench seat (replaces Deluxe II companion chair)

Seating - Command Elite contoured helm chair (1) horizontally & vertically adjustable w/deluxe cushioning & flip-up bolster

Seating - Command Elite contoured helm chair & companion chair (2) horizontally & vertically adjustable w/deluxe cushioning & flip-up bolster

Steering - Helm Master EX® w/Full Maneuverability

TV - 19" LED flat screen w/AV input panel