

# **PERFORMANCE BULLETIN**



(843) 761-6090

## **SEA FOX® 288 COMMANDER**

Length	28' 0"
Beam	9' 8"
Dry Weight (Boat Mfr. Pub)	6,000 lbs
Maximum HP	600 hp
Fuel Capacity	200 gal
Weight as Tested	8,284 lbs

#### F300XCA / LF300XCA

Horsepower	300 hp
Induction	EFI
Displacement	4.2 L
Weight (Estimated)	562 lbs
Gear Ratio	1.75

#### **ENGINE MOUNTING HEIGHT**

Mounting Hole Position	#2
Ventilation Plate Height	3/4" Above Boat Bottom

#### PROPELLER(S)

Series	Saltwater Series II™
Diameter x Pitch	15 1/4 x 19
Yamaha Part #	6CE-45970-20-00
Propeller Material	Polished Stainless Steel

#### **TEST CONDITIONS**

Number of People	2
Air / Water Temperature	88° F / 81° F
(Fahrenheit)	66 17 61 1
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

# **COMMENTS**

Test weight includes 1/2 tank of fuel, 2 batteries, safety and test gear.

YPB#: PB\_SFX\_288Commander\_t\_F300XCA\_2017-08-13\_OCC



Engine: Yamaha F300XCA / LF300XCA

**Boat:** Sea Fox® 288 Commander

**Configuration:** Twin Test Date: 13-Aug-2017



### **PERFORMANCE DATA**

RPM	МРН	GPH	MPG
1000	6.5	2.6	2.5
1500	8.5	4.4	1.93
2000	10.6	6.8	1.56
2500	20	10.2	1.96
3000	29.4	12.7	2.32
3500	33.5	16.1	2.08
4000	39.6	22	1.8
4500	44.7	28.3	1.58
5000	49.4	33.7	1.47
5500	53	40.8	1.3
6000	58.5	51.9	1.13
0-30 MPH: 4.5			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boat's actual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability. Please confirm the specifications and performance data or pour specific boat/reging combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha Perseves the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.