



# **2023** CFORCE 600 **TOURING**

**Available** colours



# **Inclusions**

More than \$4 000 in included add-ons!

# The most equipped vehicles on the market

Standard features and benefits

Hitch receiver \$100 value

Passenger backrest \$200 value

5-year CFMOTO warranty \$2 000 value

3 000 Lbs Towing winch (complete assy) \$1 000 value

#### Safety and convenience package

- Hand protectors
- 12v outlet
- LED headlight with integrated turn signals
- Horn



- USB plug

\$1 000 value



5 Year limited warranty: 1 year complete with no milage restriction + 48 months balance powertrain only or 5,000 km

# **Starting at \$11 049\***













Electric-power Engine management normal/work

charging port

Fuel injected

Cytech clutch system

# **Specifications**

#### Motor

Type: Single-Cylinder, liquid-cooled, 4-valves, 4-strokes

Displacement: 580 cc

**Bore & Stroke:** 

91 x 89.2 mm (3.58 x 3.5 in)

Compression: 10.7:1

**Engine management:** 

Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Amp

## Size / weight

Lenath x width x height: 2 235 x 1 180 x 1 390 mm

(88 x 46.4 x 54.7 in)

Wheelbase: 1 480 mm (58.2 in)

Ground clearance: 270 mm (10.6 in)

Minimum turning Radius:

3700 mm (146 in)

Fuel tank capacity: 18 L (4.76 gal)

Net weight: 415 kg (915 lbs)

Rack capacity (Front/Rear): 20 kg (44 lbs) / 40 kg (88 lbs)

#### **Brakes**

Four wheel hydraulic disc + rear wheel parking

#### Wheels

Front wheels:

Aluminium alloy (12 x 6 in)

Rear wheels:

Aluminium alloy (12 x 7.5 in)

Front tires: AT 25 x 8-12

Rear tires: AT 25 x 10-12

#### **Transmission**

CV-Tech IBC clutch system:

Variable transmission.

Gearbox: L/H/N/R/P (parking lock shift system)

Power train: 2WD / 4WD, electric

locking differential

# Suspension and direction

Front suspension:

Double A-arm independant

Front travel: 160 mm (6.3 in)

Rear suspension: Double A-arm independant

Rear travel: 210 mm (8.2 in)

Steering:

Electonic Power Steering (EPS)

### Protection plan

EASY protection plan available











