

G-56A Grapple

Productive, Durable, Value®



cylinders, hoses, & fittings

Secure & covered hydraulic hoses

Four sided protection of cylinder rods

Side mounted auxiliary connections

Eight-tine grapple base

Four point reinforcement

Fully enclosed back




The best value pricing in the industry!

SPECIFICATIONS

Weight (approximate) without attachment hoses Width of grapple Depth of grapple Maximum height of grapple (closed) Maximum height of grapple (open) Maximum opening gap

478 lbs. 217 kg. 56 in. 1,422 mm. 41 in. 1.041 mm. 762 mm. 30 in. 41.75 in. 1,060 mm. 40 in. 1,016 mm.



More useful load

Serial number identification

Detailed operator's manual

Industry leading safety labeling

One year warranty on materials and workmanship









Premium hydraulic cylinders, hoses, & fittings

Secure & covered hydraulic hoses

Four sided protection of cylinder rods

Side mounted auxiliary connections

Ten-tine grapple base

Four point reinforcement


Fully enclosed back



SPECIFICATIONS

Weight (approximate) without attachment hoses Width of grapple
Depth of grapple
Maximum height of grapple (closed)
Maximum height of grapple (open)
Maximum opening gap

684 lbs. 310 kg. 72 in. 1,829 mm. 41 in. 1,041 mm. 30 in. 762 mm. 41.75 in. 1,060 mm. 40 in. 1,016 mm.



More useful load

Serial number identification

Detailed operator's manual

Industry leading safety labeling

One year warranty on materials and workmanship



