

# Explore new horizons



**CFMOTO**  
CANADA ✦

# CFORCE 1000 OVERLAND 2024

CF1000AZ

Available  
colours



**The most equipped vehicles  
on the market**

**More than \$5,600 in add-ons!**

Standard features  
and benefits

Removable rear cargo box  
Storage capacity of 105 L  
**\$600 value**

Skid plate assembly  
**\$1,050 value**

3,500 lbs winch  
(complete assembly)  
**\$1,000 value**

High strength aluminum  
winch armor  
**\$100 value**

Hand guard assembly  
with windshield  
**\$300 value**

Aluminium rims with  
14" retaining ring  
**\$1,800 value**

5-year CFMOTO warranty

Safety and convenience  
package

- Including:
- LED lights
  - Side mirrors
  - Hand protector
  - Retaining bars for passenger
  - Trailer connector
  - USB port
  - 12V outlet
  - Turn signals
  - Horn
- \$750 value**

**BEST**  
**5**  
**YEAR**  
LIMITED WARRANTY

5 Year limited warranty:  
1 year complete with no mileage  
restriction + 48 months balance  
powertrain only or 5,000 km



Hydraulic Shock  
Absorber With 5 Spring  
Preload Adjustment



Electric-power  
steering



Cvtch clutch  
system

## Specifications

### Motor

Type: V-Twin cylinder, 4 strokes,  
8 valves

Displacement: 963 cc

Bore & Stroke:  
91 x 74 mm (3.58 x 2.9 in)

Compression: 10.6:1

Engine management:  
Fuel injected engine

Cooling system: Liquid

Starting: Electric

Battery: 30 Ah

### Size / weight

Length x Width x Height:  
2310 x 1264 x 1420 mm  
(90.9 x 49.8 x 55.9 in)

Wheelbase: 1480 mm (58.3 in)

Minimum ground clearance:  
285 mm (11.2 in)

Minimum turning radius:  
3800 mm (149.6 in)

Fuel tank capacity: 28 L (7.3 gal)

Net weight: 490 kg (1080 lbs)

Towing capacity: 748 kg (1659 lbs)

Payload capacity: 250 kg (551 lbs)

Rear box capacity:

Front 20 kg (44 lbs)

Rear 40 kg (88 lbs)

### Brakes

Four wheel hydraulic disc +  
rear wheel parking

### Wheels

Front wheels:  
Aluminum alloy (14 in)

Rear wheels:  
Aluminum alloy (14 in)

Front tires: AT 27 x 9-14

Rear tires: AT 27 x 11-14

### Transmission

CV-Tech IBC clutch system:  
Variable transmission

Gear box: L / H / N / R / P (parking  
lock shift system)

Power train: 2WD / 4WD, electric  
locking differential

### Suspension and direction

Front suspension: Double A-arm,  
independent suspension, gas shock  
absorber with adjustable rebound/  
compression

Front travel: 180 mm (7.1 in)

Rear suspension: Independent  
trailing arm rear, fully adjustable  
gas shocks

Rear travel: 190 mm (7.5 in)

Steering: Electric Power Steering  
(EPS)

### Protection plan

EASY protection plan available



Follow us



cfmoto.ca

\*The pictures are for illustrative purposes only and accessories shown are not included. Specifications to change without notice. Details in store.