



HTX HALF-TON STRAIGHT-BLADE

APPLICATIONS: DOWNSIZED 4X4s, 1/2-TON TRUCKS AND SUVs, LIGHT DUTY PICKUPS



SPECIFICATIONS	7'0" HTX (Steel Poly Stainless)	7'6" HTX (Steel Poly Stainless)
Blade Width (Straight)	84" (213 cm)	90" (229 cm)
Plowing Width @ 30° Angle	73" (185 cm)	78" (185 cm)
Blade Height	26" (66 cm)	26" (66 cm)
Blade Thickness	14-ga (.19 cm) Mild Steel 1/4" (.6 cm) Poly 14-ga (.19 cm) Stainless Steel	14-ga (.19 cm) Mild Steel 1/4" (.6 cm) Poly 14-ga (.19 cm) Stainless Steel
Cutting Edge (High Performance)	1/4" x 6" (.6 cm x 15 cm)	3/8" x 6" (1 cm x 15 cm)
Reinforcement Ribs	4 vertical, 2 diagonal	6 vertical, 2 diagonal
Plow Shoes	Optional	Optional
Trip Springs	2	2
Angle Cylinders	1-1/2" x 6-1/2" (4 cm x 17 cm)	1-1/2" x 6-1/2" (4 cm x 17 cm)
Lift Cylinder	1-3/4" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)	1-3/4" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)
Shock Absorber	N/A	N/A
Attachment System	SmartHitch 2	SmartHitch 2
Plow Weight*	393 lb (178 kg) 367 lb (166 kg) 393 lb (178 kg)	440 lb (200 kg) 416 lb (188 kg) 440 lb (200 kg)
Plow Lights	SL3 L.E.D. with Ice Shield Technology	SL3 L.E.D. with Ice Shield Technology

*Plow weight does not include vehicle mount weight. Vehicle mount weight range: 45-75 lb (20-34 kg).

BOSS Products, a division of The Toro Company, reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used herein.

©2016 BOSS Products/The Toro Company. All rights reserved. Patents: www.ttcopats.com