



# TRIP-EDGE SUPER-DUTY STRAIGHT-BLADE

**APPLICATIONS:** 4X4s, 1/2-TON TO 1-TON TRUCKS, SUVs AND SKID STEERS



SPECIFICATIONS	7'6" Trip-Edge (Steel   Stainless Steel)	8' Trip-Edge (Steel   Stainless Steel)	9' Trip-Edge** (Steel   Stainless Steel)
Blade Width (Straight)	90" (229 cm)	96" (244 cm)	108" (274 cm)
Plowing Width @ 30° Angle	78" (198 cm)	83" (211 cm)	93-1/2" (238 cm)
Blade Height	31" (79 cm)	31" (79 cm)	31" (79 cm)
Blade Thickness	11-ga Steel   14-ga 304 Stainless	11-ga Steel   14-ga 304 Stainless	11-ga Steel   14-ga 304 Stainless
Base Angle	1/2" x 6" x 3-1/2" (1.3 cm x 15 cm x 9 cm)	1/2" x 6" x 3-1/2" (1.3 cm x 15 cm x 9 cm)	1/2" x 6" x 3-1/2" (1.3 cm x 15 cm x 9 cm)
Cutting Edge	1/2" x 6" (1.3 cm x 15 cm)	1/2" x 6" (1.3 cm x 15 cm)	1/2" x 6" (1.3 cm x 15 cm)
Reinforcement Ribs	6 vertical, 2 diagonal	6 vertical, 2 diagonal	6 vertical, 2 diagonal
Plow Shoes	Cast Iron	Cast Iron	Cast Iron
Trip Springs	4	4	4
Trip Pivot Pin Diameter	1 (3 cm)	1 (3 cm)	1 (3 cm)
Trip Spring Type	3/8" (1 cm) hooked extension spring	3/8" (1 cm) hooked extension spring	3/8" (1 cm) hooked extension spring
Trip-Edge Adjustable	Standard	Standard	Standard
Angle Cylinders	1-1/2" x 10" (4 cm x 25 cm)	1-1/2" x 10" (4 cm x 25 cm)	1-1/2" x 10" (4 cm x 25 cm)
Lift Cylinder	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)	2" x 1-1/8" x 10" (5 cm x 3 cm x 25 cm)
Attachment System	SmartHitch 2	SmartHitch 2	SmartHitch 2
Plow Weight*	796 lb (361 kg)   853 lb (387 kg)	825 lb (374 kg)   875 lb (397 kg)	877 lb (398 kg)   934 lb (424 kg)
Plow Lights	SL3 L.E.D. with Ice Shield Technology	SL3 L.E.D. with Ice Shield Technology	SL3 L.E.D. with Ice Shield Technology

\*Plow weight does not include vehicle mount weight. Vehicle mount weight range: 75-105 lb (34-48 kg).

\*\*Includes 1-ton trucks with dual rear wheels.