

TRASH PUMPS



DPT50



DPT80

Model	DPT50	DPT80
Pump type	Trash pump	Trash pump
Suction / Discharge port diameter	50 mm (2 in)	80 mm (3 in)
Total head	30 m (98 ft)	25 m (82 ft)
Suction head	7.5 m (23 ft)	7.5 m (23 ft)
Flow	500 L/min	1000 L/min
Engine type	4-stroke OHV Air Cooled Single Cylinder	
Horsepower	7 HP	7 HP
Displacement	212 cc	212 cc
Starting system	Recoil	Recoil
Fuel tank capacity	3.6 L (1 gal)	3.6 L (1 gal)
Dry weight	30 kg (66 lb)	35 kg (77 lb)

WATER PUMPS



DP40



DP50



DP80

Model	DP40	DP50	DP80
Pump type	Centrifugal	Centrifugal	Centrifugal
Suction / Discharge port diameter	40 mm (1.5 in)	50 mm (2 in)	80 mm (3 in)
Total head	18 m (59 ft)	32 m (105 ft)	28 m (92 ft)
Suction head	6 m (20 ft)	7.5 m (23 ft)	7.5 m (23 ft)
Flow	233 L/min	467 L/min	967 L/min
Engine type	4-stroke OHV Air Cooled Single Cylinder		
Horsepower	3.5 HP	7 HP	7 HP
Displacement	79 cc	212 cc	212 cc
Starting system	Recoil	Recoil	Recoil
Fuel tank capacity	1.4 L (0.37 gal)	3.6 L (1 gal)	3.6 L (1 gal)
Dry weight	13 kg (29 lb)	22 kg (49 lb)	25 kg (55 lb)

WOOD CHIPPERS



Rotor and blades



SC15E



B1500E

Model	SC15E	B1500E
Engine type	4-stroke OHV Air Cooled Single Cylinder	
Displacement	420 cc / 15 HP	420 cc / 15 HP
Starting system	Electric & recoil	Electric & recoil
Fuel tank capacity	6.5 L (1.7 gal)	6.5 L (1.7 gal)
Chipping capacity	3.5 in	5 in
Battery	Standard	Standard
Cutting	1 blade and 16 hammers	2 blades on rotor and 1 counter-blade on the chassis
Drive type	Twin V belts	Twin V belts
Dimensions: L x W x H	80 x 48 x 11.5 cm (31 x 19 x 4 in)	52 x 72 x 93 cm (21 x 28 x 37 in)
Dry weight	110 kg (243 lb)	165 kg (364 lb)

The Ducar Series of fine power products are characterized by advanced design, compact structure, reliable performance, easy starting and low fuel consumption.

Ducar power products are covered by a one-year limited consumer warranty.

They are the best choice for the environmentally conscious user. In fact, all of Ducar's engines have been certified by the EPA (Environment Protection Agency, USA). The generators meet CSA certification. We are proud to provide you with a safe, reliable and durable power equipment.



Distributed by:
MTI
 CANADA
www.mticanada.ca

Your dealer:

DUCAR


POWER EQUIPMENT



GENERATORS



D 2 0 0 0 i S



D 2 0 0 0 i S - P K



D 4 0 0 0 i



D G 1 5 0 0



D G 3 5 0 0



D G 6 5 0 0



D G 9 2 5 0 E



D G 9 2 5 0 E H D



D G 1 5 0 0 0 E

Model	D2000iS Inverter	D4000i Inverter	DG1500	DG3500	DG3500(R)	DG4950	DG6500	DG6500(R)	DG9250E & HD	DG15000E
Frequency	60 Hz	60 Hz	60 Hz	60 Hz		60 Hz	60 Hz		60 Hz	60 Hz
Maximum wattage	2000W	4000W	1500W	3000W		5000W	6500W		9250W	15000W
Rated wattage	1600W	3500W	1400W	2800W		4000W	5500W		7500W	12500W
AC voltage	120V	120V	120V	120 / 240V		120 / 240V	120 / 240V		120 / 240V	120 / 240V
DC voltage	12V / 5A	12V / 8.3A	12V / 8.3A	12V / 8.3A		12V / 8.3A	12V / 8.3A		12V / 8.3A	—
Engine type	4-stroke OHV Air Cooled Single Cylinder									Twin Cylinder
Displacement	80 cc	224 cc	98 cc	212 cc		224 cc	420 cc		420 cc	713 cc
Horsepower	3 HP	7.5 HP	3.5 HP	7 HP		8 HP	15 HP		15 HP	20 HP
Starting system	Recoil	Electric & recoil	Recoil	Recoil	Remote starter & recoil	Recoil	Electric & recoil	Remote starter & recoil	Electric & recoil	Electric
Fuel tank capacity	4.5 L / 1.1 gal	12 L / 3.2 gal	6 L / 1.59 gal	15 L / 4 gal		15 L / 4 gal	25 L / 6.6 gal		25 L / 6.6 gal	40 L / 10.6 gal
Oil tank capacity	0.4 L / 0.1 gal	0.6 L / 0.2 gal	0.4 L / 0.1 gal	0.6 L / 0.2 gal		0.6 L / 0.2 gal	1 L / 0.3 gal		1 L / 0.3 gal	1.5 L / 0.4 gal
Noise level	59 dB	59 dB	65 dB	69 dB		72 dB	74 dB		77 dB	79 dB
Oil alert	Standard	Standard	Standard	Standard		Standard	Standard		Standard	Standard
Transport wheels	—	Standard	—	—		Standard	Standard		Standard	Standard
Battery	—	Standard	—	—	Standard	—	Standard		Standard	Standard
Dry weight	21 kg (46 lb)	47.5 kg (105 lb)	26 kg (57 lb)	45 kg (99 lb)		52 kg (114 lb)	83 kg (183 lb)		E: 90 kg (198 lb) E HD: 111 kg (245 lb)	215 kg (474 lb)

Model DG9250EHD has an auto idle.
Specifications are subject to change without notice. Models may differ from the picture. Printed in Canada © MTI Canada inc.

GASOLINE ENGINES

Model	DJ154F	DJ168F	DJ170F	DH270	DJ188F & F-D	DJ190F-D	DHT720E
Engine type	4-stroke OHV Air Cooled Single Cylinder						Twin Cylinder
Displacement	79 cc / 3.5 HP	196 cc / 6.5 HP	208 cc / 7 HP	270 cc / 9 HP	389 cc / 13 HP	420 cc / 15 HP	713 cc / 20 HP
Starting system	Recoil	Recoil	Recoil	Recoil	F: Recoil F-D: Electric & recoil	Electric & recoil	Electric
Crankshaft diameter	16 mm	19.05 mm	19.05 mm	25.4 mm	25.4 mm	25.4 mm	25.4 mm
Crankshaft type	Key way / Q Type						
Bore / Stroke	54 mm / 34.4 mm	68 mm / 54 mm	70 mm / 54 mm	77 mm / 58 mm	88 mm / 64 mm	90 mm / 66 mm	80 mm / 71 mm
Engine oil capacity	0.4 L (0.1 gal)	0.6 L (0.2 gal)	0.6 L (0.2 gal)	1 L (0.3 gal)	1.1 L (0.3 gal)	1.1 L (0.3 gal)	1.5 L (0.4 gal)
Oil alert	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Dry weight	10 kg (22 lb)	15 kg (33 lb)	15,5 kg (34 lb)	24 kg (53 lb)	F: 30 kg (66 lb) F-D: 31 kg (68 lb)	30,5 kg (67 lb)	47 kg (104 lb)

D J 1 6 8 F



D J 1 9 0 F - D



D H T 7 2 0 E



PRESSURE WASHERS

Model	R100	MDI2900-L
Engine type	4-stroke OHV Air Cooled Single Cylinder	
Displacement	79 cc / 3 HP	196 cc / 6.5 HP
Starting system	Recoil	Recoil
Pressure	1 450 psi	2 900 psi
Delivery	6 L / min	11.3 L / min
Hose length	6 m (20 ft)	10 m (33 ft)
Nozzle	3	4
Dry weight	15 kg (33 lb)	40 kg (88 lb)



R 1 0 0



M D I 2 9 0 0 - L

LAWN MOWERS



D M 4 1 S



D M 5 3 S



D M 5 0 P L - A

Model	DM41S	DM53S	DM53SE	DM50PL-A
Engine model	DVO160	DV173		DVO160
Displacement	161 cc	173 cc		161 cc
Starting system	Recoil	Recoil	Electric & recoil	Recoil
Engine speed	2800 rpm			
Mower type	Self propelled			Push
Cutting width	17 in (43 cm)	21 in (53 cm)		20 in (51 cm)
Cutting height	7 cutting positions 25 mm to 75 mm			5 cutting positions 25 mm to 75 mm
Dry weight	29 kg (64 lb)	36 kg (79 lb)		27 kg (60 lb)

TILLER

Model	DT36V-6
Engine model	DVO160
Engine type	4-stroke OHV Air Cooled Single Cylinder
Displacement	161 cc
Starting system	Recoil
Transmission system	Worm and gear
Clutch type	Belt tensioned clutch
Bore / stroke	65 mm / 48.5 mm
Tillage Width	22 in (56 cm)
Front wheel	6 in (15 cm)
Dry weight	30 kg (66 lb)

