

GRAVELY

PRO-TURN 600



MEET YOUR NEW EMPLOYEE OF THE MONTH FOR THE FORESEEABLE FUTURE.

When you add a Pro-Turn 600 to your crew, it's kind of like adding another employee. It cuts faster and more efficiently, handling more work in less time. Its Operator Pod System was designed to keep you mowing comfortably sunrise to sunset, cutting back on driver fatigue.

Best of all, it will impress both your clients and any potential crew members because they'll see you only use the best.

5YR
FIVE YEAR OR 1500 HOUR
WARRANTY

52"

MODEL - 992505

35 HP / Kawasaki® FX1000V Engine

60"

MODEL - 992501

35 HP / Kawasaki® FX1000V Engine

MODEL - 992503

38.5 HP / Kawasaki® FX1000V-EFI Engine

72"

MODEL - 992502

35 HP / Kawasaki® FX1000V Engine

MODEL - 992504

38.5 HP / Kawasaki® FX1000V-EFI Engine

DIAL-A-HEIGHT This lets the operator easily adjust the deck height by quarter-inch increments.

PARKER HTG TRANSMISSION Warranty that matches the machine warranty and allows up to 15 mph operation. Making the Pro-Turn 600 a very efficient mower for any crew trying to get work out of every daylight hour.

X-FACTOR® 3 DECK The deck has been completely redesigned for better grass dispersion. Its new look is constructed from 7-gauge steel to deliver years of solid performance.

PRO-TURN® 600



See your professional Gravelly® dealer for complete warranty details.

	652	660	660	672	672
MODEL NUMBER	992505	992501	992503	992502	992504
ENGINE	KAWASAKI® FX1000V	KAWASAKI® FX1000V	KAWASAKI® FX1000V-EFI	KAWASAKI® FX1000V	KAWASAKI® FX1000V-EFI
HORSEPOWER	35 HP	35 HP	38.5 HP	35 HP	38.5 HP
DISPLACEMENT	999 CC	999 CC	999 CC	999 CC	999 CC
DRIVE SYSTEM	PARKER HTG TRANSMISSION				
FUEL CAPACITY	12.7 GAL				
GROUND SPEED (APPROX. Mph) (Forward/ Reverse)	15 MPH / 6 MPH				
DECK					
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT				
DECK CONSTRUCTION	FABRICATED X-FACTOR III				
NUMBER OF SPINDLES	3				
BLADE TIP SPEED (FPM)	18,000				
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM				
SPINDLE BEARINGS	BALL BEARING				
DECK ENGAGEMENT	OGURA® GT3.5 ELECTRIC CLUTCH				
CUTTING WIDTH	52 IN	60 IN	60 IN	72 IN	72 IN
CUTTING HEIGHTS	1.0 IN - 5.5 IN				
CUTTING POSITIONS	19				
WHEELS					
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES				
FRONT	SMOOTH 15 X 6-6 SEMI PNEUMATIC				
REAR	26 X 12-16 LOW PROFILE RADIAL TURF				
FEATURES					
SEAT	HIGH BACK BOLSTERED WITH SUSPENSION POD SYSTEM				
FOLDABLE ROPS	STANDARD				
MACHINE					
WEIGHT	1535 LBS	1586 LBS	1601 LBS	1646 LBS	1661 LBS
LENGTH	83 IN				
WIDTH (w/o CHUTE)	55 IN	63 IN	63 IN	75 IN	75 IN
WIDTH (w/ CHUTE)	63 IN	75 IN	75 IN	87 IN	87 IN
HEIGHT (w/ ROPS EXT/DOWN)	71.5 IN / 47.8 IN				
WARRANTY					
UNIT	5 YEAR / 1500 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS - SEE YOUR PROFESSIONAL GRAVELLY® DEALER FOR COMPLETE WARRANTY DETAILS				
DECK SHELL & FRAME	LIMITED LIFETIME				

ATTACHMENTS & ACCESSORIES

MULCHING KIT
 TRAILER HITCH KIT
 LED HEADLIGHT KIT
 STRIPING KIT
 POWERED BAGGER KIT
 OCDB KIT
 SUNSHADE KIT
 REAR TWEEL KIT
 RADIAL DRIVE CONVERSION KIT
 LASEREDGE BLADES
 TUNE UP KIT
 POLY SIDE GRASS CATCHER
 ELECTRIC DECK LIFT
 ENTRY ASSIST HANDLE
 FRONT TWEELS
 GRAVELLY EQUIPMENT COVER
 FRONT WEIGHT KIT

GRAVELLY®

GRAVELLY.COM

AN ARIENS|CO BRAND

© Copyright 2022 AriensCo. All rights reserved. Registered trademark and ™ trademark of Ariens Company, Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravelly.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.