

# RAFT TRAILERS

10' & 12'



**10' & 12'**

## STANDARD FEATURES

- > All-Aluminum Construction
- > 24" O/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > 6000# Straight Coupler w/ 2" Ball
- > (2) 5000# Safety Chains
- > Dexter Torsion Ride Axles
- > 5/4" Pressure Treated Decking
- > Rear Roller w/Bearings
- > Manual Winch w/ 24" Post
- > (5) Tie-Down Points, per side
- > (2) Front Tie-Down Points
- > Recessed LED Marker Lights
- > Limited 4-Year Warranty

## STANDARD SPECIFICATIONS

TRAILER MODEL	10' RAFT	12' RAFT
Model Number	MRFT84x10	MRFT84x12
Deck (WxL)	84"x10'	84"x12'
Overall (WxL)	84"x14'	84"x16'
Deck Height	26"	26"
Hitch Height	21"	21"
Axle(s) - Qty/Rating	1-2200# Idler	1-2200# Idler
Wheels	13" Silver Mods	13" Silver Mods
Tires	175/80R13	175/80R13
GVWR	2200#	2200#
Curb Weight	540#	590#
Payload	1660#	1610#
Power Connection	4-Way Flat	4-Way Flat

## OPTIONS & ACCESSORIES (Expanded list of available options can be found in MES option Section)

TIRE/WHEEL ASSEMBLIES & ACCESSORIES
Spare 13" Silver Mod Wheel w/ 175/80R13 Tire
Upgrade to 13" Aluminum (Radial; From 13" Silver Mod Wheels)
Bolt-On Spare Tire Carrier (Tongue-Mounted)
CONSTRUCTION OPTIONS
Tilt Bed Option (For Raft Trailer ) (Pin System)
Anti-Rattle Tilt Bed Option (For Raft Trailer)
Upgrade to 36" Winch Post (Replaces 24" Winch Post) (Raft Trailer)

FLOORING OPTIONS
Upgrade to 3/4" Quad Ply Decking (Non-Skid Surface, FRP Backer; PBF)
TIE DOWN OPTIONS
D-Rings for Raft Trailer (Bolt-On)
Welded Side Tie Down Ring
Light Duty Surface-Mounted D-Ring (Installed)
ACCESSORIES
Add 1200# Tongue-Mounted Wheel Jack