



PSTF2 400

Submersible Pump

Durable, lightweight and perfect for any job

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

Highlights

- Lightweight, compact design
- Built-in thermal protection prevents motor damage
- Durable mechanical seals

Technical Data

■ Mechanical - Output Details

| | |
|----------------------|-------------|
| Flow rate max. | 200.0 l/min |
| Solid diameter max. | 7.0 mm |
| Delivery height max. | 12.0 m |

■ Mechanical Details

| | |
|------------------------------|----------|
| Length | 255.0 mm |
| Width | 185.0 mm |
| Height | 328.0 mm |
| Operating weight | 11.3 kg |
| Intake-/Pressure socket-dia. | 50.0 mm |

■ Motor

| | |
|-----------------|---------|
| Nominal power | 0.40 KW |
| Nominal current | 5.4 A |
| Nominal voltage | 110.0 V |

| | |
|-------------------|---------------|
| Nominal frequency | 60.0 Hz |
| Nominal speed | 3,321.0 1/min |
| Phase | 1.0 ~ |

■ Environment Data

| | |
|-----------------------------|---------|
| Temp. limit borrowed liquid | 40.0 °C |
|-----------------------------|---------|

■ Electrical System

| | |
|---------------------|---------------------|
| Length Cable | 6.2 m |
| Cable cross-section | 1.3 mm ² |
| Cable definition | PVC Sheath |

■ Shipping and Storage

| | |
|---------------------|----------|
| Length for shipping | 410.0 mm |
| Width for shipping | 255.0 mm |
| Height for shipping | 217.0 mm |
| Shipping weight | 16.6 kg |