ER636H
COMPACT HYDRAULIC EXCAVATOR

**BUILT FOR PERFORMANCE.
DESIGNED FOR RESULTS.**



SDLG ER636H Excavator (Base Machine)	**$66,000.00**
Freight / Transportation	**$799.99**
Pre-Delivery Inspection (PDI) & Setup	**$618.99**
Documentation / Admin Fee	**$230.99**
TOTAL FEES	**$1,649.97**
TOTAL SELLING PRICE (Before Taxes)	**$67,649.97**
HST (15% - New Brunswick)	**$10,147.50**
TOTAL PRICE (Taxes Included)	**$77,797.47**

Registration and delivery to customer (if required) extra.

SPECIFICATIONS - MANUAL FIRST, NA SPEC FOR GAPS

Operating weight	**4,010 kg (8,842 lb)**
Engine model	**D1703BM-DI-EF04 (Kubota D1703 family)**
Rated power / speed	**18.2 kW (24.4 hp) @ 2,200 rpm**
Engine displacement	**1.647 L (100.5 cu in)**
Pump capacity	**88 L/min (23.3 US gal/min)**
Hydraulic working pressure	**24 MPa (240 bar / 3,480 psi)**
Max. bucket digging force	**32 kN (7,194 lbf)**
Max. arm digging force	**23.5 kN (5,283 lbf)**
Travel speed - low / high	**2.1 / 3.7 km/h (1.3 / 2.3 mph)**
Maximum gradeability	**57% (about 30°)**
Maximum slewing speed	**9 rpm**
Standard bucket capacity	**0.12 m³ (0.16 yd³)**
Bucket capacity range	**0.08-0.16 m³**
Blade (W x H)	**1,700 x 350 mm (66.9 x 14 in)**
Average ground pressure	**35.3 kPa (5.1 psi)**
Fuel tank	**45 L (11.9 US gal)**

WORKING RANGE - ER636H-NA-CAB MANUAL

Maximum excavation radius	**5,355 mm (211.0 in)**
Maximum ground excavation range	**5,240 mm (206.5 in)**
Maximum excavation height	**4,660 mm (183.6 in)**
Maximum unloading height	**3,340 mm (131.6 in)**
Maximum excavation depth	**3,110 mm (122.5 in)**
Maximum vertical excavation depth	**2,140 mm (84.3 in)**
Max. depth at 2.5 m flat bottom	**2,610 mm (102.8 in)**

DIMENSIONS

Total length	**4,890 mm (192.7 in)**
Overall width	**1,700 mm (67.0 in)**
Total height	**2,675 mm (105.4 in)**
Upper assembly width	**1,560 mm (61.5 in)**
Track shoe width	**300 mm (11.8 in)**
Tail turning radius	**860 mm (33.9 in)**
Track wheelbase	**1,700 mm (67.0 in)**
Track length	**2,150 mm (84.7 in)**
Upper assembly ground clearance	**550 mm (21.7 in)**
NA spec shipping size (L x W x H)	**4,890 x 1,700 x 2,524 mm**

STANDARD / VERIFIED FEATURES

- Load-sensitive hydraulic system with pilot control
- High-traction travel motor
- X1/X3 auxiliary pipelines (official SDLG feature listing)
- Auxiliary pipelines with 5 quick connectors (official SDLG feature listing)
- ROPS-certified enclosed cab; three LED work lights (official SDLG cab listing)
- Centrally located filters for easier maintenance
- Dozer blade and boom deflection

WARRANTY

5 Years / 5,000 Hours
Factory-warranty term is advertised in North American ER636H dealer listings. Confirm eligibility, start date and coverage terms for the specific serial number before sale.

Verification basis: ER636H-NA-CAB Operation & Maintenance Manual (Jan. 2025) controls where it provides a value. Missing specifications are filled from the SDLG North America ER636H specification sheet / official SDLG ER636H feature pages. Where regional online values conflict with the NA-CAB manual (for example operating weight or ground pressure), the NA-CAB manual value is used.

YARD GEAR
1318 Hanwell Road, Fredericton, NB E3C 1A5
506-742-7772 | www.yardgear.ca

**EQUIPMENT PEOPLE
CAN COUNT ON.**